

EXHIBIT 46
ENVIRONMENTAL AND RADIO FREQUENCY EXPOSURE STATEMENT
MEREDITH CORPORATION
MINOR CHANGE IN CONSTRUCTION PERMIT BPCDT20080225ABE
WHNS-DT, GREENVILLE, SOUTH CAROLINA
CH 21, 400.0 KW-D, 482.5 MTR. AGL

The proposed modification of construction permit BPCDT20080225ABE will not involve any changes to proposed location of the post transition digital antenna on the existing tower. No change in tower location or height is proposed and, therefore, will not result in any environmental impact.

The WHNS post-transition digital facility, operating on channel 21, was evaluated in terms of potential radio frequency (RF) energy exposure at ground level to workers and the general public. The radiation center for the antenna is located 482.5 meters above ground level. An average power level of 400.0 kW ERP was utilized in the calculations. A minimum conservative relative field value of 0.20 is assumed for the antenna's downward radiation. The calculated power density at a point 2 meters (6.6 feet) above ground level is 0.002 mW/cm² which is 0.13% of the FCC's recommended limit of 1.72 mW/cm² for an occupational/controlled environment and 0.67% of 0.34 mW/cm² for general public/uncontrolled exposure.

The total contribution of all nearby, existing and the proposed facilities was also evaluated in terms of potential radio frequency (RF) energy exposure at ground level to workers and the general public. Total contribution was calculated to be well within the allowable exposure limit for both workers and the general public.

Access to the transmitting tower and any radio frequency generating equipment is restricted and appropriately marked with warning signs. In the event that workers or other authorized personnel enter restricted areas or climb the tower, appropriate measures will be taken to assure worker safety with respect to radio frequency radiation exposure. Such measures include reducing the average exposure by spreading out the work over a longer period of time, wearing "accepted" RFR protective clothing and/or RFR exposure monitors or scheduling work when the stations are at reduced power or shut down.

