

RF HAZARD STATEMENT

FM TRANSLATOR STATION W286DL  
AGUADILLA, PUERTO RICO  
CHANNEL 286

With respect to the potential for human exposure to radio frequency (RF) energy, calculations prepared in accordance with FCC Bulletin OET-65 (Edition 97-01)<sup>\*</sup> indicate that the proposal will not result in human exposure to RF energy at ground level in excess of FCC standards. The calculation of RF energy at 2-m above ground was made using the following formula from the OET-65 document:

$$S = \frac{(33.4)F^2P}{R^2}$$

where,  $S$  = power density in  $\mu\text{W}/\text{cm}^2$ ,  $F$  = relative field factor at the angle to the calculation point,  $P$  = the total effective radiated power relative to a dipole in watts, and  $R$  = distance from the antenna radiation center to the calculation point in meters. Based on the conservative assumption of a relative field factor of 1.0 with a total effective radiated power of 0.5 kW, and an antenna radiation center height above ground of 23 m, the calculated power density will not exceed  $37.9 \mu\text{W}/\text{cm}^2$ . Therefore, the calculated RF exposure at 2 m above ground will not exceed 19% of the FCC limit of  $200 \mu\text{W}/\text{cm}^2$  for general population / uncontrolled environments.<sup>†</sup>

The transmitter site shall be restricted from access. In the event that personnel are required to climb the tower structure, the proposed FM translator transmissions shall be reduced or terminated as necessary to prevent RF exposure above the FCC recommended limits.

---

<sup>\*</sup> Federal Communications Commission OET Bulletin No. 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields (Edition 97-01, August 1997).

<sup>†</sup> There are no broadcast facilities located closer than 600 m from the proposed transmitter site.