

EXHIBIT 15-I-2 Composite WBUD Ground Conductivity Data

WBUD 1260 kHz Lic DA2U BL921228AA 01-Jan-2007
 NJ TRENTON 5.000 kW 3 Towers 0 Augmentations
 N.Lat: 40 15 56 W.Lon: 74 45 27 24 Measured Cond

' ' means estimated conductivity, from M-3 map.
 'M*' means measured conductivity (main bearing).

All distances are in kilometers (US metric curves)
 All distances are cumulative.
 All radiations are in mV/m at one kilometer

Bearing	Radiation	Region		Region		Region	
		Cond	Dist	Cond	Dist	Cond	Dist
0.0+	801.9	2.0+	57.3	4.0	60.4	2.0	124.9
		4.0	500.0				
4.5+	693.7	2.0+	57.3	4.0	58.0	2.0	130.3
		4.0	307.0	2.0	323.7	4.0	500.0
5.0+	681.3	2.0+	57.3	4.0	57.8	2.0	131.0
		4.0	304.9	2.0	327.2	4.0	500.0
7.0-	631.2	2.0-	30.4	1.0-	70.0	2.0	132.0
		4.0	301.3	2.0	344.6	4.0	500.0
10.0-	554.8	2.0-	30.4	1.0-	70.0	2.0	132.6
		4.0	304.2	2.0	392.7	4.0	500.0
14.5M*	439.2	2.0M*	30.4	1.0M*	70.0	2.0	128.0
		4.0	315.1	2.0	500.0		
15.0+	426.4	2.0+	30.4	1.0+	70.0	2.0	127.3
		4.0	316.5	2.0	500.0		
20.0+	301.2	2.0+	30.4	1.0+	70.0	2.0	120.5
		4.0	326.7	2.0	500.0		
24.0-	207.1	1.5-	1.9	3.0-	29.9	4.0	59.0
		2.0	103.2	4.0	332.2	2.0	442.0
		1.0	448.2	0.5	500.0		
24.5-	196.0	1.5-	1.9	3.0-	29.9	4.0	59.2
		2.0	99.0	4.0	332.9	2.0	413.1
		1.0	449.7	0.5	500.0		
25.0-	185.0	1.5-	1.9	3.0-	29.9	4.0	59.4
		2.0	95.1	4.0	333.1	2.0	385.9
		1.0	451.2	0.5	500.0		
30.0M*	88.0	1.5M*	1.9	3.0M*	29.9	4.0	265.6
		1.0	500.0				
34.0M*	51.7	1.5M*	2.3	3.0M*	30.1	4.0	145.8
		1.0	500.0				

EXHIBIT 15-I-2 (cont.)
Composite WBUD Ground Conductivity Data

WBUD 1260 kHz Lic DA2U BL921228AA 01-Jan-2007
NJ TRENTON 5.000 kW 3 Towers 0 Augmentations
N.Lat: 40 15 56 W.Lon: 74 45 27 24 Measured Cond

Bearing	Radiation	Region		Region		Region	
		Cond	Dist	Cond	Dist	Cond	Dist
35.0+	54.6	1.5+	2.3	3.0+	30.1	4.0	142.3
		1.0	489.8	2.0	500.0		
39.0+	89.4	1.5+	2.3	3.0+	30.1	4.0	132.4
		1.0	461.7	2.0	500.0		
40.0+	98.9	1.5+	2.3	3.0+	30.1	4.0	130.5
		1.0	227.2	2.0	248.5	1.0	457.5
		2.0	500.0				
44.0-	130.3	3.0-	20.1	2.0-	37.5	4.0	125.0
		1.0	207.4	2.0	331.2	1.0	435.9
		2.0	456.3	5000.0	459.1	2.0	500.0
45.0-	135.9	3.0-	20.1	2.0-	37.5	4.0	123.9
		1.0	204.1	2.0	339.5	1.0	426.8
		2.0	455.0	5000.0	457.5	2.0	478.5
		5000.0	500.0				
49.0M*	148.3	3.0M*	20.1	2.0M*	37.5	4.0	94.4
		5000.0	94.6	4.0	120.3	1.0	193.3
		2.0	427.0	5000.0	500.0		
50.0+	148.7	3.0+	20.1	2.0+	37.5	4.0	80.9
		5000.0	83.2	4.0	88.8	5000.0	96.4
		4.0	103.9	5000.0	135.8	1.0	191.0
		2.0	425.4	5000.0	500.0		
54.0M*	140.0	3.0M*	24.9	1.0M*	37.0	4.0	72.0
		5000.0	79.6	0.5	81.4	4.0	99.7
		5000.0	104.4	4.0	111.6	5000.0	115.9
		4.0	121.4	5000.0	191.3	2.0	385.0
		5000.0	500.0				
55.0+	135.2	3.0+	24.9	1.0+	37.0	4.0	47.3
		5000.0	47.7	4.0	71.6	5000.0	77.2
		0.5	86.3	4.0	101.1	5000.0	102.7
		4.0	111.3	5000.0	114.3	4.0	130.6
		5000.0	192.5	2.0	396.7	5000.0	500.0
56.0+	129.4	3.0+	24.9	1.0+	37.0	4.0	47.5
		5000.0	49.7	4.0	71.2	5000.0	75.1
		0.5	91.8	4.0	110.9	5000.0	112.7
		4.0	131.7	5000.0	136.4	4.0	137.2
		5000.0	200.6	2.0	398.5	5000.0	500.0

EXHIBIT 15-I-2 (cont.)
Composite WBUD Ground Conductivity Data

WBUD 1260 kHz Lic DA2U BL921228AA 01-Jan-2007
NJ TRENTON 5.000 kW 3 Towers 0 Augmentations
N.Lat: 40 15 56 W.Lon: 74 45 27 24 Measured Cond

Bearing	Radiation	Region		Region		Region	
		Cond	Dist	Cond	Dist	Cond	Dist
59.0+	106.5	3.0+	24.9	1.0+	37.0	4.0	48.1
		5000.0	57.1	4.0	59.6	5000.0	73.7
		0.5	142.8	4.0	143.4	5000.0	221.3
		2.0	232.2	5000.0	234.5	2.0	327.3
		5000.0	330.2	2.0	393.7	5000.0	500.0
60.0+	97.4	3.0+	24.9	1.0+	37.0	4.0	48.3
		5000.0	73.4	0.5	86.1	5000.0	87.7
		0.5	144.8	5000.0	156.7	0.5	158.8
		5000.0	229.8	2.0	230.9	5000.0	234.7
		2.0	245.5	5000.0	247.5	2.0	255.8
		5000.0	256.1	2.0	319.6	5000.0	332.1
		2.0	338.4	5000.0	339.1	2.0	393.4
		5000.0	500.0				
64.0-	59.2	3.0-	19.6	2.0-	49.2	4.0	49.4
		5000.0	93.5	0.5	182.7	5000.0	217.6
		0.5	233.6	5000.0	287.1	2.0	299.5
		5000.0	302.9	2.0	306.1	5000.0	329.1
		2.0	340.7	5000.0	342.7	2.0	353.7
		5000.0	359.3	2.0	368.4	5000.0	380.3
		2.0	398.2	5000.0	435.7	2.0	439.6
65.0-	52.7	3.0-	19.6	2.0-	49.2	4.0	49.7
		5000.0	88.9	0.5	191.7	5000.0	203.7
		0.5	219.1	5000.0	345.7	2.0	350.3
		5000.0	376.7	2.0	407.5	5000.0	432.9
		2.0	438.8	5000.0	500.0		
66.0M*	50.2	3.0M*	19.6	2.0M*	49.2	4.0	50.7
		5000.0	91.9	0.5	210.6	5000.0	373.2
		2.0	394.1	5000.0	397.4	2.0	434.1
		5000.0	434.6	2.0	437.4	5000.0	500.0
70.0+	88.9	3.0+	19.6	2.0+	49.2	4.0	59.7
		5000.0	156.1	0.5	201.6	5000.0	205.5
		0.5	234.6	5000.0	500.0		
75.0+	187.0	3.0+	19.6	2.0+	49.2	4.0	67.4
		5000.0	500.0				
76.0+	209.3	3.0+	19.6	2.0+	49.2	4.0	67.2
		5000.0	500.0				
80.0-	303.8	2.0-	50.4	0.5-	64.9	4.0	66.5
		5000.0	500.0				
85.0-	429.5	2.0-	50.4	0.5-	64.9	4.0	66.0
		5000.0	500.0				
90.0M*	558.1	2.0M*	50.4	0.5M*	64.9	5000.0	500.0

EXHIBIT 15-I-2 (cont.)
Composite WBUD Ground Conductivity Data

WBUD 1260 kHz Lic DA2U BL921228AA 01-Jan-2007
NJ TRENTON 5.000 kW 3 Towers 0 Augmentations
N.Lat: 40 15 56 W.Lon: 74 45 27 24 Measured Cond

Bearing	Radiation	Region		Region		Region	
		Cond	Dist	Cond	Dist	Cond	Dist
95.0+	684.9	2.0+	50.4	0.5+	64.9	5000.0	500.0
100.0+	805.6	2.0+	50.4	0.5+	64.9	5000.0	500.0
105.0-	917.1	1.5-	29.9	0.5-	58.9	4.0	64.1
		5000.0	500.0				
110.0M*	1016.7	1.5M*	29.9	0.5M*	58.9	4.0	62.9
		5000.0	500.0				
115.0+	1102.8	1.5+	29.9	0.5+	58.9	4.0	64.2
		5000.0	500.0				
120.0+	1174.1	1.5+	29.9	0.5+	58.9	4.0	65.6
		5000.0	500.0				
125.0	1229.9	4.0	68.1	5000.0	500.0		
130.0-	1269.9	3.0-	31.7	4.0	71.5	5000.0	500.0
135.0-	1293.9	3.0-	31.7	4.0	73.5	5000.0	500.0
140.0M*	1302.0	3.0M*	31.7	4.0	80.2	5000.0	500.0
145.0+	1293.9	3.0+	31.7	4.0	82.5	5000.0	500.0
150.0+	1269.9	3.0+	31.7	4.0	83.9	5000.0	500.0
155.0-	1229.9	2.0-	27.0	0.5-	79.7	4.0	90.9
		5000.0	500.0				
160.0M*	1174.1	2.0M*	27.0	0.5M*	79.7	4.0	94.1
		5000.0	500.0				
162.0+	1147.4	2.0+	27.0	0.5+	79.7	4.0	95.0
		5000.0	500.0				
165.0+	1102.8	2.0+	27.0	0.5+	79.7	4.0	97.3
		5000.0	98.7	4.0	101.5	5000.0	500.0
170.0-	1016.7	2.0-	42.5	0.1-	83.7	4.0	107.8
		5000.0	500.0				
172.0M*	978.4	2.0M*	42.5	0.1M*	83.7	4.0	106.1
		5000.0	110.0	4.0	113.1	5000.0	500.0
175.0+	917.1	2.0+	42.5	0.1+	83.7	4.0	103.9
		5000.0	105.6	4.0	118.8	5000.0	500.0
180.0-	805.6	2.0-	40.6	1.0-	69.8	4.0	134.2
		5000.0	500.0				
182.0-	758.3	2.0-	40.6	1.0-	69.8	4.0	144.6
		5000.0	500.0				
185.0M*	684.9	2.0M*	40.6	1.0M*	69.8	4.0	123.2
		5000.0	124.6	4.0	148.6	5000.0	500.0

EXHIBIT 15-I-2 (cont.)
Composite WBUD Ground Conductivity Data

WBUD 1260 kHz Lic DA2U BL921228AA 01-Jan-2007
NJ TRENTON 5.000 kW 3 Towers 0 Augmentations
N.Lat: 40 15 56 W.Lon: 74 45 27 24 Measured Cond

Bearing	Radiation	Region		Region		Region	
		Cond	Dist	Cond	Dist	Cond	Dist
190.0M*	558.1	3.0M*	27.4	2.0M*	40.9	1.0M*	80.0
		4.0	120.9	5000.0	165.2	4.0	180.9
		2.0	232.2	5000.0	499.2	4.0	500.0
195.0+	429.5	3.0+	27.4	2.0+	40.9	1.0+	80.0
		4.0	124.4	5000.0	159.4	4.0	187.6
		2.0	317.2	5000.0	405.5	4.0	411.3
		5000.0	420.1	4.0	428.9	5000.0	437.6
		4.0	461.0	5000.0	466.6	4.0	475.0
200.0-	303.8	5000.0	491.3	4.0	500.0		
		2.0-	52.0	1.0-	87.7	4.0	118.3
		5000.0	146.1	4.0	195.7	2.0	256.8
		5000.0	257.1	2.0	276.2	5000.0	391.1
		4.0	396.4	5000.0	400.4	4.0	498.4
204.0-	209.3	5000.0	500.0				
		2.0-	52.0	1.0-	87.7	4.0	116.5
		5000.0	138.3	4.0	201.8	2.0	245.8
		5000.0	252.1	2.0	256.2	5000.0	336.9
		2.0	349.2	5000.0	358.3	2.0	363.7
205.0M*	187.0	5000.0	370.3	2.0	381.2	4.0	387.6
		5000.0	395.9	4.0	437.0	2.0	500.0
		2.0M*	52.0	1.0M*	87.7	4.0	115.7
		5000.0	129.5	4.0	203.6	2.0	233.6
		5000.0	329.5	2.0	334.9	5000.0	335.5
210.0-	88.9	2.0	347.0	5000.0	348.1	2.0	352.5
		5000.0	354.6	2.0	366.5	5000.0	369.7
		2.0	386.0	4.0	386.8	5000.0	394.4
		2.0	500.0				
		4.0-	29.9	3.0-	60.0	4.0	112.3
214.0M*	50.2	5000.0	119.7	4.0	213.9	2.0	246.2
		5000.0	275.9	4.0	280.5	5000.0	292.3
		4.0	320.0	5000.0	325.4	2.0	352.9
		5000.0	355.7	2.0	385.0	5000.0	388.2
		2.0	500.0				
214.0M*	50.2	4.0M*	29.9	3.0M*	60.0	4.0	110.4
		5000.0	117.8	4.0	214.5	40.0	219.9
		4.0	224.3	40.0	227.3	5000.0	231.4
		2.0	242.5	5000.0	261.1	4.0	279.3
		5000.0	287.2	4.0	316.6	5000.0	319.2
		2.0	500.0				

EXHIBIT 15-I-2 (cont.)
Composite WBUD Ground Conductivity Data

WBUD 1260 kHz Lic DA2U BL921228AA 01-Jan-2007
NJ TRENTON 5.000 kW 3 Towers 0 Augmentations
N.Lat: 40 15 56 W.Lon: 74 45 27 24 Measured Cond

Bearing	Radiation	Region		Region		Region	
		Cond	Dist	Cond	Dist	Cond	Dist
215.0+	52.7	4.0+	29.9	3.0+	60.0	4.0	109.8
		5000.0	117.4	4.0	208.5	40.0	221.2
		4.0	226.3	40.0	230.0	5000.0	238.4
		2.0	240.1	5000.0	250.7	4.0	258.4
		5000.0	262.7	4.0	279.4	5000.0	285.8
		4.0	314.7	5000.0	317.8	2.0	500.0
220.0+	97.4	4.0+	29.9	3.0+	60.0	4.0	100.4
		5000.0	109.3	4.0	188.4	40.0	188.8
		4.0	195.2	40.0	237.2	4.0	256.3
		5000.0	260.1	4.0	280.9	5000.0	297.2
		4.0	313.4	2.0	500.0		
221.0+	106.5	4.0+	29.9	3.0+	60.0	4.0	99.8
		5000.0	105.6	4.0	184.0	40.0	185.9
		4.0	192.0	40.0	232.7	4.0	257.5
		5000.0	259.5	4.0	278.2	5000.0	281.5
		4.0	286.0	5000.0	293.4	4.0	312.6
		2.0	500.0				
224.0-	129.4	3.0-	29.9	1.0-	65.0	5000.0	66.0
		4.0	94.8	5000.0	104.6	4.0	175.4
		40.0	178.9	4.0	183.0	40.0	217.7
		4.0	282.9	5000.0	285.9	4.0	310.1
		2.0	500.0				
225.0-	135.2	3.0-	29.9	1.0-	65.0	5000.0	68.7
		4.0	88.0	5000.0	104.3	4.0	181.5
		40.0	209.7	4.0	210.5	40.0	213.6
		4.0	214.3	40.0	217.9	4.0	283.7
		5000.0	295.6	4.0	308.4	2.0	500.0
230.0-	148.7	3.0-	29.9	1.0-	65.0	4.0	123.1
		40.0	193.4	4.0	201.2	40.0	201.7
		4.0	205.6	40.0	206.7	4.0	254.8
		5000.0	257.3	4.0	276.7	5000.0	277.0
		4.0	290.0	2.0	500.0		
231.0M*	148.3	3.0M*	29.9	1.0M*	65.0	4.0	119.6
		40.0	120.9	4.0	138.4	40.0	195.3
		4.0	206.1	40.0	206.6	4.0	250.9
		5000.0	253.8	4.0	278.3	2.0	500.0
235.0+	135.9	3.0+	29.9	1.0+	65.0	4.0	136.4
		40.0	139.8	4.0	156.3	40.0	159.5
		4.0	182.0	40.0	182.2	4.0	191.7
		40.0	196.0	4.0	220.3	2.0	500.0
236.0-	130.3	2.0-	79.8	4.0	194.6	40.0	196.7
		4.0	207.7	2.0	500.0		
240.0M*	98.9	2.0M*	79.8	4.0	181.4	2.0	500.0

EXHIBIT 15-I-2 (cont.)
Composite WBUD Ground Conductivity Data

WBUD	1260 kHz	Lic	DA2U	BL921228AA	01-Jan-2007
NJ	TRENTON		5.000 kW	3 Towers	0 Augmentations
N.Lat:	40 15 56	W.Lon:	74 45 27		24 Measured Cond

Bearing	Radiation	Region		Region		Region	
		Cond	Dist	Cond	Dist	Cond	Dist
241.0+	89.4	2.0+	79.8	4.0	177.7	2.0	500.0
245.0-	54.6	3.5-	9.7	5.0-	30.4	4.0	176.5
		2.0	500.0				
246.0M*	51.7	3.5M*	9.7	5.0M*	30.4	4.0	179.1
		2.0	500.0				
250.0M*	88.0	4.0M*	49.9	5.0M*	86.6	4.0	199.4
		2.0	500.0				
255.0+	185.0	4.0+	49.9	5.0+	86.6	4.0	221.0
		2.0	320.6	4.0	481.5	2.0	500.0
256.0+	207.1	4.0+	49.9	5.0+	86.6	4.0	218.9
		2.0	312.9	4.0	496.7	2.0	500.0
260.0-	301.2	2.0-	78.9	4.0	204.1	2.0	286.3
		4.0	485.5	2.0	500.0		
265.0M*	426.4	2.0M*	78.9	4.0	187.9	2.0	267.7
		4.0	464.4	2.0	500.0		
270.0+	554.8	2.0+	78.9	4.0	176.7	2.0	256.0
		4.0	330.2	2.0	340.3	4.0	500.0
273.0+	631.2	2.0+	78.9	4.0	170.0	2.0	251.3
		4.0	316.7	2.0	358.6	4.0	500.0
275.0-	681.3	4.0-	23.7	2.0-	64.5	4.0	163.8
		2.0	250.1	4.0	310.7	2.0	371.1
		4.0	518.3				
280.0-	801.9	4.0-	23.7	2.0-	64.5	4.0	148.7
		2.0	251.1	4.0	298.2	2.0	406.4
		4.0	473.3	8.0	500.0		
283.0M*	870.0	4.0M*	23.7	2.0M*	64.5	4.0	129.2
		2.0	261.0	4.0	287.4	2.0	436.6
		4.0	456.2	8.0	500.0		
285.0+	913.2	4.0+	23.7	2.0+	64.5	4.0	120.3
		2.0	451.4	8.0	500.0		
290.0+	1012.8	4.0+	23.7	2.0+	64.5	4.0	108.5
		2.0	448.6	8.0	500.0		
293.0-	1066.2	1.5-	32.0	2.0-	78.1	4.0	103.0
		2.0	448.0	8.0	452.3	4.0	500.0
295.0-	1098.9	1.5-	32.0	2.0-	78.1	4.0	99.7
		2.0	436.0	4.0	504.4		
300.0M*	1170.2	1.5M*	32.0	2.0M*	78.1	4.0	94.1
		2.0	245.8	4.0	472.3	8.0	501.0

EXHIBIT 15-I-2 (cont.)
Composite WBUD Ground Conductivity Data

WBUD	1260 kHz	Lic	DA2U	BL921228AA	01-Jan-2007
NJ	TRENTON		5.000 kW	3 Towers	0 Augmentations
N.Lat:	40 15 56	W.Lon:	74 45 27		24 Measured Cond

Bearing	Radiation	Region		Region		Region	
		Cond	Dist	Cond	Dist	Cond	Dist
305.0+	1226.0	1.5+	32.0	2.0+	78.1	4.0	90.0
		2.0	204.9	4.0	434.2	8.0	471.0
		10.0	500.0				
310.0+	1266.0	1.5+	32.0	2.0+	78.1	4.0	87.0
		2.0	132.2	4.0	425.2	8.0	453.7
		10.0	460.2	20.0	500.0		
315.0-	1290.1	2.5-	30.9	1.0-	76.9	4.0	85.5
		2.0	123.4	4.0	411.4	8.0	501.3
320.0M*	1298.1	2.5M*	30.9	1.0M*	76.9	4.0	84.8
		2.0	119.1	4.0	367.2	8.0	488.3
		15.0	500.0				
325.0+	1290.1	2.5+	30.9	1.0+	76.9	4.0	84.7
		2.0	116.0	4.0	395.8	8.0	457.9
		15.0	500.0				
330.0+	1266.0	2.5+	30.9	1.0+	76.9	4.0	85.3
		2.0	113.8	4.0	392.0	8.0	430.8
		15.0	484.2	4.0	486.5	6.0	500.0
335.0	1226.0	4.0	86.1	2.0	112.6	4.0	378.7
		8.0	411.1	15.0	444.0	4.0	500.0
340.0	1170.2	4.0	84.5	2.0	112.4	4.0	385.9
		8.0	429.0	15.0	465.8	10.0	481.3
		4.0	500.0				
345.0	1098.9	4.0	77.6	2.0	114.0	4.0	424.2
		8.0	427.3	4.0	431.9	8.0	438.9
		4.0	453.7	15.0	465.3	10.0	493.1
		4.0	500.0				
347.0-	1066.2	2.0-	57.3	4.0	74.0	2.0	114.9
		4.0	463.4	15.0	465.3	10.0	499.0
		4.0	500.0				
350.0-	1012.8	2.0-	57.3	4.0	69.4	2.0	116.5
		4.0	475.4	10.0	500.0		
355.0-	913.2	2.0-	57.3	4.0	64.3	2.0	120.1
		4.0	508.8				
357.0M*	870.0	2.0M*	57.3	4.0	62.6	2.0	121.9
		4.0	500.0				