

ENGINEERING REPORT

FM Translator “Long Form” Filing for Original Construction Permit Application

NEW288D – Portland, ME
File No. BNPFT-20030317GVE
Facility ID No. 150422

Long-Form “Singleton Filing pursuant
to Auction 83 (AUC-03-83-D)

July, 2013

COPYRIGHT 2013

MUNN-REESE, INC.
Broadcast Engineering Consultants
Coldwater, MI 49036

Table of Contents

Discussion of Report

FM Booster/Fill-in Translator Requirements (See Discussion)

Interference Requirements

Exhibit 13.1 - Copy of Existing Antenna Structure Registration

Exhibit 13.2 - Vertical Plan of Existing Tower Structure

Exhibit 13.3 - Licensed vs Proposed Service Contour Study

Exhibit 13.4 - Proposed vs Primary Station Service Contour Study

Contour Overlap Requirements

Exhibit 13.5 - Tabulation of Proposed Allocation

Exhibit 13.6 - Contour Protection Studies Toward APP288D - Lewiston, ME

Exhibit 13.7a - §74.1204(d) Waiver Request toward WBCI(FM) "Vertical Pattern Study"

Exhibit 13.7b - §74.1204(d) Waiver Request toward WBCI(FM) "Aerial Photograph Study"

Exhibit 13.8 - Manufacturer's Vertical Radiation Pattern Documentation

TV Channel 6 Protection Requirements (See Discussion)

Unattended Operation Requirements (See Discussion)

Multiple Translator Requirements (See Discussion)

RF Radiation Study Requirement

Exhibit 17.1 - RF Compliance Study

(Exhibit numbering is in response to FCC Online Form 349, Section III-A)

Discussion

This firm has been retained to prepare the required engineering report in support of an original Construction Permit “Long Form” Filing for FM Translator Application BNPFT-20030317GVE (Facility ID No. 150422). The pending “Short-Form” Application specified operation on CH288D (105.5 MHz) – Portland, ME with 0.013 kW of non-directional power at an antenna COR of 126.6 meters AMSL. Revised Operating Parameters will be requested in this “Long-Form” Filing. Continued operation on Channel CH288D (105.5 MHz) with a power of 0.019 kW ERP is requested from the same site location. A circularly polarized non-directional antenna will be utilized at the new antenna COR height of 111 meters AMSL. The translator will rebroadcast primary station WMGX(FM) – Portland, ME, CH226B-HD3 (Facility ID No. 58548) as an FM HD3 Fill-In Translator.

The facility will be located on an existing tower which bears Antenna Structure Registration Number 1219887. A copy of ASR #1219887 has been included in **Exhibit 13.1**. The vertical antenna system has been plotted in **Exhibit 13.2**. As this proposal will not increase the overall tower height, it is believed the FAA need not be notified.

It has been determined the translator may be used in the area without interference to any existing FM broadcast station or facility with the exception of WBCI(FM) – Bath, ME (CH290B). General allocation details are found in **Exhibit 13.5**. A §74.1204(d) Second Adjacent Channel Given Interference Waiver is requested toward WBCI(FM) as included in **Exhibit(s) 13.7a&b**. Full protection will be afforded WBCI(FM) as the calculated interference area beyond 145 meters will not reach the ground nor a two meter artificial plane representing a standard human at ground level when taking into account the downward radiation characteristics of the antenna as supplied by the antenna manufacturer. The portion of the §74.1204(d) WBCI(FM) protection within 145 meters of the site is currently void of population, buildings (with the exception of the dedicated transmitter building) or major roads as noted in **Exhibit 13.7b**. There is one (1) facility, existing or proposed, close enough to merit further study. Therefore supplemental contour protection studies have been provided toward co-channel protection APP288D – Lewiston, ME (BNPFT-20030317DOX) as included in **Exhibit 13.6**. It is believed sufficient clearance exists precluding the need for additional contour protection showings.

The applicant would like to note the use of the NGDC 30 second terrain database for all allocation, contour and HAAT calculations contained here-in.

The proposed 54 dB μ contour of the Translator lies wholly inside of the WMGX(FM) Class B primary 54 dB μ contour. A map of the proposed service contour in relation to the primary station service contour has been included in **Exhibit 13.4**. The Translator will rebroadcast WMGX(FM) as an FM HD3 Fill-In Translator.

The proposed operating parameters have been changed from the original “Short-Form” values, however the proposed service contour serves a portion of the present service area as seen in **Exhibit 13.3**.

Discussion (continued)

RADIATION PROTECTION: The Commission requires an engineering study regarding compliance with the guidelines for human protection from radiofrequency radiation. This report section is in response to that provision of the Rules. The current Federal Communications Commission guidelines for RF radiation protection are set forth in OET Bulletin No. 65 (Edition 97-01), and the accompanying Supplement A, (Edition 97-01).

The FM Broadcast facility proposed in this application will not produce human exposure to radiofrequency radiation in excess of the applicable safety standards specified in §1.1307(b)(3) of the Commission's rules concerning RF contributors of less than 5%. ***Exhibit 17.1*** provides the details of the study that was made to demonstrate compliance. The facility is properly marked with signs, and entry is restricted by means of fencing with locked doors and/or gates. Any other means as may be required to protect employees and the general public will be employed.

In the event work would be required in proximity to the antenna such that the person or persons working in the area would be potentially exposed to fields in excess of the guidelines set forth in OET Bulletin No. 65 (Edition 97-01), the transmitter power will be reduced or the station will cease operation during the critical period.

DISTANCES TO CONTOURS: The following tabulation of the distances to the proposed service contours results from calculations performed in accordance with §73.313(d) and §73.333 Figure 1 utilizing the NGDC 30 second terrain database.

N. Lat. = 434126.0 W. Lng. = 701905.0						
HAAT and Distance to Contour,						
FCC, FM 2-10 Mi, 51 pts Method - NGDC 30 SEC						
Azi.	AV EL	HAAT	ERP kW	dBk	Field	60-F5
000	68.0	43.0	0.0190	-17.21	1.000	4.44
030	30.0	81.0	0.0190	-17.21	1.000	6.12
060	11.9	99.1	0.0190	-17.21	1.000	6.80
090	3.9	107.1	0.0190	-17.21	1.000	7.07
120	0.0	111.0	0.0190	-17.21	1.000	7.19
150	11.0	100.0	0.0190	-17.21	1.000	6.83
180	14.9	96.1	0.0190	-17.21	1.000	6.69
210	28.0	83.0	0.0190	-17.21	1.000	6.20
240	34.2	76.8	0.0190	-17.21	1.000	5.96
270	52.3	58.7	0.0190	-17.21	1.000	5.26
300	50.4	60.6	0.0190	-17.21	1.000	5.34
330	67.5	43.5	0.0190	-17.21	1.000	4.46
Ave El= 31.01 M HAAT= 79.99 M AMSL= 111						