

[Exhibit 12]

Non-Interference Compliance

Regarding Facility id 148978

Channel 222

Description of Exhibit 12 Contents

This exhibit demonstrates that the proposed facility complies with contour overlap and interference protection provisions in all of the applicable rule sections and that this application for a construction permit is in full compliance with 47 C.F.R. § 74.1204.

This facility will serve as a 1st adjacent fill-in to KEGE. The transmit site is on an unpopulated mountain and as demonstrated, Radio Assist Ministry is confident that this application will be in full compliance with 47 C.F.R. § 74.1203 (d) whereas it will not cause interference within the boundaries of its primary's principal community.

Let it be noted that should any actual real world interference occur, the applicant acknowledges that it will promptly suspend operation of this translator in accordance with 47 C.F.R. § 74.1203.

Page 2 of this exhibit is an explanation of the method used to demonstrate compliance with contour overlap and interference provisions based on 47 C.F.R. § 74.1204(d), which states:

[A]n application otherwise precluded by this section will be accepted if it can be demonstrated that no actual interference will occur due to intervening terrain, lack of population or such other factors as may be applicable.

Page 3 of this exhibit contains the tabulated data from the interference analysis, which shows all stations whose protected contours come within 50 km of the 34 dBμ F(50,10) contour of the proposed translator. These tabulated values were calculated using data from the FCC's CDBS files and 30 arc second terrain data. The column labeled "Adj" shows the number of channels difference between the entry and the proposed translator. The column labeled "Dist" shows the distance in km. The column labeled "Overlap" shows the area of contour overlap in square kilometers.

Page 4 of this exhibit is a portion of a USGS 1:24,000 scale 7.5 minute quadrangle at full scale with the calculated area of interference overlaid. The sheet includes the quadrangle name and measurement scale at the bottom-left corner (note: "Mt" refers to meters). The area of interference was calculated using the free space equation and 120 radials.

Page 5 of this exhibit is a high resolution aerial photo of the vicinity surrounding the proposed translator's tower site provided by the U.S. Geological Survey's National Aerial Photography Program. It has been included to provide clarification of the nature of the buildings in the vicinity.

Compliance with 47 C.F.R. § 74.1204(d)

All authorized second and third adjacent stations with which the proposed translator has contour overlap are tabulated below. Column four show the station's signal level at the proposed translator's tower site, and column five gives the minimum value within the entire standard interfering contour of the proposed translator (100 dBμ for most classes, 94 for class B, 97 for class B1). The minimum second or third adjacent F(50,50) contour within the proposed translator's standard interfering contour was used to calculate the proposed translator's actual "worst-case" interfering contour.

<u>Application_id</u>	<u>File Number</u>	<u>Callsign</u>	<u>Contour at Tower</u>	<u>Min. Contour</u>
1035650	BMPH20041223ABE	KEGE	115	85
	Minimum F(50,50) Contour of Adjacent Station within Proposed Translator's Standard Interfering Contour			85

FCC 02-244 at Section II.A.5 states that "when demonstrating that 'no actual interference will occur due to . . . other factors,' pursuant to Section 74.1204(d), an applicant may use the undesired-to-desired signal ratio method." The undesired-to-desired ratio for first adjacent stations required by § 74.1204(a) is -6 dB. Since the minimum protected contour strength within the proposed translator's standard interference contour is **85 dBμ**, this makes the proposed translator's worst-case interfering contour **79 dBμ**. By the free-space equation, this contour is calculated to extend a maximum of **792 m** from the transmit antenna.

The interfering contour of the proposed translator was calculated for 120 radials and plotted on the pertinent portion of a USGS quadrangle (page 4 of this exhibit). As demonstrated on the quadrangle, there are no populated structures or highways within the area of interference (Note: FCC 02-244 at Section II.A.6 states that USGS quadrangles "have been recognized as acceptable to demonstrate lack of population"). Hence, in accordance with 47 C.F.R. § 74.1204(d) and the clarification provided by the FCC in the decision *Re: Living Way Ministries* (FCC 02-244), a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Antenna Manufacturer: NIC
Antenna Model: BKG77
CORAGL: 18 m
Maximum ERP: 0.001 kW
Interfering Contour: 79 dBμ
Max Int. Contour Distance: 792 m

**Adjacent Channel Study
For Station K275AN, Facility_id: 148978**

Co-channel through third adjacent:

Application_id	Facility_id	Prefix	ARN	Call	Licensee	Class	City	State	Status	ERP	RCAMSL	Channel	Adj	Dist	Overlap
1035650	87656	BMPH	20041223ABE	KEGE	INTERMART BROADCASTING POCATELLO, INC.	C2	POCATELLO	ID	CP MOD	12	1808	221	1	1.3	72.0003
632651	141125	BNPFT	20030317ECI	NEW	MAX T. NICHOLS	D	POCATELLO	ID	APP	0.25	1419	225	3	8.6	0
633337	141684	BNPFT	20030314BNV	NEW	EDUCATIONAL MEDIA FOUNDATION	D	BLACKFOOT	ID	APP	0.25	1420	225	3	39.2	0
93510	30247	BLFT	19861020TN	K221CE	CITICASTERS CO.	D	LAVA HOT SPRINGS	ID	LIC	0.059	1900	221	1	50.3	0
1144598	92376	BLED	20060908AAG	KSQS	FAITH COMMUNICATIONS CORP.	A	RIRIE	ID	LIC	0.25	1706.5	219	3	91.4	0
1232706	173941	BNPED	20071019AIR	NEW	BRIGHAM YOUNG UNIVERSITY - IDAHO	A	BURLEY	ID	APP	0.085	2548	220	2	106.6	0
974139	63832	BLH	20040129AJH	KBLQ-FM	SUN VALLEY RADIO, INC.	C1	LOGAN	UT	LIC	100	1746	225	3	124.6	0

