

Exhibit 35 - Statement B  
**ENVIRONMENTAL CONSIDERATIONS**  
prepared for  
**Univision Radio Stations Group, Inc.**  
**KRGT(FM) Sunrise Manor, Nevada**  
**Ch. 257C2 8.8 kW 351 m**

*Univision Radio Station Group, Inc.* (“*Univision*”) is the licensee of KRGT(FM) (Ch. 257C0, Indian Springs, NV). *Univision* herein proposes to relocate KRGT(FM) to an existing tower with a six (6) bay half wave spaced ERI SHP-6AC-HW antenna side-mounted with a radiation center 49.6 meters above ground with a proposed, circularly polarized effective radiated power (“ERP”) of 8.8 kW.

The use of existing transmitting locations has been characterized as being environmentally preferable by the Commission, according to Note 1 of §1.1306 of the FCC Rules. Because no change in structure height is proposed, no change in current structure marking and lighting requirements is anticipated. Therefore, it is believed that this application may be categorically excluded from environmental processing pursuant to §1.1306 of the Commission’s rules.

### **Human Exposure to Radiofrequency Radiation**

The proposed operation was evaluated for human exposure to radiofrequency energy using the procedures outlined in the Commission's OET Bulletin No. 65 (“OET 65”). OET 65 describes a means of determining whether a proposed facility meets the radiofrequency exposure guidelines adopted in §1.1310. Under present Commission policy, a facility may be presumed to comply with the limits specified in §1.1310 if it satisfies the exposure criteria set forth in OET 65. Based upon that methodology, and as demonstrated in the following, the proposed transmitting system will comply with the cited adopted guidelines.

The general population/uncontrolled maximum permitted exposure (“MPE”) limit specified in §1.1310 for Channel 268 (101.5 MHz) is 200  $\mu\text{W}/\text{cm}^2$ . *Univision* is proposing to use a non-directional, circularly polarized, six bay half-wave paced antenna mounted 49.6 meters above ground level with an ERP of 8.8 kW.

## **Exhibit 35 - Statement B – Environmental Considerations**

*(Page 2 of 3)*

Using the FCC's FM Model program, referring to FCC Public Notice DA 16-340, the ERI antenna SHP-6AC-HW corresponds to the EPA Type 3 Opposed U Dipole antenna set for 6 bays and  $0.5 \lambda$ . With that antenna setting and additional parameters of 49.6m AGL, horizontal and vertical ERPs of 8800 Watts, it was determined that the proposed facility would contribute a worst-case RF power density of  $2.93 \mu\text{W}/\text{cm}^2$  or 0.002  $\mu\text{W}/\text{cm}^2$  or 1.5 percent of the general population/uncontrolled limit.

§1.1307(b)(3) states that facilities at locations with multiple emitters are categorically excluded from responsibility for taking any corrective action in the areas where their contribution is less than five percent of the pertinent MPE limit. Since the instant situation meets the five percent exclusion test at all ground level areas, the impact of any other facilities near this site may be considered independently from this proposal. Accordingly, it is believed that the impact of the proposed operation should not be considered to be a factor at ground level as defined under §1.1307(b).

### **Safety of Tower Workers and the General Public**

As demonstrated herein, excessive levels of RF energy will not be caused by the proposal at publicly accessible areas at ground level near the antenna supporting structure. Consequently, members of the general public will not be exposed to RF levels in excess of the Commission's guidelines. Nevertheless, tower access will continue to be restricted and controlled through the use of a locked gate. According to information provided by the applicant, appropriate RF exposure warning signs are posted. In the event that maintenance or other workers gain access to the tower, power output of the transmitter will be decreased or shut off to protect workers.

With respect to worker safety, it is believed that based on the preceding analysis, excessive exposure would not occur in areas at ground level. A site exposure policy will be employed protecting maintenance workers from excessive exposure when work must be performed on the tower in areas where high RF levels may be present. Such protective measures may include, but will not be limited to, restriction of access to areas where levels in excess of the guidelines may be

## **Exhibit 35 - Statement B – Environmental Considerations**

*(Page 3 of 3)*

expected, power reduction, or the complete shutdown of facilities when work or inspections must be performed in areas where the exposure guidelines would otherwise be exceeded. On-site RF exposure measurements may also be undertaken to establish the bounds of safe working areas. The applicant will coordinate exposure procedures with all pertinent stations. Based on the preceding, it is believed that the instant proposal may be categorically excluded from environmental processing under §1.1306 of the Rules, hence preparation of an Environmental Assessment is not required.

### **Conclusion**

It is therefore believed that the proposed KRGFT(FM) facility satisfies all of the pertinent Commission Rules and Policies now in effect.