

Engineering Statement

The WMMS auxiliary antenna will be located upon an existing tower described by ASR 1015771, which is part of the WHK (AM) array. Licensee acknowledges its responsibility to conduct pre and post construction measurements.

The proposed facilities were evaluated in terms of potential radio frequency radiation exposure at ground level in accordance with OET Bulletin No. 65, "Evaluating Compliance With FCC-Specified Guidelines for Human Exposure to Radio frequency Radiation."

The proposed antenna system is an EPA type 3, 3- bay, "Rototiller " antenna, mounted with its center of radiation 99.4 meters above ground level, and will operate with an effective radiated power of 17.33 Kilowatts in both the horizontal and vertical planes. At 2 meters above ground, at 49 meters from the base of the tower, this proposal will contribute worst case, 12.8 microwatts per square centimeter, or 1.28 percent of the allowable ANSI limit for controlled exposure, and 6.4 percent of the allowable limit for uncontrolled exposure. It is therefore believed that this proposal is in compliance with OET Bulletin Number 65 as required by the Federal Communications Commission.

Further, the applicant will see that signs are posted in the vicinity of the tower, warning of potential radio frequency hazards at the site. The site itself is restricted from public access and there is a fence surrounding the tower which is approximately 6 meters out from the base. The applicant will cooperate with other users of the tower to reduce power of the facility, or discontinue operation, as necessary to limit human exposure to levels less than specified by the Federal Communications Commission should anyone be required to climb the tower for maintenance or inspection.