

Exhibit 15 – Table I  
**FM OVER ANALYSIS**  
**USGS 3 Second Terrain Data**  
 prepared for  
**The Wheeler School**  
 WELH(FM) Providence, Rhode Island  
 Facility ID 66656  
**Ch. 201A 4 kW (Max DA) 41 m**

WELH.Proposed  
 Channel = 201A  
 Max ERP = 4 kW  
 RCAMSL = 71.6 M  
 N. Lat. 41 51 26.7  
 W. Lng. 71 19 05.6  
 Protected  
 60 dBu

WFHL BLED20030623ADC  
 Channel = 201A  
 Max ERP = 0.3 kW  
 RCAMSL = 51 M  
 N. Lat. 41 38 15.0  
 W. Lng. 70 52 19.0  
 Interfering  
 40 dBu

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
063.0	004.0000	0038.1	015.9	324.3	000.3000	0027.3	039.1	33.60	
064.0	004.0000	0037.9	015.9	324.2	000.3000	0027.3	038.8	33.68	
065.0	004.0000	0037.6	015.8	324.0	000.3000	0027.4	038.6	33.77	
066.0	004.0000	0037.2	015.7	323.8	000.3000	0027.5	038.3	33.85	
067.0	004.0000	0036.7	015.6	323.5	000.3000	0027.6	038.1	33.93	
068.0	004.0000	0036.3	015.5	323.3	000.3000	0027.7	037.8	34.01	
069.0	004.0000	0035.9	015.4	323.0	000.3000	0027.8	037.6	34.09	
070.0	004.0000	0035.3	015.3	322.7	000.3000	0028.0	037.4	34.17	
071.0	003.9442	0034.8	015.1	322.3	000.3000	0028.1	037.2	34.24	
072.0	003.8809	0034.5	015.0	322.0	000.3000	0028.1	037.0	34.31	
073.0	003.8259	0034.2	014.9	321.7	000.3000	0028.1	036.8	34.38	
074.0	003.7636	0034.0	014.8	321.4	000.3000	0028.1	036.6	34.45	
075.0	003.7095	0033.7	014.6	321.1	000.3000	0028.1	036.4	34.51	
076.0	003.6557	0033.7	014.6	320.8	000.3000	0028.0	036.2	34.59	
077.0	003.5948	0034.0	014.6	320.7	000.3000	0028.0	035.9	34.67	
078.0	003.5419	0034.5	014.7	320.5	000.3000	0028.0	035.7	34.76	
079.0	003.4820	0034.9	014.7	320.4	000.3000	0027.9	035.5	34.84	
080.0	003.4299	0035.2	014.7	320.2	000.3000	0027.8	035.2	34.92	
081.0	003.2906	0035.5	014.6	319.8	000.3000	0027.6	035.1	34.98	
082.0	003.1542	0035.8	014.5	319.5	000.3000	0027.5	034.9	35.04	
083.0	003.0206	0036.2	014.4	319.1	000.3000	0027.4	034.7	35.10	
084.0	002.8900	0036.5	014.3	318.8	000.3000	0027.3	034.6	35.16	
085.0	002.7622	0036.9	014.2	318.4	000.3000	0027.1	034.4	35.21	
086.0	002.6374	0037.4	014.1	318.0	000.3000	0026.8	034.3	35.27	
087.0	002.5154	0037.9	014.1	317.7	000.3000	0026.5	034.1	35.32	
088.0	002.3963	0038.1	013.9	317.3	000.3000	0026.3	034.0	35.36	
089.0	002.2801	0038.6	013.9	316.9	000.3000	0026.2	033.9	35.41	
090.0	002.1668	0039.4	013.8	316.6	000.3000	0026.2	033.7	35.47	
091.0	002.0794	0039.9	013.8	316.2	000.3000	0026.1	033.6	35.52	
092.0	001.9937	0040.4	013.7	315.9	000.3000	0026.0	033.5	35.57	
093.0	001.9099	0040.7	013.6	315.4	000.3000	0025.9	033.4	35.60	
094.0	001.8279	0040.8	013.5	315.0	000.3000	0025.8	033.3	35.62	
095.0	001.7424	0041.0	013.4	314.6	000.3000	0025.7	033.3	35.65	
096.0	001.6641	0041.2	013.3	314.1	000.3000	0025.6	033.2	35.67	
097.0	001.5876	0041.4	013.2	313.7	000.3000	0025.4	033.2	35.69	
098.0	001.5129	0041.2	013.0	313.2	000.3000	0025.4	033.2	35.68	
099.0	001.4400	0040.3	012.7	312.6	000.3000	0025.2	033.3	35.64	
100.0	001.3689	0039.9	012.5	312.1	000.3000	0025.2	033.4	35.61	
101.0	001.3133	0039.6	012.3	311.6	000.3000	0025.1	033.4	35.60	

**Exhibit 15 – Table I**  
**FM OVER ANALYSIS**  
(page 2 of 5)

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
102.0	001.2589	0039.2	012.1	311.1	000.3000	0025.2	033.4	35.58	
103.0	001.2056	0038.6	011.9	310.6	000.3000	0025.2	033.5	35.55	
104.0	001.1535	0038.3	011.7	310.2	000.3000	0025.0	033.6	35.53	
105.0	001.1025	0038.3	011.6	309.8	000.3000	0024.9	033.6	35.52	
106.0	001.0527	0038.5	011.5	309.4	000.3000	0024.7	033.6	35.52	
107.0	001.0040	0039.2	011.5	309.1	000.3000	0024.4	033.6	35.53	
108.0	000.9565	0040.1	011.5	308.7	000.3000	0024.1	033.5	35.56	
109.0	000.9101	0040.8	011.4	308.4	000.3000	0023.7	033.5	35.57	
110.0	000.8649	0041.4	011.4	308.1	000.3000	0023.2	033.5	35.57	
111.0	000.8317	0041.6	011.3	307.7	000.3000	0022.8	033.5	35.57	
112.0	000.7992	0041.8	011.2	307.3	000.3000	0022.6	033.5	35.56	
113.0	000.7674	0042.3	011.2	307.0	000.3000	0022.4	033.5	35.56	
114.0	000.7362	0042.5	011.1	306.6	000.3000	0022.2	033.5	35.55	
115.0	000.7056	0042.7	011.0	306.3	000.3000	0022.2	033.6	35.53	
116.0	000.6757	0043.0	010.9	305.9	000.3000	0022.4	033.6	35.51	
117.0	000.6464	0043.2	010.9	305.6	000.3000	0022.6	033.7	35.49	
118.0	000.6178	0043.3	010.8	305.2	000.3000	0022.7	033.8	35.46	
119.0	000.5898	0043.5	010.7	304.9	000.3000	0022.8	033.8	35.44	
120.0	000.5625	0043.8	010.6	304.6	000.3000	0022.9	033.9	35.41	
121.0	000.5565	0044.0	010.6	304.3	000.3000	0022.8	033.9	35.41	
122.0	000.5535	0044.1	010.6	304.0	000.3000	0022.7	033.9	35.41	
123.0	000.5476	0044.3	010.6	303.7	000.3000	0022.7	033.9	35.42	
124.0	000.5446	0044.9	010.6	303.3	000.3000	0022.6	033.8	35.44	
125.0	000.5388	0045.5	010.7	303.0	000.3000	0022.6	033.8	35.45	
126.0	000.5358	0045.9	010.7	302.7	000.3000	0022.6	033.8	35.46	
127.0	000.5300	0046.1	010.7	302.4	000.3000	0022.6	033.8	35.46	
128.0	000.5271	0046.2	010.7	302.1	000.3000	0022.7	033.8	35.45	
129.0	000.5213	0046.5	010.7	301.8	000.3000	0022.7	033.8	35.44	
130.0	000.5184	0046.8	010.7	301.4	000.3000	0022.8	033.8	35.44	
131.0	000.5155	0047.3	010.8	301.1	000.3000	0023.0	033.8	35.45	
132.0	000.5127	0047.8	010.8	300.8	000.3000	0023.0	033.8	35.45	
133.0	000.5098	0048.3	010.9	300.4	000.3000	0023.2	033.8	35.45	
134.0	000.5069	0048.7	010.9	300.1	000.3000	0023.3	033.8	35.45	
135.0	000.5013	0049.2	010.9	299.8	000.3000	0023.4	033.8	35.44	
136.0	000.4984	0049.8	011.0	299.5	000.3000	0023.5	033.8	35.44	
137.0	000.4956	0050.3	011.0	299.1	000.3000	0023.6	033.8	35.43	
138.0	000.4928	0051.0	011.1	298.8	000.3000	0023.7	033.9	35.43	
139.0	000.4900	0051.9	011.2	298.4	000.3000	0023.9	033.8	35.43	
140.0	000.4872	0053.2	011.3	298.0	000.3000	0023.9	033.8	35.45	
141.0	000.4679	0055.6	011.4	297.6	000.3000	0023.8	033.7	35.47	
142.0	000.4489	0057.5	011.5	297.3	000.3000	0023.8	033.8	35.46	
143.0	000.4303	0057.1	011.3	297.1	000.3000	0023.7	034.0	35.38	
144.0	000.4122	0056.3	011.1	296.9	000.3000	0023.6	034.3	35.28	
145.0	000.3944	0055.7	011.0	296.8	000.3000	0023.6	034.5	35.19	
146.0	000.3745	0055.7	010.8	296.6	000.3000	0023.6	034.7	35.11	
147.0	000.3576	0056.1	010.8	296.4	000.3000	0023.6	034.9	35.05	
148.0	000.3411	0056.6	010.7	296.2	000.3000	0023.6	035.0	34.99	
149.0	000.3249	0057.1	010.6	296.0	000.3000	0023.7	035.2	34.93	
150.0	000.3091	0057.6	010.5	295.9	000.3000	0023.8	035.4	34.87	
151.0	000.2959	0057.9	010.4	295.7	000.3000	0023.8	035.5	34.81	
152.0	000.2852	0058.3	010.4	295.5	000.3000	0023.9	035.7	34.75	
153.0	000.2725	0058.7	010.3	295.4	000.3000	0023.9	035.9	34.69	
154.0	000.2601	0059.0	010.2	295.2	000.3000	0024.0	036.1	34.62	
155.0	000.2500	0059.3	010.1	295.1	000.3000	0024.1	036.2	34.56	
156.0	000.2381	0059.6	010.0	295.0	000.3000	0024.2	036.4	34.50	
157.0	000.2266	0059.9	009.9	294.9	000.3000	0024.3	036.6	34.43	
158.0	000.2153	0060.2	009.8	294.8	000.3000	0024.4	036.8	34.36	
159.0	000.2061	0060.4	009.7	294.7	000.3000	0024.4	037.0	34.30	
160.0	000.1954	0060.6	009.6	294.7	000.3000	0024.5	037.2	34.23	

**Exhibit 15 – Table I**  
**FM OVER ANALYSIS**  
(page 3 of 5)

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
161.0	000.1954	0060.4	009.6	294.5	000.3000	0024.5	037.3	34.18	
162.0	000.1954	0060.0	009.6	294.4	000.3000	0024.6	037.5	34.13	
163.0	000.1954	0059.4	009.5	294.2	000.3000	0024.7	037.6	34.08	
164.0	000.1954	0057.9	009.4	294.2	000.3000	0024.7	037.8	34.01	
165.0	000.1971	0057.1	009.4	294.1	000.3000	0024.7	038.0	33.96	
166.0	000.1971	0058.5	009.5	293.8	000.3000	0024.9	038.0	33.94	
167.0	000.1971	0058.6	009.5	293.7	000.3000	0024.9	038.2	33.90	
168.0	000.1971	0058.1	009.4	293.6	000.3000	0024.9	038.3	33.85	
169.0	000.1971	0058.2	009.5	293.4	000.3000	0024.9	038.5	33.80	
170.0	000.1971	0058.3	009.5	293.3	000.3000	0024.9	038.6	33.76	
171.0	000.1918	0057.9	009.4	293.3	000.3000	0024.9	038.8	33.70	
172.0	000.1866	0057.9	009.3	293.2	000.3000	0024.9	038.9	33.64	
173.0	000.1832	0058.1	009.3	293.1	000.3000	0024.9	039.1	33.59	
174.0	000.1781	0058.3	009.2	293.1	000.3000	0024.9	039.3	33.54	
175.0	000.1731	0058.3	009.1	293.1	000.3000	0024.9	039.4	33.48	
176.0	000.1681	0058.6	009.1	293.0	000.3000	0024.9	039.6	33.43	
177.0	000.1632	0059.2	009.1	293.0	000.3000	0024.9	039.8	33.38	
178.0	000.1600	0059.7	009.1	292.9	000.3000	0024.9	039.9	33.33	
179.0	000.1552	0060.1	009.0	292.8	000.3000	0024.9	040.1	33.28	
180.0	000.1505	0060.5	009.0	292.8	000.3000	0024.9	040.2	33.23	
181.0	000.1568	0060.9	009.1	292.6	000.3000	0024.8	040.3	33.20	
182.0	000.1632	0060.8	009.2	292.4	000.3000	0024.8	040.4	33.16	
183.0	000.1697	0060.4	009.3	292.2	000.3000	0024.7	040.6	33.12	

WFHL BLED20030623ADC  
Channel = 201A  
Max ERP = 0.3 kW  
RCAMSL = 51 M  
N. Lat. 41 38 15.0  
W. Lng. 70 52 19.0  
Protected  
60 dBu

WELH.Proposed  
Channel = 201A  
Max ERP = 4 kW  
RCAMSL = 71.6 M  
N. Lat. 41 51 26.7  
W. Lng. 71 19 05.6  
Interfering  
40 dBu

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
244.0	000.3000	0036.5	008.2	133.2	000.5092	0048.4	040.9	38.76	
245.0	000.3000	0035.4	008.0	133.0	000.5099	0048.3	040.8	38.77	
246.0	000.3000	0034.2	007.9	132.7	000.5106	0048.2	040.7	38.79	
247.0	000.3000	0032.7	007.7	132.4	000.5114	0048.0	040.7	38.79	
248.0	000.3000	0031.3	007.6	132.1	000.5123	0047.9	040.6	38.79	
249.0	000.3000	0029.8	007.4	131.9	000.5130	0047.7	040.6	38.79	
250.0	000.3000	0028.4	007.4	131.8	000.5133	0047.7	040.5	38.83	
251.0	000.3000	0027.4	007.4	131.7	000.5135	0047.6	040.3	38.86	
252.0	000.3000	0027.2	007.4	131.6	000.5138	0047.6	040.2	38.89	
253.0	000.3000	0027.0	007.4	131.5	000.5140	0047.5	040.1	38.93	
254.0	000.3000	0026.9	007.4	131.4	000.5143	0047.5	040.0	38.96	
255.0	000.3000	0026.9	007.4	131.3	000.5146	0047.4	039.9	38.99	
256.0	000.3000	0026.7	007.4	131.2	000.5149	0047.4	039.8	39.03	
257.0	000.3000	0026.3	007.4	131.1	000.5152	0047.3	039.7	39.06	
258.0	000.3000	0026.1	007.4	131.0	000.5155	0047.3	039.6	39.09	
259.0	000.3000	0026.1	007.4	130.9	000.5159	0047.2	039.5	39.12	
260.0	000.3000	0026.1	007.4	130.8	000.5162	0047.2	039.4	39.15	
261.0	000.3000	0026.3	007.4	130.6	000.5166	0047.1	039.3	39.18	
262.0	000.3000	0026.6	007.4	130.5	000.5169	0047.1	039.2	39.21	
263.0	000.3000	0026.9	007.4	130.4	000.5173	0047.0	039.1	39.24	

**Exhibit 15 – Table I**  
**FM OVER ANALYSIS**  
(page 4 of 5)

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
264.0	000.3000	0027.2	007.4	130.3	000.5176	0046.9	039.0	39.27	
265.0	000.3000	0027.4	007.4	130.1	000.5180	0046.9	038.9	39.30	
266.0	000.3000	0027.7	007.4	130.0	000.5184	0046.8	038.8	39.33	
267.0	000.3000	0027.6	007.4	129.9	000.5188	0046.8	038.7	39.35	
268.0	000.3000	0027.2	007.4	129.7	000.5192	0046.7	038.6	39.38	
269.0	000.3000	0027.1	007.4	129.6	000.5196	0046.7	038.5	39.40	
270.0	000.3000	0026.7	007.4	129.4	000.5201	0046.6	038.5	39.43	
271.0	000.3000	0026.3	007.4	129.3	000.5205	0046.6	038.4	39.45	
272.0	000.3000	0025.9	007.4	129.1	000.5209	0046.5	038.3	39.48	
273.0	000.3000	0025.8	007.4	129.0	000.5215	0046.5	038.2	39.51	
274.0	000.3000	0026.0	007.4	128.8	000.5224	0046.4	038.1	39.53	
275.0	000.3000	0026.3	007.4	128.6	000.5233	0046.4	038.1	39.56	
276.0	000.3000	0026.4	007.4	128.5	000.5243	0046.4	038.0	39.59	
277.0	000.3000	0026.7	007.4	128.3	000.5253	0046.3	037.9	39.62	
278.0	000.3000	0026.9	007.4	128.1	000.5262	0046.3	037.9	39.64	
279.0	000.3000	0027.1	007.4	128.0	000.5271	0046.2	037.8	39.66	
280.0	000.3000	0027.1	007.4	127.8	000.5276	0046.2	037.7	39.68	
281.0	000.3000	0026.9	007.4	127.6	000.5282	0046.2	037.7	39.71	
282.0	000.3000	0026.6	007.4	127.5	000.5287	0046.2	037.6	39.73	
283.0	000.3000	0026.3	007.4	127.3	000.5292	0046.2	037.6	39.76	
284.0	000.3000	0026.4	007.4	127.1	000.5297	0046.1	037.5	39.78	
285.0	000.3000	0026.1	007.4	126.9	000.5305	0046.1	037.5	39.80	
286.0	000.3000	0025.5	007.4	126.7	000.5316	0046.1	037.4	39.82	
287.0	000.3000	0025.2	007.4	126.5	000.5327	0046.0	037.4	39.83	
288.0	000.3000	0025.1	007.4	126.3	000.5338	0046.0	037.3	39.85	
289.0	000.3000	0024.8	007.4	126.2	000.5349	0046.0	037.3	39.87	
290.0	000.3000	0024.5	007.4	126.0	000.5359	0045.9	037.3	39.89	
291.0	000.3000	0024.5	007.4	125.8	000.5365	0045.9	037.2	39.89	
292.0	000.3000	0024.7	007.4	125.6	000.5370	0045.8	037.2	39.89	
293.0	000.3000	0024.9	007.4	125.4	000.5376	0045.7	037.2	39.89	
294.0	000.3000	0024.8	007.4	125.2	000.5382	0045.6	037.1	39.89	
295.0	000.3000	0024.2	007.4	125.0	000.5388	0045.5	037.1	39.89	
296.0	000.3000	0023.7	007.4	124.8	000.5399	0045.4	037.1	39.89	
297.0	000.3000	0023.7	007.4	124.6	000.5411	0045.3	037.1	39.89	
298.0	000.3000	0023.9	007.4	124.4	000.5423	0045.2	037.0	39.88	
299.0	000.3000	0023.6	007.4	124.2	000.5435	0045.0	037.0	39.87	
300.0	000.3000	0023.3	007.4	124.0	000.5446	0044.9	037.0	39.86	
301.0	000.3000	0023.0	007.4	123.8	000.5452	0044.8	037.0	39.85	
302.0	000.3000	0022.7	007.4	123.6	000.5458	0044.7	037.0	39.83	
303.0	000.3000	0022.6	007.4	123.4	000.5464	0044.5	037.0	39.81	
304.0	000.3000	0022.7	007.4	123.2	000.5470	0044.4	037.0	39.79	
305.0	000.3000	0022.8	007.4	123.0	000.5476	0044.3	037.0	39.78	
306.0	000.3000	0022.3	007.4	122.8	000.5488	0044.2	037.0	39.77	
307.0	000.3000	0022.4	007.4	122.6	000.5500	0044.2	037.0	39.77	
308.0	000.3000	0023.1	007.4	122.4	000.5512	0044.1	037.0	39.76	
309.0	000.3000	0024.4	007.4	122.2	000.5524	0044.1	037.0	39.76	
310.0	000.3000	0025.0	007.4	122.0	000.5535	0044.1	037.1	39.76	
311.0	000.3000	0025.2	007.4	121.8	000.5541	0044.0	037.1	39.75	
312.0	000.3000	0025.1	007.4	121.6	000.5547	0044.0	037.1	39.75	
313.0	000.3000	0025.3	007.4	121.4	000.5553	0044.0	037.1	39.74	
314.0	000.3000	0025.5	007.4	121.2	000.5559	0044.0	037.2	39.73	
315.0	000.3000	0025.8	007.4	121.0	000.5565	0044.0	037.2	39.72	
316.0	000.3000	0026.0	007.4	120.8	000.5576	0043.9	037.2	39.71	
317.0	000.3000	0026.3	007.4	120.6	000.5587	0043.9	037.3	39.70	
318.0	000.3000	0026.7	007.4	120.4	000.5599	0043.9	037.3	39.69	
319.0	000.3000	0027.4	007.4	120.2	000.5610	0043.8	037.3	39.68	
320.0	000.3000	0027.7	007.4	120.1	000.5621	0043.8	037.4	39.66	
321.0	000.3000	0028.1	007.4	119.9	000.5659	0043.7	037.4	39.67	
322.0	000.3000	0028.1	007.4	119.7	000.5709	0043.7	037.5	39.68	

**Exhibit 15 – Table I**  
**FM OVER ANALYSIS**  
(page 5 of 5)

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
323.0	000.3000	0027.8	007.4	119.5	000.5759	0043.7	037.5	39.69	
324.0	000.3000	0027.4	007.4	119.3	000.5809	0043.6	037.6	39.70	
325.0	000.3000	0026.8	007.4	119.1	000.5858	0043.6	037.6	39.71	
326.0	000.3000	0025.9	007.4	119.0	000.5907	0043.5	037.7	39.71	
327.0	000.3000	0025.0	007.4	118.8	000.5956	0043.5	037.7	39.72	
328.0	000.3000	0024.2	007.4	118.6	000.6004	0043.4	037.8	39.72	
329.0	000.3000	0023.9	007.4	118.4	000.6051	0043.4	037.9	39.73	
330.0	000.3000	0024.1	007.4	118.3	000.6099	0043.4	037.9	39.73	
331.0	000.3000	0023.8	007.4	118.1	000.6145	0043.3	038.0	39.73	
332.0	000.3000	0023.2	007.4	118.0	000.6191	0043.3	038.1	39.73	
333.0	000.3000	0023.4	007.4	117.8	000.6237	0043.3	038.1	39.73	
334.0	000.3000	0024.3	007.4	117.6	000.6282	0043.3	038.2	39.73	
335.0	000.3000	0025.6	007.4	117.5	000.6327	0043.2	038.3	39.73	
336.0	000.3000	0027.3	007.4	117.3	000.6371	0043.2	038.4	39.73	
337.0	000.3000	0029.5	007.4	117.2	000.6414	0043.2	038.5	39.72	
338.0	000.3000	0031.2	007.5	116.9	000.6492	0043.1	038.5	39.77	
339.0	000.3000	0032.4	007.7	116.6	000.6577	0043.1	038.4	39.82	
340.0	000.3000	0032.9	007.7	116.4	000.6636	0043.1	038.5	39.84	
341.0	000.3000	0033.0	007.7	116.3	000.6681	0043.0	038.6	39.83	
342.0	000.3000	0033.4	007.8	116.1	000.6736	0043.0	038.6	39.83	
343.0	000.3000	0034.8	008.0	115.7	000.6831	0042.9	038.6	39.89	
344.0	000.3000	0035.1	008.0	115.6	000.6883	0042.9	038.7	39.88	
345.0	000.3000	0034.3	007.9	115.5	000.6894	0042.9	038.9	39.83	
346.0	000.3000	0031.9	007.6	115.7	000.6841	0042.9	039.2	39.70	
347.0	000.3000	0029.7	007.4	115.8	000.6807	0042.9	039.4	39.60	
348.0	000.3000	0028.7	007.4	115.7	000.6842	0042.9	039.5	39.58	
349.0	000.3000	0027.4	007.4	115.6	000.6876	0042.9	039.6	39.57	
350.0	000.3000	0026.7	007.4	115.5	000.6909	0042.9	039.7	39.55	
351.0	000.3000	0026.7	007.4	115.4	000.6942	0042.8	039.8	39.53	
352.0	000.3000	0026.6	007.4	115.3	000.6973	0042.8	039.9	39.50	
353.0	000.3000	0026.4	007.4	115.2	000.7003	0042.8	040.0	39.48	
354.0	000.3000	0026.6	007.4	115.1	000.7033	0042.7	040.1	39.45	
355.0	000.3000	0027.4	007.4	115.0	000.7062	0042.7	040.2	39.43	
356.0	000.3000	0028.9	007.4	114.9	000.7089	0042.7	040.4	39.40	
357.0	000.3000	0030.2	007.4	114.8	000.7125	0042.7	040.5	39.38	
358.0	000.3000	0031.0	007.5	114.6	000.7180	0042.6	040.5	39.38	
359.0	000.3000	0031.6	007.6	114.4	000.7234	0042.6	040.6	39.38	
000.0	000.3000	0032.2	007.7	114.2	000.7287	0042.6	040.7	39.37	
001.0	000.3000	0033.1	007.8	114.0	000.7350	0042.5	040.8	39.37	
002.0	000.3000	0034.2	007.9	113.8	000.7422	0042.5	040.9	39.38	
003.0	000.3000	0034.9	008.0	113.6	000.7478	0042.4	041.0	39.38	
004.0	000.3000	0035.4	008.0	113.5	000.7522	0042.4	041.1	39.36	