

Larry H. Will, P.E.

Broadcast Engineering

1055 Powderhorn Drive
Glen Mills, PA 19342-9504

PH (610) 399-1826
E-Mail lhwill@verizon.net

SONSHINE FAMILY TELEVISION CORPORATION

LICENSEE OF WBPH-DT

DTV CHANNEL 9

BETHLEHEM, PENNSYLVANIA

FAC ID# 60850

**FCC FILE # FCC FILE # BLCDT-20060609AAH
BLCDT-20100907AAF (Pending)**

**APPLICATION FOR A NEW MINOR CP TO INCREASE ERP AND TO
CHANGE DIRECTIONAL ANTENNA PATTERN**

RFR EXHIBIT 49

April 25, 2011

SONSHINE FAMILY TELEVISION CORPORATION

LICENSEE OF WBPH-DT

DTV CHANNEL 9

BETHLEHEM, PENNSYLVANIA

FAC ID# 60850

FCC FILE # BPCDT-20100105AAH

ENGINEERING EXHIBIT 49

ENVIRONMENTAL CONSIDERATIONS

The instant application is excluded under 1.1306. There are no changes proposed to the existing pre-1986 tower and there will be no terrain disturbances as a result of the modifications proposed herein. The construction involves replacing an existing antenna with one of similar size and shape. Using the procedures outlined in Supplement A, OET Bulletin 65, Edition 97-01 and specifically Equation 10, I have evaluated the RFR energy radiation from the antenna system of proposed WBPH-DT as follows:

The proposed WBPH-DT is the only broadcast antenna at the station location required to be considered by 47 CFR 1.1307(b). WBPH-DT is proposing to utilize an average ERP of 120 kilowatts (maximum DA) with horizontal polarization.

WBPH-DT

WBPH-DT, Channel 9, is requesting a modification of a C.P. to utilize an average ERP of 120 kilowatts (DA) with horizontal polarization. The proposed WBPH-DT transmitting antenna is a medium gain unit with an elevation power gain of 6X top mounted with a base

approximately 141 meters up the tower. Because of the elevation gain, the ERP at angles departing +/- 10 degrees from the horizon is attenuated by a minimum of 10 dB. For occupational/controlled environment (1.0 mW/cm^2 at 189 MHz) and utilizing Equation 10 of OET Bulletin 65 and allowing for 10 dB at steep angles below 10 degrees, the required physical separation is 20.1 meters. For general population/uncontrolled environment (0.2 mW/cm^2), the required physical spacing is 44.8 meters. Since the bottom of the antenna is approximately 141 meters above the ground, the height of the structure limits the possible excessive radiation values to at least 96.2 meters above the ground. Again using Equation 10 of OET Bulletin 65, and using the total average RF power corrected for steep angles, the **actual RF level at 2 meters above the ground from WBPH-DT is 20.7 uW/cm^2 or less than 10.4 % of the total allowable at 189 MHz.**

Therefore the total calculated RFR levels at the base of the proposed tower contributed by the WBPH-DT proposed operation are calculated to *be no more than 10.4 %* of the total and well below the allowable limits of OET Bulletin 65 for the general public/uncontrolled environment.

As a result this multi-user site along with WBPH-DT will continue to be in full compliance with the RFR requirements of FCC OET 65 and 47 CFR 1.1312.