

Non-Interference Compliance

Regarding Facility id 151736

Channel 232

Description of Exhibit 13 Contents

This exhibit demonstrates that the proposed facility complies with contour overlap and interference protection provisions in all of the applicable rule sections and that this application for a construction permit is in full compliance with 47 C.F.R. § 74.1204.

Let it be noted that should any actual real world interference occur, the applicant acknowledges that it will promptly suspend operation of this translator in accordance with 47 C.F.R. § 74.1203.

Page 2 of this exhibit is an explanation of the method used to demonstrate compliance with contour overlap and interference provisions based on 47 C.F.R. § 74.1204(d), which states:

[A]n application otherwise precluded by this section will be accepted if it can be demonstrated that no actual interference will occur due to intervening terrain, lack of population or such other factors as may be applicable.

Page 3 contains a tabulation of the vertical radiation pattern of the proposed antenna and the minimum ground clearance of the interfering contour based on this pattern.

Page 4 includes a tabulation of the vertical radiation pattern for the proposed antenna provided by the antenna manufacturer.

Page 5 of this exhibit contains the tabulated data from the interference analysis, which shows all stations whose protected contours come within 50 km of the 34 dBμ F(50,10) contour of the proposed translator. These tabulated values were calculated using data from the FCC's CDBS files and 30 arc second terrain data. The column labeled "Adj" shows the number of channels difference between the entry and the proposed translator. The column labeled "Dist" shows the distance in km. The column labeled "Overlap" shows the area of contour overlap in square kilometers.

Page 6 of this exhibit is a portion of a USGS 1:24,000 scale 7.5 minute quadrangle at full scale with the calculated area of interference overlaid. The sheet includes the quadrangle name and measurement scale at the bottom-left corner (note: "Mt" refers to meters). The area of interference was calculated using the free space equation and 120 radials.

Page 7 of this exhibit is an aerial photo of the vicinity surrounding the proposed translator's tower site.

Compliance with 47 C.F.R. § 74.1204(d)

All authorized second and third adjacent stations with which the proposed translator has contour overlap are tabulated below. Column four show the station's signal level at the proposed translator's tower site, and column five gives the minimum value within the entire standard interfering contour of the proposed translator (100 dBμ for most classes, 94 for class B, 97 for class B1). The minimum second or third adjacent F(50,50) contour within the proposed translator's standard interfering contour was used to calculate the proposed translator's actual "worst-case" interfering contour.

Application_id	File Number	Callsign	Contour at Tower	Min. Contour
153863	BLH19901029KC	WMTM-FM	60.4	60.2
222665	BLH19960401KA	WDEC-FM	65.3	65.1
Minimum F(50,50) Contour of Adjacent Station within Proposed Translator's Standard Interfering Contour				60.2

FCC 02-244 at Section II.A.5 states that "when demonstrating that 'no actual interference will occur due to . . . other factors,' pursuant to Section 74.1204(d), an applicant may use the undesired-to-desired signal ratio method." The undesired-to-desired ratio for second and third adjacent stations required by § 74.1204(a) is 40 dB. Since the minimum protected contour strength within the proposed translator's standard interference contour is **60.2 dBμ**, this makes the proposed translator's worst-case interfering contour **100.2 dBμ**. By the free-space equation, this contour is calculated to extend a maximum of **247.2 m** from the transmit antenna.

The maximum horizontal plane of the interfering contour was calculated for 120 radials and plotted on the pertinent portion of a USGS quadrangle (page 6 of this exhibit). However, the field strength of the proposed translator's antenna varies with angle of depression from horizontal. The antenna relative fields are tabulated on the following page at 5 degree increments, starting at 5 degrees below horizontal. Antenna relative field strength data was provided and certified by the manufacturer of the proposed antenna. Using a free-space calculation that neglects any loss due to reflection, the vertical ground clearance of the proposed translator's interference contour has been tabulated. As shown on the following page, the area of interference clears the tower ground level (TGL) by **12.2 m** at the lowest point. The applicant has taken into account USGS quadrangles and relevant aerial photography in stating that no structures, except possibly tower support structures, puncture the area of interference. Hence, in accordance with 47 C.F.R. § 74.1204(d) and the clarification provided by the FCC in the decision *Re: Living Way Ministries* (FCC 02-244), a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Antenna Manufacturer:	NIC
Antenna Model:	BKG77
CORAGL:	122 m
Maximum ERP:	0.013 kW
Interfering Contour:	100.2 dBμ
Max Int. Contour Distance:	247.2 m
Min Ground Clearance:	12.2 m

Depression Angle Below Horizontal	Antenna Relative Field	ERP (watts)	Distance to Interfering Contour from Antenna (m)	Horizontal Distance of Interfering Contour from Tower (m)	Vertical Clearance of Interfering Contour above TGL (m)
5	.999	13.0	246.9	246.0	100.5
10	.982	12.5	242.7	239.0	79.9
15	.954	11.8	235.8	227.8	61.0
20	.918	11.0	226.9	213.2	44.4
25	.871	9.9	215.3	195.1	31.0
30	.818	8.7	202.2	175.1	20.9
35	.758	7.5	187.3	153.5	14.5
40	.691	6.2	170.8	130.8	12.2
45	.616	4.9	152.2	107.7	14.3
50	.538	3.8	133.0	85.5	20.1
55	.465	2.8	114.9	65.9	27.9
60	.391	2.0	96.6	48.3	38.3
65	.313	1.3	77.4	32.7	51.9
70	.239	0.7	59.1	20.2	66.5
75	.176	0.4	43.5	11.3	80.0
80	.128	0.2	31.6	5.5	90.8
85	.103	0.1	25.5	2.2	96.6
90	.105	0.1	26.0	0.0	96.0
Minimum Clearance above TGL:					12.2 m



BK077


Vertical	-66	0.297	54	0.479	174	0.468
Values	-63	0.345	57	0.436	177	0.479
-180	0.487	-60	0.391	60	0.391	
-177	0.478	-57	0.436	63	0.345	
-174	0.467	-54	0.479	66	0.297	
-171	0.460	-51	0.523	69	0.253	
-168	0.454	-48	0.568	72	0.211	
-165	0.447	-45	0.616	75	0.176	
-162	0.439	-42	0.661	78	0.145	
-159	0.429	-39	0.706	81	0.120	
-156	0.419	-36	0.745	84	0.105	
-153	0.402	-33	0.783	87	0.100	
-150	0.385	-30	0.818	90	0.105	
-147	0.369	-27	0.852	93	0.118	
-144	0.359	-24	0.881	96	0.134	
-141	0.350	-21	0.910	99	0.151	
-138	0.338	-18	0.934	102	0.168	
-135	0.326	-15	0.954	105	0.185	
-132	0.314	-12	0.972	108	0.202	
-129	0.303	-9	0.987	111	0.219	
-126	0.290	-6	0.999	114	0.236	
-123	0.278	-3	0.999	117	0.252	
-120	0.265	0	1.000	120	0.265	
-117	0.251	3	0.999	123	0.278	
-114	0.236	6	0.999	126	0.290	
-111	0.218	9	0.987	129	0.304	
-108	0.202	12	0.972	132	0.314	
-105	0.185	15	0.954	135	0.327	
-102	0.168	18	0.934	138	0.338	
-99	0.151	21	0.910	141	0.350	
-96	0.134	24	0.881	144	0.360	
-93	0.118	27	0.852	147	0.370	
-90	0.105	30	0.818	150	0.386	
-87	0.100	33	0.783	153	0.403	
-84	0.105	36	0.745	156	0.420	
-81	0.120	39	0.706	159	0.430	
-78	0.145	42	0.661	162	0.440	
-75	0.176	45	0.616	165	0.448	
-72	0.211	48	0.568	168	0.455	
-69	0.253	51	0.523	171	0.461	

Better than SWR

Adjacent Channel Study **For Station W232BI, Facility_id: 151736**

Co-channel through third adjacent:



Application_id	Facility_id	Prefix	ARN	Call	Licensee	Class	City	State	Status	ERP	RCAMSL	Channel	Adj	Dist	Overlap
222665	63786	BLH	19960401KA	WDEC-FM	SUMTER BROADCASTING CO., INC.	C3	AMERICUS	GA	LIC	25	205	234	2	32.1	0.0776
153863	12381	BLH	19901029KC	WMTM-FM	COLQUITT BROADCASTING COMPANY, LLC	C1	MOULTRIE	GA	LIC	100	261	230	2	60.1	0.0776
1169436	151751	BLFT	20070123ACD	W232AB	RADIO ASSIST MINISTRY, INC.	D	CAMILLA	GA	LIC	0.01	210	232	0	55.5	0
1303664	165968	BLH	20090326ADU	WLEL	GARY S. HESS	A	ELLAVILLE	GA	LIC	4.8	230	232	0	69.5	0
1190840	138251	BLFT	20070613AAY	W231BB	AUGUSTA RADIO FELLOWSHIP INSTITUTE, INC	D	LUMPKIN	GA	LIC	0.01	282	231	1	74.4	0
644863	151772	BNPFT	20030317IDR	NEW	RADIO ASSIST MINISTRY, INC.	D	MONTEZUMA	GA	APP	0.01	249.6	232	0	75	0
1190843	138324	BLFT	20070613AAX	W235AS	AUGUSTA RADIO FELLOWSHIP INSTITUTE, INC	D	IRWINVILLE	GA	LIC	0.013	216	235	3	77.5	0
638735	146161	BNPFT	20030317DVT	NEW	EDGEWATER BROADCASTING, INC.	D	THOMASVILLE	GA	APP	0.038	122.1	233	1	85.6	0
1363373	23615	BMLED	20100412ABG	WIZB	RADIO TRAINING NETWORK, INC.	C3	ABBEVILLE	AL	LIC	19.5	211	232	0	105.8	0
65066	51590	BLH	19840106AE	WTNT-FM	CLEAR CHANNEL BROADCASTING LICENSES, INC	C1	TALLAHASSEE	FL	LIC	98	303	235	3	116.8	0
602557	52551	BLH	20020529ABR	WPEZ	CUMULUS LICENSING LLC	C1	JEFFERSONVILLE	GA	LIC	100	321	229	3	138.6	0



Facility id: 151736;
Area of Interference;

(ALBANY WEST)
4147 II SW
SCALE 1:24 000

ALBANY 4.7 MI.



CONTOUR INTERVAL 10 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929

...M GRID AND 1988 MAGNETIC NORTH
DECLINATION AT CENTER OF SHEET
...ns shown in purple and woodland compiled in cooperation
...ate of Georgia agencies from aerial photographs
1983 and other sources. This information not field checked
dated 1988

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY
DENVER, COLORADO 80225 OR RESTON, VIRGINIA 22092
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

