Doug Vernier Telecommunications Consultants
721 West 1st St. Ste. A, Cedar Falls, IA 50613

Exhibit #15

KUWZ Minor Change
University of Wyoming

REFERENCE CH# 213C - 90.5 MHz, Pwr= 50 kW, HAAT=487.0 M, COR= 2655 M DISPLAY DATES
41 25 39 N Average Protected F(50-50)= 78.87 km DATA 12-11-03
109 07 18 W Ave. F(50-10) 40 dBu= 174.6 54 dBu= 116.3 80 dBu= 37.3 100 dBu= 10.2 SEARCH 12-11-03

CH CALL / CITY	TYPE / STATE	AZI. <--	DIST / FILE #	LAT. / LNG.	Pwr(kW) / HAAT(M)	COR(M) / INT(km)	PRO(km) / LICENSEE	*IN* (Overlap in km)	*OUT* (Overlap in km)
213C KUWZ Rock Springs	LIC CY WY	292.3 112.3	20.27 BLED19941109KG	41 29 47 109 20 47	100.000 272	2364 177.8	70.1 University Of Wyoming	-230.59*<	-227.57*<
213A 980529 Logan	APP CN UT	279.6 99.6	228.88 BPED19980529ME	41 44 22 111 50 05	6.000 -861	1408 179.3	15.8 Broadcasting For The Chall	77.74	33.82
213C2 KDNK.A Carbondale	APP ZCX CO	145.8 325.8	268.07 BPED20031126ASI	39 25 08 107 22 10	0.301 874	3227 172.1	41.6 Carbondale Community Acces	83.90	54.31
213A 971205 Logan	APP DCN UT	282.9 102.9	251.71 BPED19971205MA	41 53 43 112 04 43	0.300 462	1869 179.2	29.0 Listners Community Radio O	83.50	43.49
213C3 KDNK Carbondale	LIC CN CO	145.9 325.9	266.87 BLED19930913KF	39 25 35 107 22 48	0.215 993	3252 172.1	40.9 Carbondale Community Acces	83.66	53.84
212C KCSPFM Casper	LIC CN WY	56.9 236.9	274.81 BLED19921013KA	42 44 24 106 18 23	100.000 576	2554 119.7	90.8 Western Inspirational B/ct	58.60	64.25
266A RDEL Wamsutter	DEL WY	73.8 253.8	99.71	41 40 18 107 58 18	6.000 114	2177 96.8	30.0	29.0R	70.7M
266A ALLO Wamsutter	VAC WY	73.8 253.8	99.71 RM9671	41 40 18 107 58 18	6.000 114	2177 96.8	30.0	29.0R	70.7M
212C2 KUWJ Jackson	LIC CN WY	329.9 149.9	262.74 BLED19921207KC	43 27 40 110 45 09	3.000 291	2489 124.3	39.3 University Of Wyoming	120.27	99.20
215A KUWX Pinedale	LIC C WY	337.5 157.5	170.77 BLED20000627AFX	42 50 40 109 55 24	0.450 85	2359 10.8	13.7 University Of Wyoming	85.21	146.28
212C2 KLFV.C Grand Junction	CP CX CO	173.0 353.0	264.17 BPED20000330ABE	39 03 57 108 44 48	3.000 695	2196 103.8	58.7 Educational Media Foundati	106.26	101.68
212C3 KLFV Grand Junction	LIC CN CO	173.0 353.0	264.17 BLED19911227KA	39 03 57 108 44 48	1.500 693	2194 103.8	51.9 Educational Media Foundati	115.91	108.50
211C3 KHCO.C Hayden	CP CX CO	122.1 302.1	185.59 BPED19981215MF	40 31 36 107 15 52	10.000 179	2231 9.7	41.4 Broadcasting For The Chall	107.56	134.52
06Z2C KBCJ Vernal	CP HN UT	180.9 0.9	118.99 BPCT19960919KG	40 21 22 109 08 41	83.200 503	2541 422.5	118.3 Vernal Broadcasting, Inc.	To Grd B=	0.65

"*"Affixed to 'IN' or 'Out' values = site inside protected contour.
ERP and HAAT are on direct line to and from reference station. "<" = Contour Overlap

HOW TO READ THE FM COMPUTER PRINT-OUT

The computer printout should be self-explanatory for the most part. The parameters of the station being checked, (reference station) are printed in the heading. The 60 dBu protected contour is predicted from the Commission's F(50-50) table, while the 40, 54, 80 and 100 dBu contours are interference contours derived from the Commission's F(50-10) table. Contour distances are in kilometers and are predicted using spline interpolation from data points identical to those published in Report No. RS 76-01 by Gary C. Kalagian. Critical contour distances are determined using the Commission's TVFMINT FORTRAN subroutine. When interference contour distances are less than 16 kilometers the F(50-50) tables are used. If signal contour distances are less than 1.6 km the free-space equation is used.

The column listed "* IN *" is the sum of the reference station's 60 dBu protected contour and the data file station's interference contour subtracted from the distance between the stations. (All distances are derived by the method detailed in Sec. 73.208 of the Rules and Regulations as amended in Docket 80-90.) Therefore, the column is a measure of incoming interference. Negative distances in this column indicate the presence of interference. Listed antenna heights are the average heights of eight standard radials as found in the Commission's records unless otherwise noted, in which case the specific antenna heights and the DA power, if applicable, along the straight line azimuths between the reference station and the database station are used and visa versa. The column labeled "* OUT *" shows the distance in kilometers of overlap or clearance between the reference station's interference contour and the database station's protected contour. Negative distance figures in this column indicate outgoing overlap interference.

Under the "AZIMUTH" column, the first row of numbers indicate the bearings from True North of the data base stations in relationship with the reference station, while the numbers in the second row indicate the reverse bearings from the database station to the reference station.

The columns labeled "INT" and "PRO" hold the distance in kilometers of the appropriate interference contour and the protected contour of a data base station.

For I.F. relationships the "IN" and "OUT" columns change their significance. The letter "R" stands for the minimum **required** distance in kilometers, while the letter "M" in the next column follows the **available clear space** separation in kilometers. Minimum separation distances when displayed are taken from Sec 73.207 of the rules as amended. Canadian and Mexican separation distances, U/D ratios and protected contour values are from the US/Mexican Working Agreement and the US/Canada Working Agreement".

The first three letters of the "TYPE" column identify the current FCC status of the stations. The fourth letter will be a "D" if the facility is directional. “Z” indicates a 73.215 directional. An “N” indicates it is a 73.215 station that operates omni. The fifth letter will be an E, H or V depending on the type of antenna polarization. The sixth letter will be a "Y" if the antenna uses beam tilt or an “X” if the commission is not sure, otherwise it will be an “N”.