

Calvary Chapel of Twin Falls, Inc.

REFERENCE
39 22 30.0 N.
103 48 05.0 W.

CH# 220D - 91.9 MHz, Pwr= 0.05 kW, HAAT= 183.4 M, COR= 1888 M
Average Protected F(50-50)= 11.81 km
Omni-directional

DISPLAY DATES
DATA 09-27-16
SEARCH 09-29-16

CH CITY	CALL	TYPE STATE	ANT	AZI <--	DIST FILE #	LAT LNG	PWR(kW) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
220D Limon	K220HK	LIC_V_ CO		89.2 269.3	9.16 BLFT20121120AAW	39 22 34.0 103 41 41.0	0.075 135	25.7 1830	7.7 Calvary Chapel Of Twin Fal	-26.9*	-44.9*
221C2 Castle Rock	KJMN	LIC_NCX CO		271.0 90.2	107.11 BLH20050603AAV	39 23 07.0 105 02 52.0	42.000 163	96.0 2226	65.5 Entravision Holdings, LLC	-0.5	23.9
220D Brush	K220IM	LIC_C_ CO		7.7 187.8	100.97 BLFT20100709AGZ	40 16 30.0 103 38 33.0	0.250 50	28.7 1365	8.5 Educational Communications	58.5	46.5
06NT Manitou Springs	K06BI	LI_DHN CO		239.5 58.8	110.80 BLTTV1446	38 51 50.0 104 54 15.0	0.001 188	1.6 2012	0.8	2.4R	108.4M

Terrain database is NGDC 30 SEC, R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
In & Out distances between contours are shown at closest points. Reference zone= West Zone, Co to 3rd adjacent.
All separation margins (if shown) include rounding. Call signs with strikeout need not be protected.
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
"*"affixed to 'IN' or 'OUT' values = site inside restricted contour.