

LARRY P. WAGGONER

PROPOSED K268CP
VERTICAL PLANE DIRECTIONAL PATTERN
Pattern RMS 0.830 Field

Azimuth	Field	dBk	ERP(kW)	Azimuth	Field	dBk	ERP(kW)
0	0.355	-27.24	0.002	180	1.000	-18.24	0.015
5	0.316	-28.24	0.001	185	1.000	-18.24	0.015
10	0.282	-29.24	0.001	190	1.000	-18.24	0.015
15	0.251	-30.24	0.001	195	1.000	-18.24	0.015
20	0.251	-30.24	0.001	200	1.000	-18.24	0.015
25	0.251	-30.24	0.001	205	1.000	-18.24	0.015
30	0.251	-30.24	0.001	210	1.000	-18.24	0.015
35	0.251	-30.24	0.001	215	1.000	-18.24	0.015
40	0.251	-30.24	0.001	220	1.000	-18.24	0.015
45	0.251	-30.24	0.001	225	1.000	-18.24	0.015
50	0.251	-30.24	0.001	230	1.000	-18.24	0.015
55	0.282	-29.24	0.001	235	1.000	-18.24	0.015
60	0.316	-28.24	0.001	240	1.000	-18.24	0.015
65	0.355	-27.24	0.002	245	1.000	-18.24	0.015
70	0.398	-26.24	0.002	250	1.000	-18.24	0.015
75	0.447	-25.24	0.003	255	1.000	-18.24	0.015
80	0.501	-24.24	0.004	260	1.000	-18.24	0.015
85	0.562	-23.24	0.005	265	1.000	-18.24	0.015
90	0.631	-22.24	0.006	270	1.000	-18.24	0.015
95	0.708	-21.24	0.008	275	1.000	-18.24	0.015
100	0.794	-20.24	0.009	280	1.000	-18.24	0.015
105	0.891	-19.24	0.012	285	1.000	-18.24	0.015
110	1.000	-18.24	0.015	290	1.000	-18.24	0.015
115	1.000	-18.24	0.015	295	1.000	-18.24	0.015
120	1.000	-18.24	0.015	300	1.000	-18.24	0.015
125	1.000	-18.24	0.015	305	1.000	-18.24	0.015
130	1.000	-18.24	0.015	310	1.000	-18.24	0.015
135	1.000	-18.24	0.015	315	1.000	-18.24	0.015
140	1.000	-18.24	0.015	320	0.891	-19.24	0.012
145	1.000	-18.24	0.015	325	0.794	-20.24	0.009
150	1.000	-18.24	0.015	330	0.708	-21.24	0.008
155	1.000	-18.24	0.015	335	0.631	-22.24	0.006
160	1.000	-18.24	0.015	340	0.562	-23.24	0.005
165	1.000	-18.24	0.015	345	0.501	-24.24	0.004
170	1.000	-18.24	0.015	350	0.447	-25.24	0.003
175	1.000	-18.24	0.015	355	0.398	-26.24	0.002