

Robert Moore

REFERENCE CH# 255D - 98.9 MHz, Pwr= 0.002 kW, HAAT= 92.2 M, COR= 648 M Mars Hill Broadcasting Co. Inc.
 44 20 27.0 N. Average Protected F(50-50)= 3.67 km DISPLAY DATES
 74 07 44.0 W. Omni-directional DATA 06-01-13
 SEARCH 07-01-13

CH CITY	CALL	TYPE STATE	ANT STATE	AZI <--	DIST FILE #	LAT LNG	PWR(kw) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*OUT* (Overlap in km)
252D	643762	APP	_C	0.0	0.00	44 20 27.0	0.010	0.2	6.8	-6.9*
Saranac Lake		NY		0.0	BNPFT20030317AFQ	74 07 44.0	92	648	Mars Hill Broadcasting Co.	
255C1	WOKO	LIC	_CN	80.3	74.99	44 27 03.0	100.000	156.4	59.5	2.7
Burlington		VT		260.9	BLH19880920KB	73 11 51.0	94	189	Hall Communications, Inc.	
From Channel 255C2										
253C1	CIELFM	OPE	_HN	17.9	136.16	45 30 20.0	41.000	7.9	77.7	62.7M
Longueuil		QC		198.3		73 35 32.0	302	327	73.5R	
SPECIAL NEGOTIATED SHORT-SPACED ALLOCATION										
256C1	AL1902	AL	___	311.2	149.58	45 13 01.0	100.000	105.7	86.0	66.1M
Ottawa-hull		ON		130.2		75 33 51.0	299	386	83.5R	
Proposed to Commission 950725-Specially negotiated, short-spaced allotment limited to the following or equivalent; 1.3kw ERP and 173m HAAT along the 147.8 degree azimuth towards channel 257B1 in Potsdam, NY; 89kw ERP and 165m HAAT along the 180 degree azimuth towards channel 257B1 in Lowville, NY.										

Terrain database is FCC NGDC 30 Sec , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
 In & Out distances between contours are shown at closest points. Reference zone= East Zone, Co to 3rd adjacent.
 All separation margins (if shown) include rounding
 Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
 Incoming contour overlap is ignored.
 "*"affixed to 'IN' or 'OUT' values = site inside protected contour.
 « = Station meets FCC minimum distance spacing for its class.