

RF CERTIFICATION
AND STATEMENT

The proposed antenna will be energized such that it produces 0.25 kW (250 watts) ERP from the center of radiation 55 meters above the ground. The applicant employs an ERI FM-100-1 single bay antenna system. Based on the formulas expressed in OET bulletin No. 65, August 1997, "Evaluating Compliance with F.C.C. Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields" published by the Federal Communications Commission's Office of Engineering and applying a combination of the element and array pattern as defined in E.P.A. study PB85-245868 ("**Engineering Assessment of the Potential Impact of the Federal Radiation Protection Guidance on the AM, FM and TV Broadcast Services**"). The highest calculated power density can be found 54.51 meters from the tower. At this location, the value is 1.228 uW/sq.cm. This value amounts to 0.1229 percent of the maximum for a "controlled" environment. In an uncontrolled environment, this amounts to 0.6142percent of maximum. This proposal is in full compliance with all applicable FCC rules. These calculations were performed using the V-Soft Communications RFHaz-III program.

The applicant will posted signs at the tower access to warn of the possible RF hazards. The applicant will also coordinate with any other occupants of the tower and will cease operation if a tower crew will be working on the structure.

/s/ Clyde Scott, Jr.
EME Communications
293 JC Saunders Road
Moultrie, GA 31768

ERI/JAMPRO JBCP "Roto" EPA-Typ 3, 1 Bay, Spac= 1, H=.25 kW, V=.25 kW, 55 M AG

