



Exhibit 34

Environmental Impact Statement

Bradley Snow
Channel 291C2
Mooreland, Oklahoma

This proposed modification application does not involve any of the environmental probations listed in Section 1.1311 of the Commission's Rules. Construction will not be a major environmental action.

The antenna for the proposed 291C2 facility will be energized such that it produces 50.0 kW ERP circularly polarized from a center of radiation 134.8 meters above ground. The proposed facility will utilize an ERI model SHPX-6AC6 6 bay antenna.

By using the formulas expressed in OST Bulletin, No. 65, October 1985, "Evaluating Compliance with F.C.C. Specified Guidelines for Human Exposure to Radio Frequency Radiation", published by the Federal Communications Commission's Office of Science and Technology, and then by applying a combination of the element and array pattern as identified in E.P.A. study PB85-245868 ("Engineering Assessment of the Potential Impact of the Federal Radiation Protection Guidance on the AM, FM and TV Broadcast Services") using an ERI circularly polarized antenna, it can be shown that the proposed antenna generates a maximum of 12.51 microwatts per square centimeter at a distance of 43 meters from the tower base, and 6 feet above the ground. This value amounts to 6.2569 percent of the uncontrolled maximum, and 1.2514 percent of the controlled maximum.

Access to the tower will be restricted with a fence and a locked gate. Signs will be posted warning of the radiation hazard. Company procedures have already been established to protect workers who must climb the tower. The transmitting power of the station will be reduced, or completely turned off to insure that these workers will not be exposed to excessive radiation levels.

RF Results, LLC

201 N. Grand, Suite 700 • Enid, OK 73701
Phone and Fax: (855) 737-3785 • (855) RFRESULTS
www.rfresults.com



Respectfully Submitted,

William H. Nolan

William H. Nolan
Senior Broadcast Engineer
RF Results, LLC