

DELAUDER COMMUNICATIONS, INC.

P.O. Box 1095
Ashburn, Virginia 20146-1095
(703) 299-9222

ENGINEERING REPORT

WTMV-LD, Ogden, NC Displacement to Channel 35

ENVIRONMENTAL STATEMENT

This proposal does not involve a site location specified under Section 1.1307(a) through (a)(8) of the FCC Rules.

The digital LPTV stations of the Applicant at this location produces an ERP that is less than or equal to 15 kilowatts. Assuming: (a) a maximum ERP of 15 kilowatts; (b) a relative field of less than 0.2 in the critical downward angles; and (c) a distance of at least 85 meters from the lowest antenna element to 2 meters above ground level, the maximum power density is calculated as follows:

$$S = 33.4 (F)(F)(ERP) / [(R)(R)]$$

Where, S equals power density in uW/cm²
 F equals the relative field factor
 ERP equals the effective radiate power in watts
 R equals the distance in meters

$$= 33.4 (0.2)(0.2)(15,000) / [(85)(85)]$$

$$= 2.8 \text{ uW/cm}^2$$

2.8 uW/cm² represents less than 5% of the uncontrolled power density limit (315.3 uW/cm² for UHF; 200 uW/cm² for VHF). The electromagnetic radiation from this proposed operation will not produce a value in excess of the radiation standard. The electromagnetic radiation from the proposed operation will not combine with other facilities on or near the structure to produce a significant change in value.

If this is a structure that may support various other operations, the applicant will cooperate with the other operators in establishing a plan for work done on the structure in close proximity to the existing antenna.