

Preliminary Specification for TRASAR® Top Mounted UHF Elliptically Polarized Coaxial Slotted Array Television Antenna

**KVPT, RF Channel 32
GatesAir, Fresno, CA**

**March 27, 2017
Revised August 2, 2017**

**Antenna Model:
ATW18H6-ETC3-32H**

**Specification Number
20170307-752**

Electronics Research, Inc. 7777 Gardner Road Chandler IN 47610-9219 USA
+1 812 925-6000 (tel) +1 812 925-4030 (fax)

Your Single Source for Broadcast Solutions™ Call Toll-free at 877 ERI-LINE Visit Online at www.eriinc.com

**Preliminary Specification for
TRASAR® Top Mounted
UHF Elliptically Polarized
Coaxial Slotted Array Television Antenna**

Electrical Characteristics:

Channel:	32		
Frequency:	578 MHz to 584 MHz		
Service:	ATSC		
Azimuth Pattern Number:	Horizontal Polarization	ATW-C3	
	Vertical Polarization	ATW-V10	
Elevation Pattern Number:	Horizontal Polarization	18H6H	
	Vertical Polarization	15H6V	
Azimuth Directivity:	Horizontal Polarization	2.00	(3.01 dB)
	Vertical Polarization	2.83	(4.52 dB)
Elevation Directivity:	Horizontal Polarization	18.00	(12.55 dBd)
	Vertical Polarization	15.00	(11.76 dBd)
Peak Power Gain:	Horizontal Polarization	28.70	(14.58 dBd)
	Vertical Polarization	8.61	(9.35 dBd)
Gain at Horizontal:	Horizontal Polarization	11.87	(10.74 dBd)
	Vertical Polarization	3.72	(5.70 dBd)
Vertical/Horizontal Ratio:	0.30		
Electrical Beam Tilt:	1.50 Degrees		
Input Power Required:	7.94 kW	(9.00 dBk)	
RF Input:	6-1/8-inch EIA, 50 Ω, flanged male		
Input Power Rating (maximum):	50 kW Average Power, 8VSB		
Antenna VSWR (maximum):	1.10 Over 6 MHz Channel		

**Preliminary Specification for
TRASAR® Top Mounted
UHF Elliptically Polarized
Coaxial Slotted Array Television Antenna**

Mechanical Characteristics:

Mounting Configuration:			Top Mount	
Height of Antenna (D):			34.40 feet	(10.5 meters)
Height of Center of Radiation (B):			17.20 feet	(5.2 meters)
Overall Height (Includes four 3.5 ft lightning spurs) (A):			37.90 feet	(11.6 meters)
Deicing:			Fully enclosed pressurized radome	
Radome Diameter (C):			14.4 inches	(366 millimeters)
Radome Color:			Aviation Orange	
Climbing Device:			Steel Climbing Pole	
Calculated Weight ¹ :		No Ice	4,000 lbs	1,814.4 kg
Windload Data ³ :	EPA	No Ice	80.34 sq.ft.	7.5 sq.m.
		0.5inch (13 mm) ice	105.18 sq.ft.	9.8 sq.m.
Effective Moment Arm ³ :	EPA	No Ice	18.72 sq.ft.	(5.7 meters)
		0.5inch (13 mm) ice	19.15 sq.ft.	(5.8 meters)

MOUNTING FLANGE BOLT CIRCLE²: Quantity (20), 1.38 inch holes for 1.25 inch bolts, equally spaced on a 21.50 inch bolt circle.

This antenna is designed to be supported by a structure that can resist the antenna base reactions and which provides a support that is rigid in the three translational and three rotational degrees of freedom.


1 Please note, the listed weights and effective wind areas are based on the PRELIMINARY design of the antenna. Final As-Built values for the antenna are typically within +/-10% of the Preliminary design values, and will be provided in the technical manual that accompanies the antenna. Specified loads include the antenna, beacon and lightning spurs only. Custom mounting brackets/adapters and/or antenna input section are NOT included.

2 The mounting flange specified is the standard ERI mounting flange used for this antenna configuration. In those instances where an existing top mounted antenna is being replaced the antenna supplied will be designed with a mounting flange to match that of the existing antenna unless electrical and /or mechanical requirements for the new antenna preclude the matching flange. Customer responsible for supplying verified flange requirements for the flange configuration being matched.

3 Based on a wind speed of 85 miles per hour MPH (fastest mile) no ice and 40 MPH with 0.25-inches in base design ice (0.61-inches actual tiz) with a height above ground level (HAGL) of 220 feet per ANSI/TIA-222-G. Structure Class II, Exposure Category C and Topographic Category I. EPA values include four lightning spurs & a standard beacon.

NOTE: The purchaser or their representative shall be required to contact the tower owner, state and/or local building officials for specific design requirements and suitable parameters for a particular structure. Any variation from the parameters shown above must be communicated to ERI for comprehensive assessment.


Typical Mounting Configuration Shown. Actual Configuration May Vary.



Azimuth Pattern

Type:	ATW-C3	Polarization:	Horizontal
Directivity:	2.00 numeric (3.01 dB)	Frequency:	32 (ATSC)
Peak(s) at:		Location:	Fresno, CA
		NOTE: Pattern shape and directivity may vary with channel and mounting configuration.	

Relative Field



Tabulated Data for Azimuth Pattern


Type:

ATW-C3

Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB
0	0.347	-9.19	100	0.347	-9.19	200	0.945	-0.49	300	0.804	-1.89
2	0.329	-9.66	102	0.369	-8.66	202	0.951	-0.44	302	0.797	-1.97
4	0.311	-10.14	104	0.391	-8.16	204	0.958	-0.37	304	0.790	-2.05
6	0.296	-10.57	106	0.414	-7.66	206	0.964	-0.32	306	0.784	-2.11
8	0.285	-10.90	108	0.437	-7.19	208	0.969	-0.27	308	0.777	-2.19
10	0.274	-11.24	110	0.460	-6.74	210	0.975	-0.22	310	0.770	-2.27
12	0.272	-11.31	112	0.483	-6.32	212	0.979	-0.18	312	0.762	-2.36
14	0.269	-11.40	114	0.506	-5.92	214	0.983	-0.15	314	0.753	-2.46
16	0.271	-11.34	116	0.528	-5.55	216	0.987	-0.11	316	0.744	-2.57
18	0.276	-11.18	118	0.549	-5.21	218	0.990	-0.09	318	0.735	-2.67
20	0.282	-11.00	120	0.570	-4.88	220	0.993	-0.06	320	0.725	-2.79
22	0.293	-10.66	122	0.590	-4.58	222	0.995	-0.04	322	0.713	-2.94
24	0.304	-10.34	124	0.609	-4.31	224	0.997	-0.03	324	0.702	-3.07
26	0.317	-9.98	126	0.627	-4.05	226	0.998	-0.02	326	0.689	-3.24
28	0.330	-9.63	128	0.644	-3.82	228	0.999	-0.01	328	0.674	-3.43
30	0.343	-9.29	130	0.660	-3.61	230	1.000	0.00	330	0.660	-3.61
32	0.355	-9.00	132	0.674	-3.43	232	0.999	-0.01	332	0.644	-3.82
34	0.368	-8.68	134	0.689	-3.24	234	0.998	-0.02	334	0.627	-4.05
36	0.379	-8.43	136	0.702	-3.07	236	0.997	-0.03	336	0.609	-4.31
38	0.389	-8.20	138	0.713	-2.94	238	0.995	-0.04	338	0.590	-4.58
40	0.399	-7.98	140	0.725	-2.79	240	0.993	-0.06	340	0.570	-4.88
42	0.405	-7.85	142	0.735	-2.67	242	0.990	-0.09	342	0.549	-5.21
44	0.412	-7.70	144	0.744	-2.57	244	0.987	-0.11	344	0.528	-5.55
46	0.416	-7.62	146	0.753	-2.46	246	0.983	-0.15	346	0.506	-5.92
48	0.419	-7.56	148	0.762	-2.36	248	0.979	-0.18	348	0.483	-6.32
50	0.421	-7.51	150	0.770	-2.27	250	0.975	-0.22	350	0.460	-6.74
52	0.419	-7.56	152	0.777	-2.19	252	0.969	-0.27	352	0.437	-7.19
54	0.416	-7.62	154	0.784	-2.11	254	0.964	-0.32	354	0.414	-7.66
56	0.412	-7.70	156	0.790	-2.05	256	0.958	-0.37	356	0.391	-8.16
58	0.405	-7.85	158	0.797	-1.97	258	0.951	-0.44	358	0.369	-8.66
60	0.399	-7.98	160	0.804	-1.89	260	0.945	-0.49	360	0.347	-9.19
62	0.389	-8.20	162	0.810	-1.83	262	0.938	-0.56			
64	0.379	-8.43	164	0.817	-1.76	264	0.931	-0.62			
66	0.368	-8.68	166	0.823	-1.69	266	0.924	-0.69			
68	0.355	-9.00	168	0.830	-1.62	268	0.917	-0.75			
70	0.343	-9.29	170	0.836	-1.56	270	0.910	-0.82			
72	0.330	-9.63	172	0.843	-1.48	272	0.902	-0.90			
74	0.317	-9.98	174	0.850	-1.41	274	0.895	-0.96			
76	0.304	-10.34	176	0.858	-1.33	276	0.887	-1.04			
78	0.293	-10.66	178	0.865	-1.26	278	0.880	-1.11			
80	0.282	-11.00	180	0.872	-1.19	280	0.872	-1.19			
82	0.276	-11.18	182	0.880	-1.11	282	0.865	-1.26			
84	0.271	-11.34	184	0.887	-1.04	284	0.858	-1.33			
86	0.269	-11.40	186	0.895	-0.96	286	0.850	-1.41			
88	0.272	-11.31	188	0.902	-0.90	288	0.843	-1.48			
90	0.274	-11.24	190	0.910	-0.82	290	0.836	-1.56			
92	0.285	-10.90	192	0.917	-0.75	292	0.830	-1.62			
94	0.296	-10.57	194	0.924	-0.69	294	0.823	-1.69			
96	0.311	-10.14	196	0.931	-0.62	296	0.817	-1.76			
98	0.329	-9.66	198	0.938	-0.56	298	0.810	-1.83			

Elevation Pattern

Type:	18H6H	Polarization:	Horizontal
Directivity:		Frequency:	32 (ATSC)
Main Lobe:	18.00 numeric (12.55 dB)	Location:	Fresno, CA
Horizontal:	7.44 numeric (8.72 dB)	Beam Tilt:	1.50 degrees



Tabulated Data for Elevation Pattern

Type: 18H6H

-5 to 10 degrees in 0.25 degree increments.


10 to 90 degrees in 0.50 degree increments.

Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB
-5.00	0.118	-18.56	7.25	0.163	-15.76	29.00	0.057	-24.88	53.50	0.049	-26.20	78.00	0.015	-36.48
-4.75	0.102	-19.83	7.50	0.155	-16.19	29.50	0.044	-27.13	54.00	0.039	-28.18	78.50	0.009	-40.92
-4.50	0.107	-19.41	7.75	0.160	-15.92	30.00	0.035	-29.12	54.50	0.029	-30.75	79.00	0.007	-43.10
-4.25	0.135	-17.39	8.00	0.174	-15.19	30.50	0.037	-28.64	55.00	0.024	-32.40	79.50	0.010	-40.00
-4.00	0.175	-15.14	8.25	0.188	-14.52	31.00	0.049	-26.20	55.50	0.029	-30.75	80.00	0.014	-37.08
-3.75	0.219	-13.19	8.50	0.199	-14.02	31.50	0.058	-24.73	56.00	0.040	-27.96	80.50	0.018	-34.89
-3.50	0.259	-11.73	8.75	0.202	-13.89	32.00	0.060	-24.44	56.50	0.050	-26.02	81.00	0.022	-33.15
-3.25	0.291	-10.72	9.00	0.199	-14.02	32.50	0.054	-25.35	57.00	0.058	-24.73	81.50	0.026	-31.70
-3.00	0.311	-10.14	9.25	0.187	-14.56	33.00	0.042	-27.54	57.50	0.061	-24.29	82.00	0.029	-30.75
-2.75	0.319	-9.92	9.50	0.170	-15.39	33.50	0.033	-29.63	58.00	0.061	-24.29	82.50	0.031	-30.17
-2.50	0.311	-10.14	9.75	0.149	-16.54	34.00	0.033	-29.63	58.50	0.058	-24.73	83.00	0.033	-29.63
-2.25	0.289	-10.78	10.00	0.127	-17.92	34.50	0.044	-27.13	59.00	0.050	-26.02	83.50	0.034	-29.37
-2.00	0.252	-11.97	10.50	0.098	-20.18	35.00	0.053	-25.51	59.50	0.040	-27.96	84.00	0.034	-29.37
-1.75	0.209	-13.60	11.00	0.108	-19.33	35.50	0.058	-24.73	60.00	0.030	-30.46	84.50	0.034	-29.37
-1.50	0.174	-15.19	11.50	0.132	-17.59	36.00	0.054	-25.35	60.50	0.022	-33.15	85.00	0.033	-29.63
-1.25	0.177	-15.04	12.00	0.141	-17.02	36.50	0.045	-26.94	61.00	0.025	-32.04	85.50	0.032	-29.90
-1.00	0.232	-12.69	12.50	0.129	-17.79	37.00	0.034	-29.37	61.50	0.034	-29.37	86.00	0.030	-30.46
-0.75	0.321	-9.87	13.00	0.100	-20.00	37.50	0.029	-30.75	62.00	0.044	-27.13	86.50	0.028	-31.06
-0.50	0.426	-7.41	13.50	0.074	-22.62	38.00	0.036	-28.87	62.50	0.054	-25.35	87.00	0.026	-31.70
-0.25	0.536	-5.42	14.00	0.076	-22.38	38.50	0.047	-26.56	63.00	0.062	-24.15	87.50	0.022	-33.15
0.00	0.643	-3.84	14.50	0.096	-20.35	39.00	0.054	-25.35	63.50	0.067	-23.48	88.00	0.020	-33.98
0.25	0.744	-2.57	15.00	0.110	-19.17	39.50	0.056	-25.04	64.00	0.068	-23.35	88.50	0.017	-35.39
0.50	0.831	-1.61	15.50	0.106	-19.49	40.00	0.051	-25.85	64.50	0.067	-23.48	89.00	0.013	-37.72
0.75	0.904	-0.88	16.00	0.087	-21.21	40.50	0.041	-27.74	65.00	0.063	-24.01	89.50	0.009	-40.92
1.00	0.956	-0.39	16.50	0.065	-23.74	41.00	0.030	-30.46	65.50	0.056	-25.04	90.00	0.000	---
1.25	0.990	-0.09	17.00	0.058	-24.73	41.50	0.028	-31.06	66.00	0.046	-26.74			
1.50	1.000	0.00	17.50	0.072	-22.85	42.00	0.036	-28.87	66.50	0.036	-28.87			
1.75	0.989	-0.10	18.00	0.087	-21.21	42.50	0.046	-26.74	67.00	0.025	-32.04			
2.00	0.957	-0.38	18.50	0.090	-20.92	43.00	0.053	-25.51	67.50	0.018	-34.89			
2.25	0.906	-0.86	19.00	0.080	-21.94	43.50	0.056	-25.04	68.00	0.019	-34.42			
2.50	0.839	-1.52	19.50	0.061	-24.29	44.00	0.051	-25.85	68.50	0.028	-31.06			
2.75	0.761	-2.37	20.00	0.048	-26.38	44.50	0.043	-27.33	69.00	0.038	-28.40			
3.00	0.674	-3.43	20.50	0.054	-25.35	45.00	0.032	-29.90	69.50	0.049	-26.20			
3.25	0.587	-4.63	21.00	0.070	-23.10	45.50	0.026	-31.70	70.00	0.058	-24.73			
3.50	0.504	-5.95	21.50	0.079	-22.05	46.00	0.031	-30.17	70.50	0.066	-23.61			
3.75	0.434	-7.25	22.00	0.075	-22.50	46.50	0.041	-27.74	71.00	0.071	-22.97			
4.00	0.383	-8.34	22.50	0.062	-24.15	47.00	0.051	-25.85	71.50	0.076	-22.38			
4.25	0.354	-9.02	23.00	0.046	-26.74	47.50	0.056	-25.04	72.00	0.079	-22.05			
4.50	0.347	-9.19	23.50	0.042	-27.54	48.00	0.056	-25.04	72.50	0.079	-22.05			
4.75	0.352	-9.07	24.00	0.053	-25.51	48.50	0.050	-26.02	73.00	0.078	-22.16			
5.00	0.360	-8.87	24.50	0.066	-23.61	49.00	0.041	-27.74	73.50	0.075	-22.50			
5.25	0.365	-8.75	25.00	0.070	-23.10	49.50	0.031	-30.17	74.00	0.071	-22.97			
5.50	0.361	-8.85	25.50	0.064	-23.88	50.00	0.026	-31.70	74.50	0.066	-23.61			
5.75	0.349	-9.14	26.00	0.051	-25.85	50.50	0.030	-30.46	75.00	0.059	-24.58			
6.00	0.326	-9.74	26.50	0.038	-28.40	51.00	0.040	-27.96	75.50	0.052	-25.68			
6.25	0.295	-10.60	27.00	0.040	-27.96	51.50	0.050	-26.02	76.00	0.045	-26.94			
6.50	0.259	-11.73	27.50	0.052	-25.68	52.00	0.057	-24.88	76.50	0.037	-28.64			
6.75	0.221	-13.11	28.00	0.063	-24.01	52.50	0.058	-24.73	77.00	0.030	-30.46			
7.00	0.187	-14.56	28.50	0.064	-23.88	53.00	0.056	-25.04	77.50	0.022	-33.15			

Azimuth Pattern

Type:	ATW-V10		Polarization:	Vertical
Directivity:	2.83 numeric	(4.52 dB)	Frequency:	32 (ATSC)
Peak(s) at:			Location:	Fresno, CA
			NOTE: Pattern shape and directivity may vary with channel and mounting configuration.	

Relative Field



Tabulated Data for Azimuth PatternType: ATW-V10

Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB
0	0.266	-11.50	100	0.266	-11.50	200	0.915	-0.77	300	0.582	-4.70
2	0.256	-11.84	102	0.275	-11.21	202	0.926	-0.67	302	0.563	-4.99
4	0.247	-12.15	104	0.285	-10.90	204	0.936	-0.57	304	0.544	-5.29
6	0.237	-12.51	106	0.293	-10.66	206	0.946	-0.48	306	0.526	-5.58
8	0.228	-12.84	108	0.302	-10.40	208	0.954	-0.41	308	0.509	-5.87
10	0.219	-13.19	110	0.310	-10.17	210	0.962	-0.34	310	0.493	-6.14
12	0.211	-13.51	112	0.318	-9.95	212	0.968	-0.28	312	0.477	-6.43
14	0.202	-13.89	114	0.327	-9.71	214	0.975	-0.22	314	0.463	-6.69
16	0.194	-14.24	116	0.334	-9.53	216	0.980	-0.18	316	0.449	-6.96
18	0.188	-14.52	118	0.341	-9.34	218	0.985	-0.13	318	0.436	-7.21
20	0.182	-14.80	120	0.348	-9.17	220	0.989	-0.10	320	0.426	-7.41
22	0.176	-15.09	122	0.355	-9.00	222	0.994	-0.05	322	0.415	-7.64
24	0.172	-15.29	124	0.361	-8.85	224	0.997	-0.03	324	0.406	-7.83
26	0.169	-15.44	126	0.368	-8.68	226	0.998	-0.02	326	0.396	-8.05
28	0.166	-15.60	128	0.375	-8.52	228	0.999	-0.01	328	0.390	-8.18
30	0.164	-15.70	130	0.381	-8.38	230	1.000	0.00	330	0.382	-8.36
32	0.162	-15.81	132	0.389	-8.20	232	0.999	-0.01	332	0.375	-8.52
34	0.161	-15.86	134	0.396	-8.05	234	0.998	-0.02	334	0.368	-8.68
36	0.161	-15.86	136	0.406	-7.83	236	0.997	-0.03	336	0.361	-8.85
38	0.161	-15.86	138	0.415	-7.64	238	0.994	-0.05	338	0.355	-9.00
40	0.160	-15.92	140	0.425	-7.43	240	0.989	-0.10	340	0.348	-9.17
42	0.160	-15.92	142	0.436	-7.21	242	0.985	-0.13	342	0.341	-9.34
44	0.160	-15.92	144	0.450	-6.94	244	0.980	-0.18	344	0.334	-9.53
46	0.161	-15.86	146	0.463	-6.69	246	0.975	-0.22	346	0.327	-9.71
48	0.161	-15.86	148	0.477	-6.43	248	0.968	-0.28	348	0.318	-9.95
50	0.161	-15.86	150	0.493	-6.14	250	0.962	-0.34	350	0.311	-10.14
52	0.161	-15.86	152	0.509	-5.87	252	0.954	-0.41	352	0.303	-10.37
54	0.161	-15.86	154	0.526	-5.58	254	0.946	-0.48	354	0.294	-10.63
56	0.160	-15.92	156	0.544	-5.29	256	0.936	-0.57	356	0.285	-10.90
58	0.160	-15.92	158	0.563	-4.99	258	0.926	-0.67	358	0.275	-11.21
60	0.160	-15.92	160	0.581	-4.72	260	0.915	-0.77	360	0.266	-11.50
62	0.161	-15.86	162	0.601	-4.42	262	0.904	-0.88			
64	0.161	-15.86	164	0.620	-4.15	264	0.892	-0.99			
66	0.161	-15.86	166	0.639	-3.89	266	0.879	-1.12			
68	0.162	-15.81	168	0.659	-3.62	268	0.865	-1.26			
70	0.164	-15.70	170	0.678	-3.38	270	0.851	-1.40			
72	0.166	-15.60	172	0.698	-3.12	272	0.836	-1.56			
74	0.169	-15.44	174	0.717	-2.89	274	0.821	-1.71			
76	0.172	-15.29	176	0.736	-2.66	276	0.805	-1.88			
78	0.176	-15.09	178	0.754	-2.45	278	0.789	-2.06			
80	0.182	-14.80	180	0.772	-2.25	280	0.772	-2.25			
82	0.188	-14.52	182	0.788	-2.07	282	0.754	-2.45			
84	0.194	-14.24	184	0.805	-1.88	284	0.736	-2.66			
86	0.202	-13.89	186	0.821	-1.71	286	0.718	-2.88			
88	0.211	-13.51	188	0.836	-1.56	288	0.698	-3.12			
90	0.219	-13.19	190	0.850	-1.41	290	0.678	-3.38			
92	0.228	-12.84	192	0.864	-1.27	292	0.659	-3.62			
94	0.237	-12.51	194	0.878	-1.13	294	0.639	-3.89			
96	0.247	-12.15	196	0.891	-1.00	296	0.620	-4.15			
98	0.256	-11.84	198	0.903	-0.89	298	0.601	-4.42			

Elevation Pattern

Type: 15H6V

Polarization:

Vertical

Directivity:

Frequency:

32 (ATSC)

Main Lobe: 15.00 numeric (11.76 dB)

Location:


Fresno, CA

Horizontal: 6.47 numeric (8.11 dB)

Beam Tilt:

1.50 degrees

Relative Field



Tabulated Data for Elevation Pattern

Type:

15H6V

-5 to 10 degrees in 0.25 degree increments.

10 to 90 degrees in 0.50 degree increments.

Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB
-5.00	0.079	-22.05	7.25	0.239	-12.43	29.00	0.013	-37.72	53.50	0.021	-33.56	78.00	0.024	-32.40
-4.75	0.108	-19.33	7.50	0.203	-13.85	29.50	0.030	-30.46	54.00	0.006	-44.44	78.50	0.020	-33.98
-4.50	0.152	-16.36	7.75	0.173	-15.24	30.00	0.045	-26.94	54.50	0.016	-35.92	79.00	0.018	-34.89
-4.25	0.202	-13.89	8.00	0.154	-16.25	30.50	0.051	-25.85	55.00	0.033	-29.63	79.50	0.018	-34.89
-4.00	0.249	-12.08	8.25	0.147	-16.65	31.00	0.054	-25.35	55.50	0.046	-26.74	80.00	0.021	-33.56
-3.75	0.292	-10.69	8.50	0.149	-16.54	31.50	0.058	-24.73	56.00	0.058	-24.73	80.50	0.024	-32.40
-3.50	0.326	-9.74	8.75	0.155	-16.19	32.00	0.065	-23.74	56.50	0.066	-23.61	81.00	0.026	-31.70
-3.25	0.351	-9.09	9.00	0.160	-15.92	32.50	0.075	-22.50	57.00	0.069	-23.22	81.50	0.029	-30.75
-3.00	0.363	-8.80	9.25	0.160	-15.92	33.00	0.085	-21.41	57.50	0.069	-23.22	82.00	0.031	-30.17
-2.75	0.361	-8.85	9.50	0.155	-16.19	33.50	0.090	-20.92	58.00	0.066	-23.61	82.50	0.033	-29.63
-2.50	0.346	-9.22	9.75	0.145	-16.77	34.00	0.088	-21.11	58.50	0.059	-24.58	83.00	0.034	-29.37
-2.25	0.318	-9.95	10.00	0.132	-17.59	34.50	0.079	-22.05	59.00	0.052	-25.68	83.50	0.034	-29.37
-2.00	0.281	-11.03	10.50	0.104	-19.66	35.00	0.061	-24.29	59.50	0.048	-26.38	84.00	0.034	-29.37
-1.75	0.242	-12.32	11.00	0.104	-19.66	35.50	0.040	-27.96	60.00	0.045	-26.94	84.50	0.034	-29.37
-1.50	0.217	-13.27	11.50	0.135	-17.39	36.00	0.015	-36.48	60.50	0.046	-26.74	85.00	0.033	-29.63
-1.25	0.227	-12.88	12.00	0.168	-15.49	36.50	0.010	-40.00	61.00	0.051	-25.85	85.50	0.032	-29.90
-1.00	0.279	-11.09	12.50	0.185	-14.66	37.00	0.029	-30.75	61.50	0.058	-24.73	86.00	0.030	-30.46
-0.75	0.359	-8.90	13.00	0.179	-14.94	37.50	0.044	-27.13	62.00	0.064	-23.88	86.50	0.028	-31.06
-0.50	0.456	-6.82	13.50	0.152	-16.36	38.00	0.053	-25.51	62.50	0.068	-23.35	87.00	0.025	-32.04
-0.25	0.557	-5.08	14.00	0.113	-18.94	38.50	0.057	-24.88	63.00	0.070	-23.10	87.50	0.022	-33.15
0.00	0.657	-3.65	14.50	0.075	-22.50	39.00	0.057	-24.88	63.50	0.069	-23.22	88.00	0.020	-33.98
0.25	0.750	-2.50	15.00	0.057	-24.88	39.50	0.057	-24.88	64.00	0.066	-23.61	88.50	0.016	-35.92
0.50	0.833	-1.59	15.50	0.063	-24.01	40.00	0.060	-24.44	64.50	0.059	-24.58	89.00	0.013	-37.72
0.75	0.901	-0.91	16.00	0.071	-22.97	40.50	0.068	-23.35	65.00	0.050	-26.02	89.50	0.009	-40.92
1.00	0.952	-0.43	16.50	0.069	-23.22	41.00	0.074	-22.62	65.50	0.040	-27.96	90.00	0.000	---
1.25	0.986	-0.12	17.00	0.063	-24.01	41.50	0.078	-22.16	66.00	0.028	-31.06			
1.50	1.000	0.00	17.50	0.069	-23.22	42.00	0.077	-22.27	66.50	0.015	-36.48			
1.75	0.993	-0.06	18.00	0.089	-21.01	42.50	0.071	-22.97	67.00	0.008	-41.94			
2.00	0.967	-0.29	18.50	0.114	-18.86	43.00	0.058	-24.73	67.50	0.017	-35.39			
2.25	0.924	-0.69	19.00	0.130	-17.72	43.50	0.041	-27.74	68.00	0.029	-30.75			
2.50	0.864	-1.27	19.50	0.133	-17.52	44.00	0.021	-33.56	68.50	0.042	-27.54			
2.75	0.793	-2.01	20.00	0.120	-18.42	44.50	0.003	-50.46	69.00	0.053	-25.51			
3.00	0.712	-2.95	20.50	0.096	-20.35	45.00	0.020	-33.98	69.50	0.063	-24.01			
3.25	0.629	-4.03	21.00	0.064	-23.88	45.50	0.037	-28.64	70.00	0.071	-22.97			
3.50	0.547	-5.24	21.50	0.034	-29.37	46.00	0.050	-26.02	70.50	0.079	-22.05			
3.75	0.473	-6.50	22.00	0.026	-31.70	46.50	0.058	-24.73	71.00	0.083	-21.62			
4.00	0.415	-7.64	22.50	0.040	-27.96	47.00	0.061	-24.29	71.50	0.085	-21.41			
4.25	0.377	-8.47	23.00	0.050	-26.02	47.50	0.060	-24.44	72.00	0.087	-21.21			
4.50	0.363	-8.80	23.50	0.053	-25.51	48.00	0.057	-24.88	72.50	0.086	-21.31			
4.75	0.365	-8.75	24.00	0.056	-25.04	48.50	0.054	-25.35	73.00	0.084	-21.51			
5.00	0.378	-8.45	24.50	0.065	-23.74	49.00	0.054	-25.35	73.50	0.080	-21.94			
5.25	0.393	-8.11	25.00	0.080	-21.94	49.50	0.058	-24.73	74.00	0.075	-22.50			
5.50	0.402	-7.92	25.50	0.096	-20.35	50.00	0.064	-23.88	74.50	0.070	-23.10			
5.75	0.404	-7.87	26.00	0.106	-19.49	50.50	0.069	-23.22	75.00	0.063	-24.01			
6.00	0.396	-8.05	26.50	0.106	-19.49	51.00	0.070	-23.10	75.50	0.056	-25.04			
6.25	0.378	-8.45	27.00	0.097	-20.26	51.50	0.069	-23.22	76.00	0.049	-26.20			
6.50	0.351	-9.09	27.50	0.076	-22.38	52.00	0.062	-24.15	76.50	0.042	-27.54			
6.75	0.317	-9.98	28.00	0.050	-26.02	52.50	0.052	-25.68	77.00	0.035	-29.12			
7.00	0.278	-11.12	28.50	0.022	-33.15	53.00	0.037	-28.64	77.50	0.029	-30.75			