

RF COMPLIANCE EXHIBIT

May 23 2019


The proposed W44DH-D facility will comply with the FCC Rules concerning human exposure to radio frequency (RF) energy. The calculation of RF energy at 2-m above ground was made under the procedures of OET Bulletin No. 65. The formula employed is as follows:

$$S = \frac{(33.4)F^2P}{R^2}$$

where, S = power density in $\mu\text{W}/\text{cm}^2$, F = relative field factor at the angle to the calculation point, P = the total effective radiated power relative to a dipole in watts, and R = distance from the antenna radiation center to the calculation point in meters.

The proposed antenna will be mounted with radiation center at a height of 27.4 meters on the existing tower structure. The power density at 2 meters above ground level at the base of the tower, based on a "worst-case" vertical relative field value of 0.226 for any depression angle below horizon greater than 10 degrees, a total ERP of 15 kW (H) and an antenna center of radiation height above ground level of 27.4 meters, the calculated power density at two meters above ground level at the base of the tower is 39.7 microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$), or 10.1 % of the Commission's recommended limit applicable to uncontrolled exposure areas, 391.3 $\mu\text{W}/\text{cm}^2$, for channel 33. Since W32FB-D is concurrently proposing to operate with identical parameters, but on channel 32 (the two stations diplexed into the same antenna), the proposed W32FB-D operation would cause an RF exposure of 39.7 microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$), or 10.2 % of the recommended limit applicable for an uncontrolled exposure area, 387.3 $\mu\text{W}/\text{cm}^2$ for channel 32; thus the total RF exposure of both facilities is expected to be 20.3% of the FCC recommended limit. Since the total RF exposure will not exceed the FCC limits for uncontrolled environments, the proposal complies with the FCC limits for human exposure to RF radiation.

The applicant will verify that access to the tower site is restricted and the site will be appropriately marked with RFR warning signs. In addition, in the event that workers or other authorized personnel need to enter the restricted area or climb the tower, appropriate measures will be taken to assure worker safety with respect to radio frequency radiation exposure. Such procedures include reducing the average exposure by spreading out the work over a longer period of time, wearing RFR exposure monitors or scheduling work when station W44DH-D is shut down.



Grafton Olivera, P.E.