
TECHNICAL EXHIBIT

KWYT-LD, FI 57522
HISPANAVISION, INC., YAKIMA, WA
MINOR CHANGE TO LICENSED FACILITY

The within application is for a Minor Change to the above-referenced facility including the following changes:


1. ERP changed from 13.7 kW to 15 kW.
2. Antenna changed from Jampro JA-SS-8 to JA-SS-8/D36 SEO Elliptical polarization with 30% of the total H ERP in the Vertical Plane, 0.75° Electrical Beamtilt and 5% first Null Fill.

James R. McDonald
18 January 2021




Channel: 36
Site: KWYT-LD

Model: JA/SS-8 / D36 SEO
Description: UHF Slot Antenna
Notes: Elliptically Polarized



Channel: 36
Site: KWYT-LD

Model: JA/SS-8 / D36 SEO
Description: UHF Slot Antenna
-0.75° Beam Tilt, 5% Null Fill



Channel: 36
Site: KWYT-LD

Model: JA/SS-8 / D36 SEO
Description: UHF Slot Antenna
-0.75° Beam Tilt, 5% Null Fill

Elevation Pattern Tabulation

RELATIVE FIELD VS ELEVATION ANGLE

ELEVATION ANGLE	RELATIVE FIELD	ELEVATION ANGLE	RELATIVE FIELD	ELEVATION ANGLE	RELATIVE FIELD
10	0.216	-26	0.098	-61	0.023
9	0.215	-27	0.098	-62	0.013
8	0.171	-28	0.084	-63	0.011
7	0.087	-29	0.060	-64	0.020
6	0.083	-30	0.029	-65	0.031
5	0.240	-31	0.004	-66	0.041
4	0.425	-32	0.035	-67	0.050
3	0.611	-33	0.059	-68	0.058
2	0.777	-34	0.075	-69	0.064
1	0.906	-35	0.080	-70	0.069
0	0.983	-36	0.075	-71	0.072
-1	0.998	-37	0.062	-72	0.074
-2	0.950	-38	0.043	-73	0.075
-3	0.845	-39	0.021	-74	0.074
-4	0.695	-40	0.012	-75	0.072
-5	0.517	-41	0.030	-76	0.070
-6	0.330	-42	0.048	-77	0.066
-7	0.155	-43	0.061	-78	0.063
-8	0.051	-44	0.067	-79	0.058
-9	0.130	-45	0.067	-80	0.054
-10	0.195	-46	0.060	-81	0.049
-11	0.218	-47	0.049	-82	0.044
-12	0.201	-48	0.035	-83	0.038
-13	0.155	-49	0.021	-84	0.033
-14	0.092	-50	0.015	-85	0.027
-15	0.039	-51	0.025	-86	0.022
-16	0.061	-52	0.038	-87	0.016
-17	0.104	-53	0.049	-88	0.011
-18	0.129	-54	0.058	-89	0.006
-19	0.132	-55	0.062	-90	0.000
-20	0.114	-56	0.063		
-21	0.080	-57	0.060		
-22	0.038	-58	0.054		
-23	0.020	-59	0.045		
-24	0.054	-60	0.035		
-25	0.082				

Channel: 36
Site: KWYT-LD

Model: JA/SS-8 / D36 SEO
Description: UHF Slot Antenna
-0.75° Beam Tilt, 5% Null Fill

AZIMUTH	FIELD	dB
0	1.000	0.00
10	0.994	-0.05
20	0.978	-0.19
30	0.951	-0.44
40	0.915	-0.77
50	0.871	-1.20
60	0.820	-1.72
70	0.767	-2.30
80	0.715	-2.91
90	0.668	-3.50
100	0.631	-4.00
110	0.609	-4.31
120	0.602	-4.41
130	0.608	-4.32
140	0.623	-4.11
150	0.642	-3.85
160	0.659	-3.62
170	0.672	-3.45
180	0.676	-3.40
190	0.672	-3.45
200	0.659	-3.62
210	0.642	-3.85
220	0.623	-4.11
230	0.608	-4.32
240	0.602	-4.41
250	0.609	-4.31
260	0.631	-4.00
270	0.668	-3.50
280	0.715	-2.91
290	0.767	-2.30
300	0.820	-1.72
310	0.871	-1.20
320	0.915	-0.77
330	0.951	-0.44
340	0.978	-0.19
350	0.994	-0.05

Channel: 36
Site: KWYT-LD

Model: JA/SS-8 / D36 SEO
Description: UHF Slot Antenna
Notes: Elliptically Polarized