

11-07-2021

Terrain Data: GLOBE 30 Sec

FMOver Analysis

NEW!

WTTT 0000113853

Channel = 202A

Max ERP = 0.92 kW

RCAMSL = 232 m

N. Lat. 39 44 07.30

W. Lng. 89 31 01.10

Protected

60 dBu

Channel = 205A

Max ERP = 0.2 kW

RCAMSL = 250 m

N. Lat. 39 48 05.50

W. Lng. 89 38 59.00

Interfering

100 dBu

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
243.0	000.9200	0058.3	013.7	183.6	000.2000	0070.3	013.6	54.98	
244.0	000.9200	0058.0	013.7	184.0	000.2000	0070.2	013.4	55.26	
245.0	000.9200	0057.8	013.6	184.4	000.2000	0070.1	013.2	55.55	
246.0	000.9200	0057.7	013.6	184.9	000.2000	0069.9	013.0	55.83	
247.0	000.9200	0057.8	013.7	185.4	000.2000	0069.8	012.8	56.10	
248.0	000.9200	0058.0	013.7	186.0	000.2000	0069.7	012.6	56.39	
249.0	000.9200	0057.9	013.7	186.5	000.2000	0069.7	012.3	56.71	
250.0	000.9200	0057.7	013.6	186.9	000.2000	0069.7	012.1	57.05	
251.0	000.9200	0057.2	013.6	187.2	000.2000	0069.7	011.9	57.41	
252.0	000.9200	0056.9	013.5	187.5	000.2000	0069.8	011.7	57.77	
253.0	000.9200	0056.8	013.5	188.0	000.2000	0069.8	011.4	58.13	
254.0	000.9200	0056.9	013.5	188.5	000.2000	0069.9	011.2	58.47	
255.0	000.9200	0057.0	013.6	189.1	000.2000	0069.9	011.0	58.82	
256.0	000.9200	0057.0	013.6	189.6	000.2000	0069.9	010.8	59.18	
257.0	000.9200	0056.7	013.5	189.9	000.2000	0069.9	010.6	59.57	
258.0	000.9200	0056.2	013.5	190.2	000.2000	0069.9	010.3	59.97	
259.0	000.9200	0055.8	013.4	190.4	000.2000	0069.9	010.1	60.37	
260.0	000.9200	0055.5	013.4	190.7	000.2000	0069.8	009.9	60.77	
261.0	000.9200	0055.5	013.4	191.2	000.2000	0069.8	009.6	61.15	
262.0	000.9200	0055.5	013.4	191.6	000.2000	0069.7	009.4	61.54	
263.0	000.9200	0055.4	013.4	192.1	000.2000	0069.7	009.2	61.94	
264.0	000.9200	0055.3	013.4	192.5	000.2000	0069.7	009.0	62.35	
265.0	000.9200	0055.3	013.4	192.9	000.2000	0069.7	008.8	62.76	
266.0	000.9200	0055.2	013.4	193.4	000.2000	0069.7	008.5	63.17	
267.0	000.9200	0055.3	013.4	193.9	000.2000	0069.6	008.3	63.58	
268.0	000.9200	0055.3	013.4	194.4	000.2000	0069.5	008.1	63.99	
269.0	000.9200	0055.2	013.4	194.8	000.2000	0069.4	007.9	64.42	
270.0	000.9200	0055.2	013.4	195.2	000.2000	0069.4	007.6	64.89	
271.0	000.9200	0055.2	013.3	195.6	000.2000	0069.3	007.4	65.39	
272.0	000.9200	0055.0	013.3	196.0	000.2000	0069.2	007.2	65.94	
273.0	000.9200	0054.8	013.3	196.2	000.2000	0069.2	006.9	66.52	
274.0	000.9200	0054.6	013.3	196.4	000.2000	0069.2	006.7	67.12	
275.0	000.9200	0054.4	013.3	196.7	000.2000	0069.1	006.5	67.74	
276.0	000.9200	0054.4	013.3	197.1	000.2000	0069.1	006.3	68.38	
277.0	000.9200	0054.4	013.3	197.5	000.2000	0069.2	006.0	69.06	
278.0	000.9200	0054.4	013.3	197.9	000.2000	0069.2	005.8	69.78	

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
279.0	000.9200	0054.5	013.3	198.4	000.2000	0069.3	005.6	70.51
280.0	000.9200	0054.7	013.3	199.0	000.2000	0069.3	005.4	71.27
281.0	000.9200	0054.8	013.3	199.6	000.2000	0069.4	005.1	72.04
282.0	000.9200	0054.9	013.3	200.1	000.2000	0069.4	004.9	72.82
283.0	000.9200	0055.0	013.3	200.6	000.2000	0069.4	004.7	73.62
284.0	000.9200	0055.0	013.3	201.0	000.2000	0069.3	004.4	74.46
285.0	000.9200	0055.1	013.3	201.5	000.2000	0069.3	004.2	75.36
286.0	000.9200	0055.2	013.3	202.0	000.2000	0069.2	004.0	76.32
287.0	000.9200	0055.3	013.4	202.5	000.2000	0069.1	003.7	77.32
288.0	000.9200	0055.4	013.4	203.0	000.2000	0069.1	003.5	78.38
289.0	000.9200	0055.5	013.4	203.6	000.2000	0069.0	003.3	79.50
290.0	000.9200	0055.7	013.4	204.4	000.2000	0069.0	003.1	80.70
291.0	000.9200	0056.1	013.5	205.5	000.2000	0068.9	002.8	82.07
292.0	000.9200	0056.4	013.5	206.8	000.2000	0068.8	002.6	83.60
293.0	000.9127	0056.8	013.5	207.6	000.2000	0068.7	002.4	85.29
294.0	000.8710	0057.0	013.4	204.8	000.2000	0069.0	002.1	87.20
295.0	000.8320	0057.2	013.3	200.9	000.2000	0069.3	001.9	89.13
296.0	000.7940	0057.2	013.1	195.6	000.2000	0069.3	001.7	90.95
297.0	000.7585	0057.4	013.0	189.1	000.2000	0069.9	001.5	96.49
298.0	000.7238	0057.7	012.9	181.3	000.2000	0071.1	001.3	97.53
299.0	000.6916	0058.1	012.8	172.1	000.2000	0070.4	001.2	98.50
300.0	000.6600	0058.5	012.7	160.7	000.2000	0072.0	001.1	99.22
301.0	000.6307	0058.7	012.6	147.4	000.2000	0076.4	001.1	99.41
302.0	000.6021	0058.5	012.4	134.0	000.2000	0079.2	001.1	98.86
303.0	000.5756	0058.2	012.3	123.0	000.2000	0079.2	001.3	97.88
304.0	000.6021	0058.1	012.4	112.3	000.2000	0078.3	001.2	98.55
305.0	000.6307	0058.1	012.5	099.8	000.2000	0080.3	001.1	99.02
306.0	000.6616	0058.2	012.7	085.9	000.2000	0080.2	001.1	99.11
307.0	000.6916	0058.3	012.8	072.9	000.2000	0076.1	001.2	98.61
308.0	000.7255	0058.4	013.0	061.5	000.2000	0076.7	001.3	97.75
309.0	000.7585	0058.6	013.1	052.2	000.2000	0079.1	001.5	96.70
310.0	000.7940	0058.9	013.3	044.3	000.2000	0078.8	001.7	91.72
311.0	000.8320	0059.2	013.5	038.5	000.2000	0078.4	001.9	89.78
312.0	000.8710	0059.3	013.6	034.5	000.2000	0079.1	002.1	87.85
313.0	000.9127	0059.3	013.8	031.8	000.2000	0079.1	002.4	85.92
314.0	000.9200	0059.4	013.8	032.0	000.2000	0079.1	002.6	84.24
315.0	000.9200	0059.6	013.8	032.6	000.2000	0079.1	002.9	82.72
316.0	000.9200	0059.6	013.8	033.5	000.2000	0079.1	003.1	81.39
317.0	000.9200	0059.5	013.8	034.7	000.2000	0079.1	003.3	80.25
318.0	000.9200	0059.6	013.8	035.4	000.2000	0079.1	003.6	79.13
319.0	000.9200	0059.9	013.9	035.7	000.2000	0079.0	003.8	78.04
320.0	000.9200	0060.4	013.9	035.9	000.2000	0079.0	004.1	76.99
321.0	000.9200	0060.5	013.9	036.5	000.2000	0078.9	004.3	76.02
322.0	000.9200	0060.5	013.9	037.4	000.2000	0078.6	004.5	75.11
323.0	000.9200	0060.4	013.9	038.3	000.2000	0078.4	004.8	74.26
324.0	000.9200	0060.3	013.9	039.1	000.2000	0078.2	005.0	73.46
325.0	000.9200	0060.3	013.9	039.8	000.2000	0078.2	005.2	72.66
326.0	000.9200	0060.3	013.9	040.4	000.2000	0078.2	005.5	71.88
327.0	000.9200	0060.3	013.9	041.1	000.2000	0078.2	005.7	71.14
328.0	000.9200	0060.3	013.9	041.7	000.2000	0078.3	005.9	70.43
329.0	000.9200	0060.4	013.9	042.3	000.2000	0078.4	006.2	69.73

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
330.0	000.9200	0060.6	013.9	042.8	000.2000	0078.5	006.4	69.06
331.0	000.8981	0060.8	013.9	043.9	000.2000	0078.7	006.6	68.49
332.0	000.8764	0061.2	013.8	044.9	000.2000	0078.9	006.9	67.94
333.0	000.8532	0061.3	013.8	046.1	000.2000	0079.1	007.1	67.42
334.0	000.8320	0061.2	013.7	047.3	000.2000	0079.4	007.3	66.94
335.0	000.8112	0061.1	013.6	048.5	000.2000	0079.7	007.5	66.48
336.0	000.7906	0061.3	013.5	049.6	000.2000	0079.8	007.7	66.02
337.0	000.7702	0061.6	013.4	050.4	000.2000	0079.7	007.9	65.56
338.0	000.7485	0062.2	013.4	051.1	000.2000	0079.5	008.1	65.12
339.0	000.7287	0062.9	013.4	051.8	000.2000	0079.3	008.3	64.68
340.0	000.7092	0063.6	013.4	052.4	000.2000	0079.1	008.5	64.24
341.0	000.7238	0064.3	013.5	052.1	000.2000	0079.2	008.8	63.76
342.0	000.7386	0065.2	013.6	051.7	000.2000	0079.4	009.1	63.27
343.0	000.7535	0066.1	013.8	051.3	000.2000	0079.5	009.3	62.77
344.0	000.7686	0067.2	014.0	051.0	000.2000	0079.6	009.6	62.26
345.0	000.7838	0068.1	014.1	050.7	000.2000	0079.7	009.9	61.76
346.0	000.7974	0068.6	014.2	050.7	000.2000	0079.6	010.2	61.29
347.0	000.8129	0068.6	014.3	051.0	000.2000	0079.6	010.4	60.85
348.0	000.8286	0067.9	014.3	051.6	000.2000	0079.4	010.7	60.44
349.0	000.8443	0066.7	014.2	052.4	000.2000	0079.1	010.9	60.07
350.0	000.8603	0065.5	014.2	053.2	000.2000	0078.7	011.1	59.71
351.0	000.8656	0064.5	014.1	054.2	000.2000	0078.3	011.3	59.36
352.0	000.8728	0063.9	014.1	054.9	000.2000	0077.9	011.5	58.99
353.0	000.8782	0063.8	014.1	055.4	000.2000	0077.7	011.7	58.61
354.0	000.8836	0063.8	014.1	055.8	000.2000	0077.5	011.9	58.23
355.0	000.8908	0063.7	014.1	056.3	000.2000	0077.2	012.1	57.86
356.0	000.8962	0063.4	014.1	056.9	000.2000	0077.0	012.3	57.52
357.0	000.9017	0062.9	014.1	057.6	000.2000	0076.8	012.5	57.20
358.0	000.9072	0062.4	014.1	058.2	000.2000	0076.7	012.7	56.89
359.0	000.9145	0062.0	014.1	058.8	000.2000	0076.6	013.0	56.59
000.0	000.9200	0061.6	014.0	059.4	000.2000	0076.5	013.2	56.31
001.0	000.9200	0061.2	014.0	060.1	000.2000	0076.6	013.3	56.05
002.0	000.9200	0060.9	014.0	060.8	000.2000	0076.6	013.5	55.80

11-07-2021

Terrain Data: GLOBE 30 Sec

FMOver Analysis

WTTT 0000113853

NEW!

Channel = 205A

Max ERP = 0.2 kW

RCAMSL = 250 m

N. Lat. 39 48 05.50

W. Lng. 89 38 59.00

Protected

60 dBu

Channel = 202A

Max ERP = 0.92 kW

RCAMSL = 232 m

N. Lat. 39 44 07.30

W. Lng. 89 31 01.10

Interfering

100 dBu

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
063.0	000.2000	0076.8	010.8	351.9	000.8723	0063.9	012.4	62.38	
064.0	000.2000	0076.8	010.8	352.2	000.8739	0063.8	012.2	62.65	
065.0	000.2000	0076.7	010.8	352.5	000.8752	0063.8	012.0	62.92	
066.0	000.2000	0076.6	010.8	352.7	000.8764	0063.8	011.8	63.21	
067.0	000.2000	0076.4	010.7	352.9	000.8774	0063.8	011.6	63.50	
068.0	000.2000	0076.1	010.7	353.0	000.8784	0063.8	011.5	63.80	
069.0	000.2000	0075.9	010.7	353.2	000.8793	0063.8	011.3	64.11	
070.0	000.2000	0075.8	010.7	353.4	000.8804	0063.8	011.1	64.41	
071.0	000.2000	0075.9	010.7	353.6	000.8816	0063.8	010.9	64.72	
072.0	000.2000	0076.0	010.7	353.9	000.8830	0063.8	010.7	65.03	
073.0	000.2000	0076.1	010.7	354.1	000.8844	0063.8	010.5	65.34	
074.0	000.2000	0076.2	010.7	354.3	000.8860	0063.8	010.4	65.66	
075.0	000.2000	0076.3	010.7	354.6	000.8876	0063.8	010.2	65.98	
076.0	000.2000	0076.5	010.7	354.8	000.8894	0063.8	010.0	66.30	
077.0	000.2000	0076.7	010.8	355.0	000.8910	0063.7	009.8	66.62	
078.0	000.2000	0077.0	010.8	355.3	000.8923	0063.6	009.6	66.95	
079.0	000.2000	0077.3	010.8	355.5	000.8937	0063.6	009.4	67.28	
080.0	000.2000	0077.6	010.8	355.8	000.8951	0063.5	009.3	67.61	
081.0	000.2000	0078.0	010.8	356.1	000.8965	0063.4	009.1	67.94	
082.0	000.2000	0078.4	010.9	356.3	000.8979	0063.3	008.9	68.28	
083.0	000.2000	0078.9	010.9	356.6	000.8994	0063.1	008.7	68.61	
084.0	000.2000	0079.3	010.9	356.8	000.9007	0063.0	008.5	68.95	
085.0	000.2000	0079.7	011.0	357.1	000.9020	0062.9	008.3	69.29	
086.0	000.2000	0080.2	011.0	357.3	000.9035	0062.8	008.1	69.64	
087.0	000.2000	0080.8	011.0	357.6	000.9050	0062.6	007.9	70.00	
088.0	000.2000	0081.4	011.1	357.9	000.9065	0062.5	007.7	70.38	
089.0	000.2000	0081.2	011.0	357.8	000.9059	0062.6	007.5	70.80	
090.0	000.2000	0080.5	011.0	357.4	000.9038	0062.7	007.4	71.25	
091.0	000.2000	0079.9	011.0	357.0	000.9016	0062.9	007.2	71.71	
092.0	000.2000	0079.3	010.9	356.5	000.8992	0063.2	007.0	72.19	
093.0	000.2000	0078.9	010.9	356.2	000.8972	0063.4	006.8	72.69	
094.0	000.2000	0079.2	010.9	356.1	000.8968	0063.4	006.6	73.20	
095.0	000.2000	0079.8	011.0	356.2	000.8973	0063.4	006.4	73.73	

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
096.0	000.2000	0080.3	011.0	356.2	000.8974	0063.3	006.2	74.28
097.0	000.2000	0080.4	011.0	355.9	000.8958	0063.5	006.0	74.86
098.0	000.2000	0080.3	011.0	355.5	000.8935	0063.6	005.8	75.45
099.0	000.2000	0080.2	011.0	355.0	000.8909	0063.7	005.7	76.05
100.0	000.2000	0080.3	011.0	354.6	000.8877	0063.8	005.5	76.67
101.0	000.2000	0080.4	011.0	354.0	000.8837	0063.8	005.3	77.28
102.0	000.2000	0080.4	011.0	353.4	000.8803	0063.8	005.1	77.88
103.0	000.2000	0080.4	011.0	352.7	000.8763	0063.8	004.9	78.48
104.0	000.2000	0080.2	011.0	351.7	000.8707	0064.0	004.7	79.09
105.0	000.2000	0080.0	011.0	350.6	000.8634	0064.9	004.6	79.77
106.0	000.2000	0079.6	010.9	349.2	000.8481	0066.4	004.4	80.50
107.0	000.2000	0079.1	010.9	347.7	000.8243	0068.1	004.3	81.19
108.0	000.2000	0078.8	010.9	346.2	000.7999	0068.6	004.1	81.74
109.0	000.2000	0078.5	010.9	344.5	000.7759	0067.6	004.0	82.13
110.0	000.2000	0078.4	010.9	342.7	000.7491	0065.8	003.8	82.41
111.0	000.2000	0078.3	010.9	340.8	000.7212	0064.2	003.7	82.71
112.0	000.2000	0078.3	010.9	338.8	000.7325	0062.7	003.5	83.28
113.0	000.2000	0078.4	010.9	336.6	000.7776	0061.5	003.4	84.06
114.0	000.2000	0078.5	010.9	334.3	000.8261	0061.2	003.2	84.95
115.0	000.2000	0078.7	010.9	331.7	000.8822	0061.1	003.1	85.88
116.0	000.2000	0078.9	010.9	328.9	000.9200	0060.4	003.0	86.66
117.0	000.2000	0079.0	010.9	325.8	000.9200	0060.3	002.9	87.29
118.0	000.2000	0079.0	010.9	322.5	000.9200	0060.4	002.8	87.87
119.0	000.2000	0079.0	010.9	318.8	000.9200	0059.9	002.7	88.28
120.0	000.2000	0079.0	010.9	315.0	000.9200	0059.6	002.7	88.64
121.0	000.2000	0079.1	010.9	311.0	000.8308	0059.2	002.6	88.47
122.0	000.2000	0079.2	010.9	306.9	000.6872	0058.3	002.6	87.76
123.0	000.2000	0079.2	010.9	302.7	000.5844	0058.3	002.6	87.11
124.0	000.2000	0079.1	010.9	298.5	000.7080	0057.8	002.6	87.78
125.0	000.2000	0079.0	010.9	294.4	000.8547	0057.1	002.7	88.23
126.0	000.2000	0078.8	010.9	290.5	000.9200	0055.9	002.7	88.00
127.0	000.2000	0078.6	010.9	286.8	000.9200	0055.2	002.8	87.43
128.0	000.2000	0078.5	010.9	283.3	000.9200	0055.0	002.9	86.87
129.0	000.2000	0078.6	010.9	279.9	000.9200	0054.6	002.9	86.27
130.0	000.2000	0078.6	010.9	276.7	000.9200	0054.4	003.0	85.66
131.0	000.2000	0078.8	010.9	273.8	000.9200	0054.6	003.1	85.11
132.0	000.2000	0078.9	010.9	271.0	000.9200	0055.2	003.2	84.60
133.0	000.2000	0079.1	010.9	268.5	000.9200	0055.3	003.4	83.99
134.0	000.2000	0079.2	010.9	266.2	000.9200	0055.3	003.5	83.34
135.0	000.2000	0079.4	010.9	264.0	000.9200	0055.3	003.6	82.70
136.0	000.2000	0079.7	011.0	262.0	000.9200	0055.5	003.8	82.06
137.0	000.2000	0079.9	011.0	260.2	000.9200	0055.5	003.9	81.40
138.0	000.2000	0080.0	011.0	258.7	000.9200	0055.9	004.1	80.77
139.0	000.2000	0079.9	011.0	257.5	000.9200	0056.4	004.3	80.15
140.0	000.2000	0079.5	010.9	256.6	000.9200	0056.8	004.4	79.48
141.0	000.2000	0078.9	010.9	256.0	000.9200	0057.0	004.6	78.79
142.0	000.2000	0077.9	010.8	255.8	000.9200	0057.1	004.8	78.09
143.0	000.2000	0076.9	010.8	255.6	000.9200	0057.1	005.0	77.41
144.0	000.2000	0076.1	010.7	255.3	000.9200	0057.1	005.2	76.74
145.0	000.2000	0075.7	010.7	254.9	000.9200	0057.0	005.4	76.11
146.0	000.2000	0075.8	010.7	254.2	000.9200	0056.9	005.6	75.50

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
147.0	000.2000	0076.3	010.7	253.4	000.9200	0056.8	005.7	74.92
148.0	000.2000	0076.6	010.8	252.7	000.9200	0056.8	005.9	74.36
149.0	000.2000	0076.5	010.8	252.3	000.9200	0056.8	006.1	73.80
150.0	000.2000	0076.2	010.7	252.1	000.9200	0056.8	006.3	73.25
151.0	000.2000	0075.5	010.7	252.2	000.9200	0056.8	006.5	72.71
152.0	000.2000	0074.5	010.6	252.4	000.9200	0056.8	006.7	72.18
153.0	000.2000	0073.5	010.6	252.7	000.9200	0056.8	006.9	71.68
154.0	000.2000	0073.0	010.5	252.7	000.9200	0056.8	007.1	71.21
155.0	000.2000	0073.0	010.5	252.5	000.9200	0056.8	007.2	70.77
156.0	000.2000	0073.2	010.5	252.2	000.9200	0056.8	007.4	70.36
157.0	000.2000	0073.2	010.5	252.1	000.9200	0056.8	007.6	69.96
158.0	000.2000	0073.0	010.5	252.1	000.9200	0056.8	007.8	69.57
159.0	000.2000	0072.6	010.5	252.2	000.9200	0056.8	008.0	69.20
160.0	000.2000	0072.3	010.5	252.3	000.9200	0056.8	008.2	68.85
161.0	000.2000	0071.8	010.4	252.5	000.9200	0056.8	008.3	68.51
162.0	000.2000	0071.4	010.4	252.6	000.9200	0056.8	008.5	68.16
163.0	000.2000	0071.1	010.4	252.8	000.9200	0056.8	008.7	67.83
164.0	000.2000	0070.8	010.4	252.9	000.9200	0056.8	008.9	67.50
165.0	000.2000	0070.6	010.4	253.0	000.9200	0056.8	009.1	67.17
166.0	000.2000	0070.5	010.4	253.1	000.9200	0056.8	009.2	66.84
167.0	000.2000	0070.5	010.4	253.2	000.9200	0056.8	009.4	66.52
168.0	000.2000	0070.4	010.3	253.3	000.9200	0056.8	009.6	66.20
169.0	000.2000	0070.3	010.3	253.4	000.9200	0056.8	009.8	65.88
170.0	000.2000	0070.3	010.3	253.6	000.9200	0056.8	010.0	65.57
171.0	000.2000	0070.3	010.3	253.7	000.9200	0056.8	010.1	65.26
172.0	000.2000	0070.4	010.3	253.8	000.9200	0056.8	010.3	64.95
173.0	000.2000	0070.2	010.3	254.0	000.9200	0056.9	010.5	64.65
174.0	000.2000	0069.9	010.3	254.3	000.9200	0056.9	010.7	64.37
175.0	000.2000	0069.7	010.3	254.5	000.9200	0056.9	010.9	64.08
176.0	000.2000	0069.8	010.3	254.7	000.9200	0057.0	011.0	63.79
177.0	000.2000	0070.0	010.3	254.8	000.9200	0057.0	011.2	63.50
178.0	000.2000	0070.2	010.3	254.9	000.9200	0057.0	011.4	63.22
179.0	000.2000	0070.4	010.3	255.1	000.9200	0057.0	011.6	62.93
180.0	000.2000	0070.7	010.4	255.2	000.9200	0057.1	011.7	62.65
181.0	000.2000	0071.0	010.4	255.3	000.9200	0057.1	011.9	62.37
182.0	000.2000	0071.0	010.4	255.6	000.9200	0057.1	012.1	62.11