

TELECOMMUNICATIONS ENGINEERING  
**GRAY FRIERSON HAERTIG & ASSOC.**  
4646 S.W. COUNCIL CREST DRIVE  
PORTLAND, OREGON 97239  
503-282-2989 (Office)  
503-807-2989 (Cell)

ELECTRONIC MAIL  
gfh@haertig.com

3 December 2021  
Prepared for Radio Bilingue  
New NCE, Williams, California

## RADIOFREQUENCY FIELDS

An engineering analysis was performed to determine whether the facilities proposed herein comply with the Maximum Permissible Exposure standards outlined in 47CFR1.1310 as regards human exposure to radiofrequency electromagnetic fields and whether environmental processing would be required.

The applicant proposes to operate at 6.1 kilowatts, circularly polarized, using a Bext TFC2K antenna mounted at the 31-meter level of an existing 59-meter tower. This antenna consists of two radiating elements spaced 0.5 wavelengths apart.

The antenna support structure is located in generally flat terrain. The base of the tower is enclosed in a locked and fenced compound the areas outside of the fence are accessible to the general public. There are no other significant radiofrequency emitters in the near vicinity.

The Commission's FMModel computer software was used to calculate the radiofrequency electromagnetic power density in a plane 2 meters AGL as a function of the distance from the antenna support structure. The "Opposed V-Dipole" elevation pattern data was selected. A copy of the graphical output of this program is attached.

The highest power density occurs at a point 54 meters from the base of the tower and is equal to  $50.9 \mu\text{W}/\text{cm}^2$ . This represents 25.5% of the general public/uncontrolled MPE standard.

Appropriate signs will be installed at the base of the tower warning workers and others that the maximum permissible exposure standard may be exceeded at locations on the tower.

The applicant believes that the facilities proposed herein conform to the MPE standards outlined in 47CFR1.1310 and that environmental processing is not warranted.

