


Dielectric®



AZIMUTH PATTERN Horizontal Polarization

Proposal No. C-06479
 Date 6-Dec-16
 Call Letters 25 DTV
 Frequency 539 MHz
 Antenna Type TFU-16WB-1-R C160
 Gain 1.58 (1.99dB)
 Calculated
 Directional Drawing # WB-C160H

Rotated with boresight at 85° True

Deg	Value																		
0	0.792	36	0.945	72	0.968	108	0.797	144	0.394	180	0.677	216	0.397	252	0.798	288	0.966	324	0.946
1	0.792	37	0.950	73	0.964	109	0.789	145	0.393	181	0.676	217	0.400	253	0.805	289	0.969	325	0.941
2	0.793	38	0.955	74	0.961	110	0.780	146	0.394	182	0.675	218	0.403	254	0.813	290	0.972	326	0.936
3	0.794	39	0.960	75	0.957	111	0.771	147	0.396	183	0.673	219	0.409	255	0.820	291	0.975	327	0.930
4	0.795	40	0.964	76	0.953	112	0.762	148	0.400	184	0.670	220	0.416	256	0.827	292	0.978	328	0.925
5	0.796	41	0.969	77	0.950	113	0.752	149	0.405	185	0.666	221	0.424	257	0.833	293	0.981	329	0.919
6	0.798	42	0.973	78	0.946	114	0.742	150	0.411	186	0.661	222	0.433	258	0.839	294	0.984	330	0.913
7	0.800	43	0.976	79	0.942	115	0.731	151	0.419	187	0.655	223	0.443	259	0.845	295	0.986	331	0.907
8	0.803	44	0.980	80	0.938	116	0.720	152	0.427	188	0.649	224	0.454	260	0.851	296	0.989	332	0.901
9	0.805	45	0.983	81	0.934	117	0.709	153	0.437	189	0.642	225	0.466	261	0.856	297	0.991	333	0.895
10	0.809	46	0.986	82	0.930	118	0.697	154	0.448	190	0.634	226	0.479	262	0.862	298	0.993	334	0.889
11	0.812	47	0.989	83	0.926	119	0.685	155	0.459	191	0.625	227	0.492	263	0.867	299	0.994	335	0.883
12	0.815	48	0.991	84	0.922	120	0.672	156	0.471	192	0.616	228	0.506	264	0.871	300	0.996	336	0.877
13	0.819	49	0.994	85	0.918	121	0.659	157	0.483	193	0.606	229	0.519	265	0.876	301	0.997	337	0.871
14	0.824	50	0.995	86	0.914	122	0.646	158	0.495	194	0.595	230	0.534	266	0.881	302	0.998	338	0.865
15	0.828	51	0.997	87	0.910	123	0.633	159	0.508	195	0.584	231	0.548	267	0.885	303	0.999	339	0.860
16	0.832	52	0.998	88	0.906	124	0.619	160	0.521	196	0.573	232	0.562	268	0.889	304	0.999	340	0.854
17	0.837	53	0.999	89	0.902	125	0.605	161	0.533	197	0.561	233	0.577	269	0.894	305	0.999	341	0.849
18	0.842	54	1.000	90	0.898	126	0.590	162	0.546	198	0.548	234	0.591	270	0.898	306	0.999	342	0.844
19	0.848	55	1.000	91	0.894	127	0.576	163	0.558	199	0.536	235	0.605	271	0.902	307	0.999	343	0.838
20	0.853	56	1.000	92	0.890	128	0.562	164	0.570	200	0.523	236	0.619	272	0.906	308	0.998	344	0.834
21	0.858	57	1.000	93	0.885	129	0.547	165	0.582	201	0.511	237	0.633	273	0.910	309	0.997	345	0.829
22	0.864	58	0.999	94	0.881	130	0.533	166	0.593	202	0.498	238	0.647	274	0.914	310	0.995	346	0.824
23	0.870	59	0.998	95	0.876	131	0.519	167	0.604	203	0.486	239	0.660	275	0.917	311	0.994	347	0.820
24	0.876	60	0.997	96	0.871	132	0.505	168	0.614	204	0.474	240	0.673	276	0.921	312	0.992	348	0.816
25	0.881	61	0.996	97	0.866	133	0.491	169	0.624	205	0.462	241	0.685	277	0.925	313	0.989	349	0.813
26	0.887	62	0.994	98	0.861	134	0.478	170	0.632	206	0.451	242	0.698	278	0.929	314	0.987	350	0.809
27	0.893	63	0.992	99	0.856	135	0.465	171	0.640	207	0.441	243	0.709	279	0.933	315	0.984	351	0.806
28	0.899	64	0.990	100	0.851	136	0.453	172	0.648	208	0.431	244	0.721	280	0.937	316	0.981	352	0.803
29	0.905	65	0.988	101	0.845	137	0.441	173	0.654	209	0.422	245	0.732	281	0.940	317	0.977	353	0.801
30	0.911	66	0.986	102	0.839	138	0.431	174	0.660	210	0.414	246	0.743	282	0.944	318	0.974	354	0.799
31	0.917	67	0.983	103	0.833	139	0.422	175	0.665	211	0.408	247	0.753	283	0.948	319	0.970	355	0.797
32	0.923	68	0.980	104	0.826	140	0.413	176	0.669	212	0.403	248	0.763	284	0.952	320	0.966	356	0.795
33	0.929	69	0.977	105	0.819	141	0.406	177	0.672	213	0.399	249	0.772	285	0.955	321	0.961	357	0.794
34	0.934	70	0.974	106	0.812	142	0.401	178	0.675	214	0.397	250	0.781	286	0.959	322	0.956	358	0.793
35	0.940	71	0.971	107	0.805	143	0.397	179	0.676	215	0.396	251	0.789	287	0.962	323	0.951	359	0.793

This document contains proprietary and confidential information of Dielectric. It is to be used solely for the purpose for which it is provided. No disclosure, reproduction, or use of this document or any part of it may be made without the written permission of Dielectric.

Trusted for Decades. Ready for Tomorrow.



ELEVATION PATTERN

Proposal No. **C-06479**
 Date **6-Dec-16**
 Call Letters **25 DTV**
 Frequency **539 MHz**
 Antenna Type **TFU-16WB-1-R C160**

RMS Directivity at Main Lobe
 RMS Directivity at Horizontal

14.42 (11.59 dB)
13.20 (11.21 dB)
Calculated

Beam Tilt **0.55 deg**
 Drawing Number **16W144055**



Angle	Field								
-10.0	0.036	10.0	0.219	30.0	0.037	50.0	0.032	70.0	0.038
-9.0	0.189	11.0	0.056	31.0	0.007	51.0	0.029	71.0	0.036
-8.0	0.303	12.0	0.079	32.0	0.002	52.0	0.033	72.0	0.034
-7.0	0.321	13.0	0.129	33.0	0.014	53.0	0.044	73.0	0.032
-6.0	0.321	14.0	0.096	34.0	0.043	54.0	0.059	74.0	0.029
-5.0	0.369	15.0	0.039	35.0	0.071	55.0	0.070	75.0	0.025
-4.0	0.352	16.0	0.033	36.0	0.084	56.0	0.074	76.0	0.021
-3.0	0.188	17.0	0.036	37.0	0.082	57.0	0.068	77.0	0.017
-2.0	0.305	18.0	0.090	38.0	0.074	58.0	0.053	78.0	0.014
-1.0	0.690	19.0	0.158	39.0	0.067	59.0	0.032	79.0	0.010
0.0	0.956	20.0	0.186	40.0	0.057	60.0	0.011	80.0	0.008
1.0	0.975	21.0	0.157	41.0	0.035	61.0	0.018	81.0	0.005
2.0	0.754	22.0	0.086	42.0	0.012	62.0	0.036	82.0	0.004
3.0	0.425	23.0	0.010	43.0	0.048	63.0	0.049	83.0	0.003
4.0	0.208	24.0	0.042	44.0	0.083	64.0	0.055	84.0	0.002
5.0	0.201	25.0	0.064	45.0	0.104	65.0	0.057	85.0	0.001
6.0	0.180	26.0	0.079	46.0	0.106	66.0	0.054	86.0	0.001
7.0	0.217	27.0	0.094	47.0	0.090	67.0	0.050	87.0	0.000
8.0	0.313	28.0	0.095	48.0	0.067	68.0	0.045	88.0	0.000
9.0	0.325	29.0	0.072	49.0	0.045	69.0	0.041	89.0	0.000
									90.0 0.000

This document contains proprietary and confidential information of Dielectric. It is to be used solely for the purpose for which it is provided.
 No disclosure, reproduction, or use of this document or any part of it may be made without the written permission of Dielectric.