



RADIO FREQUENCY IMPACT, SAFETY & STATEMENT OF COMPLIANCE

The licensee of WLOS is committed to the protection of station personnel and/or tower contractors working in the vicinity of the WLOS antenna and will reduce power or cease operation, when necessary, to ensure protection to personnel.

The proposed WLOS channel 13 facility, as proposed herein, will operate with a maximum ERP of 144 kW from an elliptically polarized directional transmitting antenna with a centerline height of 211.8 meters above ground level (AGL). Considering the antenna's elevation pattern provided elsewhere in this submission, the vertical plane relative field factor is less than 0.175 at all depression angles greater than 10 degrees. The proposed WLOS channel 13 facility is predicted to produce a worst-case power density at two meters above ground level, at 146.9 meters from the tower base, of $2.999 \mu\text{W}/\text{cm}^2$, which is 1.50% of the FCC guideline value of $200.0 \mu\text{W}/\text{cm}^2$ for an "uncontrolled" environment, and 0.30% of the FCC's guideline value for "controlled" environments. Therefore, pursuant to Section 1.1307(b)(3) of the FCC Rules, because the proposed facility would not exceed 5% of the uncontrolled and controlled exposure limits, the proposal's power density contribution is considered insignificant. Further, the Applicant will continue to cooperate/coordinate with other site users and reduce power and/or cease operation during times of service or maintenance of the transmission systems as necessary to avoid potentially harmful exposure to personnel. In light of the above, the proposed facility should be categorically excluded from RF environmental processing under Section 1.1307(b) of the Commission's Rules.

WLOS

Channel 13 - Asheville, North Carolina

ERP = 144000.00 WATTS

APPENDIX A

Maximum ERP 144 kW

Polarization ----- 2 Circular meters 694.9 feet
 Antenna Height Above Ground -- 211.8
 FCC Uncontrolled RFR Limit ---- 200 $\mu\text{W}/\text{cm}^2$

Maximum Computed Power Density **2.999** $\mu\text{W}/\text{cm}^2$
 1.50% of limit

Angle Below Horizontal (degrees)	<Point X> Horiz Distance from tower to 2 m AGL (meters)	Slant Distance from antenna to Point X (meters)	Vertical Pattern (REL. FIELD)	WLOS ERP (kW)	WLOS Calculated Power Density $\mu\text{W}/\text{cm}^2$	Percent Limit	Limit Exceeded?
0			0.947	129.1405			
5	2398.0	2407.2	0.743	79.4951	0.916	0.46%	No
10	1189.8	1208.2	0.131	2.4712	0.113	0.06%	No
15	783.0	810.6	0.131	2.4712	0.251	0.13%	No
20	576.4	613.4	0.131	2.4712	0.439	0.22%	No
25	449.9	496.4	0.082	0.9683	0.262	0.13%	No
30	363.4	419.6	0.117	1.9712	0.748	0.37%	No
35	299.6	365.8	0.074	0.7885	0.394	0.20%	No
40	250.0	326.4	0.066	0.6273	0.393	0.20%	No
45	209.8	296.7	0.037	0.1971	0.150	0.07%	No
50	176.0	273.9	0.118	2.0051	1.786	0.89%	No
55	146.9	256.1	0.143	2.9447	2.999	1.50%	No
60	121.1	242.3	0.059	0.5013	0.571	0.29%	No
65	97.8	231.5	0.045	0.2916	0.364	0.18%	No
70	76.4	223.3	0.099	1.4113	1.891	0.95%	No
75	56.2	217.2	0.097	1.3549	1.918	0.96%	No
80	37.0	213.0	0.063	0.5715	0.841	0.42%	No
85	18.4	210.6	0.024	0.0829	0.125	0.06%	No
90	0.0	209.8	0.000	0.0000	0.000	0.00%	No

