

DELAWDER COMMUNICATIONS, INC.

P.O. Box 1095
Ashburn, Virginia 20146-1095
(703) 299-9222

ENGINEERING REPORT

WTMQ-LD, Jacksonville, NC Displacement Amendment to Channel 32

DISPACEMENT QUALIFICATION

This licensed LPTV station qualifies for channel displacement due to its currently-licensed channel being above TV channel 36.

INTERFERENCE PROTECTION RESULTS ON NEW CHANNEL

The output from the FCC's current "TVStudy" software is attached demonstrating full compliance with the FCC's protection requirements.

Consent Agreements required for grant of this application: None

Note: By separate attachment to this application, a waiver of Section 73.3517 – The Contingent Application Rule—is being requested regarding the predicted interference to the licensed WITN-TV, Washington, NC 32 Digital facility. WITN-TV is being re-packed to channel 34.

The applicant accepts any interference that is predicted to exist to the proposed facility by any licensed, authorized or previously proposed primary TV station. The applicant also accepts any interference that is predicted to exist to the proposed facility by any secondary TV facility that is given preferential status by the FCC over the Applicant's herein proposed facility. Additionally, as deemed necessary, the applicant may agree to consent to interference (either by a separate statement submitted with this initial application or by an amendment to this application) from another LPTV displacement application that has been submitted in the same filing window.

ENVIRONMENTAL STATEMENT

This proposal does not involve a site location specified under Section 1.1307(a) through (a)(8) of the FCC Rules.

The digital LPTV stations of the Applicant at this location produces an ERP that is less than or equal to 15 kilowatts. Assuming: (a) a maximum ERP of 15 kilowatts; (b) a relative field of less than 0.2 in the critical downward angles; and (c) a distance of at least 100 meters from the lowest antenna element to 2 meters above ground level, the maximum power density is calculated as follows:

$$S = 33.4 (F)(F)(ERP) / [(R)(R)]$$

Where, S equals power density in uW/cm²
 F equals the relative field factor
 ERP equals the effective radiate power in watts
 R equals the distance in meters

$$= 33.4 (0.2)(0.2)(15,000) / [(100)(100)]$$

$$= 2.0 \text{ uW/cm}^2$$

2.0 uW/cm² represents less than 5% of the uncontrolled power density limit (315.3 uW/cm² for UHF; 200 uW/cm² for VHF). The electromagnetic radiation from this proposed operation will not produce a value in excess of the radiation standard. The electromagnetic radiation from the proposed operation will not combine with other facilities on or near the structure to produce a significant change in value.

If this is a structure that may support various other operations, the applicant will cooperate with the other operators in establishing a plan for work done on the structure in close proximity to the existing antenna.