

DELAWDER COMMUNICATIONS, INC.

P.O. Box 1095
Ashburn, Virginia 20146-1095
(703) 299-9222

ENGINEERING REPORT

K22JW-D, to Lake Jackson, TX LPTV (Proposing Channel 27)

ENGINEERING STATEMENT

DISPLACEMENT QUALIFICATION

This licensed LPTV station qualifies for channel displacement due to interference that is predicted to be caused to KTMD, Galveston, TX 22D (LMS File Number 26839 CP). The FCC's current "TVStudy" software predicts greater than 10 percent of increased interference to the facility of 26839.

INTERFERENCE PROTECTION RESULTS ON NEW CHANNEL

The output from the FCC's current "TVStudy" software is attached demonstrating full compliance with the FCC's protection requirements.

Consent Agreements required for grant of this application: NONE

The applicant accepts any interference that is predicted to exist to the proposed facility by any licensed, authorized or previously proposed primary TV station. The applicant also accepts any interference that is predicted to exist to the proposed facility by any secondary TV facility that is given preferential status by the FCC over the Applicant's herein proposed facility. Additionally, as deemed necessary, the applicant may agree to consent to interference (either by a separate statement submitted with this initial application or by an amendment to this application) from another LPTV displacement application that has been submitted in the same filing window.

ENVIRONMENTAL STATEMENT

This proposal does not involve a site location specified under Section 1.1307(a) through (a)(8) of the FCC Rules.

The proposed LPTV produces an ERP that is equal to or less than 15 kilowatts. Assuming: (a) a maximum ERP of 12 kilowatts; (b) a relative field of less than 0.3 in the critical downward angles; and (c) a distance of at least 80 meters from the lowest antenna element to 2 meters above ground level, the maximum power density is calculated as follows:

$$S = 33.4 (F)(F)(ERP) / [(R)(R)]$$

Where, S equals power density in uW/cm²
F equals the relative field factor
ERP equals the effective radiate power in watts
R equals the distance in meters

$$= 33.4 (0.3)(0.3)(15,000) / [(80)(80)]$$

$$= 7.04 \text{ uW/cm}^2$$

7.04 uW/cm² represents less than 5% of the uncontrolled power density limit (315.3 uW/cm² for channel 14—channel 14 being the worst-case UHF channel or 200 uW/cm² for VHF). The electromagnetic radiation from this proposed operation will not produce a value in excess of the radiation standard. The electromagnetic radiation from the proposed operation will not combine with other facilities on or near the structure to produce a significant change in value.

If this is a structure that may support various other operations, the applicant will cooperate with the other operators in establishing a plan for work done on the structure in close proximity to the existing antenna.