

ERI #35662E

**TRASAR® Top Mounted
UHF Elliptically Polarized
Television Antenna Manual**

**KTKA-TV, RF Channel 16
Nexstar Broadcasting, Inc., Topeka, KS**

August 18, 2020

REVISION "A" 18AUG20
REVISER ERP TO 150 KW

**Antenna Model:
ATW17H3-ETP230-16L**

**This manual supersedes
Specification Number
20181228-237r1**

Electronics Research, Inc. 7777 Gardner Road Chandler IN 47610-9219 USA
+1 812 925-6000 (tel) +1 812 925-4030 (fax)

Your Single Source for Broadcast Solutions™ Call Toll-free at 877 ERI-LINE Visit Online at www.eriinc.com

ERI #35662E
TRASAR® Top Mounted
UHF Elliptically Polarized
Television Antenna Manual

Electrical Characteristics:

Channel:		16	
Frequency:		482 MHz to 488 MHz	
Service:		ATSC	
Azimuth Pattern Number:	Horizontal Polarization Vertical Polarization	ATW-P230 ATW-P230-V	
Elevation Pattern Number:	Horizontal Polarization Vertical Polarization	ATW17H3H ATW14H3H	
Azimuth Directivity:	Horizontal Polarization Vertical Polarization	2.30 1.41	(3.62 dB) (1.49 dB)
Elevation Directivity:	Horizontal Polarization Vertical Polarization	17.00 14.00	(12.30 dBd) (11.46 dBd)
Peak Power Gain:	Horizontal Polarization Vertical Polarization	30.80 4.19	(14.89 dBd) (6.22 dBd)
Gain at Horizontal:	Horizontal Polarization Vertical Polarization	25.62 3.78	(14.09 dBd) (5.78 dBd)
ERP Vertical/Horizontal Ratio:		0.136	
Power Ratio:		0.269	
Electrical Beam Tilt:		0.75 Degrees	
Input Power Required:		4.87 kW	(6.88 dBk)
RF Input:		6-1/8-inch EIA, 75 Ω , flanged male	
Input Power Rating (maximum):		20 kW Average Power, 8VSB	
Antenna VSWR (maximum):		1.10 Over 6 MHz Channel	

ERI #35662E
TRASAR® Top Mounted
UHF Elliptically Polarized
Television Antenna Manual

Antenna Mechanical Characteristics:

Mounting Configuration:	Top Mounted		
Height of Antenna:	38.53 feet	(11.7 meters)	
Height of Center of Radiation:	19.27 feet	(5.9 meters)	
Overall Height (Includes four 3.5 ft lightning spurs):	42.03 feet	(12.8 meters)	
Deicing:	Fully enclosed pressurized radome		
Radome Diameter:	18.40 inches	(467.4 millimeters)	
Radome Color:	Aviation Orange		
Climbing Device:	Fiberglass Ladder		
Measured Weight:	No Ice	3930.0 lb	1782.6 kg
Effective Projected Area (EPA-ft ²):	No Ice	62.38 ft ²	(5.8 m ²)
	1/2" (13 mm) ice	115.53 ft ²	(10.7 m ²)
Effective Moment Arm:	No Ice	20.81 feet	(6.34 meters)
	1/2" (13 mm) ice	20.57 feet	(6.27 meters)

MOUNTING FLANGE BOLT CIRCLE: Quantity (16), 1.38 inch holes for 1.25 inch bolts, equally spaced on a 21.50 inch bolt circle.

This antenna is designed to be supported by a structure that can resist the antenna base reactions and which provides a support that is rigid in the three translational and three rotational degrees of freedom.

Antenna design based on a wind speed of 90 miles per hour (MPH) with no ice and 40 MPH with 0.75-inches of design radial ice (2.1-inches of factored ice at antenna, tiz) with a height above ground level (HAGL) of 1381 feet per ANSI/TIA-222-G. Structure Class II, Exposure Category C and Topographic Category I. Weight and wind area values include four lightning spurs and a standard beacon.

NOTE: The purchaser or their representative shall be required to contact the tower owner, state and/or local building officials for specific design requirements and suitable parameters for a particular structure. Any variation from the parameters shown above must be communicated to ERI for comprehensive assessment.

Broadcast Antenna System Power Analysis

KTKA-TV **RF Channel: 16**
Nexstar Broadcasting, Inc.
Topeka, KS
ATW17H3-ETP230-16L

Antenna Parameters

Azimuth Directivity:

Horizontal:	2.30	(3.62 dB)
Vertical:	1.41	(1.49 dB)

Elevation Directivity:

Horizontal:	17.00	(12.30 dB)
Vertical:	14.00	(11.46 dB)

Transmission Line

Vertical Run:

Type:	6-1/8-inch EIA, 75 Ω
Length:	1,380 feet 420.6 meters
Attenuation:	0.100 dB/100 feet 0.328 dB/100 mtrs

Horizontal Run:

Type:	6-1/8-inch EIA, 75 Ω
Length:	138 feet 42.1 meters
Attenuation:	0.100 dB/100 feet 0.328 dB/100 mtrs

Transmission Line Efficiency: 70.50%

RF System/Other Efficiency: 100.00%

Effective Radiated Power:

Horizontal:	150.00 kW	(21.76 dBk)
Vertical:	20.40 kW	(13.10 dBk)

Peak Power Gain:

Horizontal:	30.80 numeric	(14.89 dBd)
Vertical:	4.19 numeric	(6.22 dBd)

Antenna Input Power:

4.87 kW	(6.88 dBk)
---------	------------

Transmission Line Losses:

-2.04 kW	(1.518 dB)
----------	------------

RF System/Other Losses:

0.00 kW	(0.000 dB)
---------	------------

Total Losses:

-2.04 kW	(1.518 dB)
----------	------------

Transmitter Power Output:

6.91 kW
(8.39 dBk)

CH.16 TOPEKA, KS

#35662E

FINAL ANTENNA DATA INCLUDED

LD35662E-1

Truck Removal / Lifting Instructions

PM35662E-1

Mechanical Parameter / Installation Drawings

Measured VSWR

Frequency (MHz)

1.02

482.00

1.03

483.00

1.02

484.00

1.02

485.00

1.01

486.00

1.01

487.00


1.03

488.00

Composite Azimuth Patterns

Type:	ATW-P230		Polarization:	Elliptical
Directivity (H-Pol):	2.30 numeric	(3.62 dB)	Frequency:	16 (ATSC)
Directivity (V-Pol):	1.41 numeric	(1.49 dB)	Location:	Topeka, KS
Percent Horizontal:	78.77%		NOTE: Pattern shape and directivity may vary with channel and mounting	
Percent Vertical:	21.23%			
Power Ratio:	26.95%			
ERP V/H Ratio::	13.60%			


— Horizontal Relative Field — Vertical Relative Field (scaled)



Azimuth Pattern

Type:	ATW-P230	Polarization:	Horizontal
Directivity:	2.30 numeric (3.62 dB)	Frequency:	16 (ATSC)
Peak(s) at:		Location:	Topeka, KS
		NOTE: Pattern shape and directivity may vary with channel and mounting configuration.	

Relative Field




Tabulated Data for Azimuth Pattern

Type: ATW-P230

Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB
0	0.370	-8.64	100	0.970	-0.26	200	0.370	-8.64	300	0.760	-2.38
2	0.370	-8.64	102	0.950	-0.45	202	0.380	-8.40	302	0.730	-2.73
4	0.370	-8.64	104	0.940	-0.54	204	0.380	-8.40	304	0.700	-3.10
6	0.370	-8.64	106	0.920	-0.72	206	0.390	-8.18	306	0.680	-3.35
8	0.370	-8.64	108	0.900	-0.92	208	0.400	-7.96	308	0.650	-3.74
10	0.370	-8.64	110	0.880	-1.11	210	0.400	-7.96	310	0.620	-4.15
12	0.370	-8.64	112	0.860	-1.31	212	0.420	-7.54	312	0.590	-4.58
14	0.370	-8.64	114	0.830	-1.62	214	0.440	-7.13	314	0.570	-4.88
16	0.370	-8.64	116	0.810	-1.83	216	0.460	-6.74	316	0.540	-5.35
18	0.370	-8.64	118	0.780	-2.16	218	0.470	-6.56	318	0.520	-5.68
20	0.370	-8.64	120	0.760	-2.38	220	0.490	-6.20	320	0.490	-6.20
22	0.380	-8.40	122	0.730	-2.73	222	0.520	-5.68	322	0.470	-6.56
24	0.380	-8.40	124	0.700	-3.10	224	0.540	-5.35	324	0.460	-6.74
26	0.390	-8.18	126	0.680	-3.35	226	0.570	-4.88	326	0.440	-7.13
28	0.400	-7.96	128	0.650	-3.74	228	0.590	-4.58	328	0.420	-7.54
30	0.400	-7.96	130	0.620	-4.15	230	0.620	-4.15	330	0.400	-7.96
32	0.420	-7.54	132	0.590	-4.58	232	0.650	-3.74	332	0.400	-7.96
34	0.440	-7.13	134	0.570	-4.88	234	0.680	-3.35	334	0.390	-8.18
36	0.460	-6.74	136	0.540	-5.35	236	0.700	-3.10	336	0.380	-8.40
38	0.470	-6.56	138	0.520	-5.68	238	0.730	-2.73	338	0.380	-8.40
40	0.490	-6.20	140	0.490	-6.20	240	0.760	-2.38	340	0.370	-8.64
42	0.520	-5.68	142	0.470	-6.56	242	0.780	-2.16	342	0.370	-8.64
44	0.540	-5.35	144	0.460	-6.74	244	0.810	-1.83	344	0.370	-8.64
46	0.570	-4.88	146	0.440	-7.13	246	0.830	-1.62	346	0.370	-8.64
48	0.590	-4.58	148	0.420	-7.54	248	0.860	-1.31	348	0.370	-8.64
50	0.620	-4.15	150	0.400	-7.96	250	0.880	-1.11	350	0.370	-8.64
52	0.650	-3.74	152	0.400	-7.96	252	0.900	-0.92	352	0.370	-8.64
54	0.680	-3.35	154	0.390	-8.18	254	0.920	-0.72	354	0.370	-8.64
56	0.700	-3.10	156	0.380	-8.40	256	0.940	-0.54	356	0.370	-8.64
58	0.730	-2.73	158	0.380	-8.40	258	0.950	-0.45	358	0.370	-8.64
60	0.760	-2.38	160	0.370	-8.64	260	0.970	-0.26	360	1.000	0.00
62	0.780	-2.16	162	0.370	-8.64	262	0.980	-0.18			
64	0.810	-1.83	164	0.370	-8.64	264	0.980	-0.18			
66	0.830	-1.62	166	0.370	-8.64	266	0.990	-0.09			
68	0.860	-1.31	168	0.370	-8.64	268	0.990	-0.09			
70	0.880	-1.11	170	0.370	-8.64	270	1.000	0.00			
72	0.900	-0.92	172	0.370	-8.64	272	0.990	-0.09			
74	0.920	-0.72	174	0.370	-8.64	274	0.990	-0.09			
76	0.940	-0.54	176	0.370	-8.64	276	0.980	-0.18			
78	0.950	-0.45	178	0.370	-8.64	278	0.980	-0.18			
80	0.970	-0.26	180	0.370	-8.64	280	0.970	-0.26			
82	0.980	-0.18	182	0.370	-8.64	282	0.950	-0.45			
84	0.980	-0.18	184	0.370	-8.64	284	0.940	-0.54			
86	0.990	-0.09	186	0.370	-8.64	286	0.920	-0.72			
88	0.990	-0.09	188	0.370	-8.64	288	0.900	-0.92			
90	1.000	0.00	190	0.370	-8.64	290	0.880	-1.11			
92	0.990	-0.09	192	0.370	-8.64	292	0.860	-1.31			
94	0.990	-0.09	194	0.370	-8.64	294	0.830	-1.62			
96	0.980	-0.18	196	0.370	-8.64	296	0.810	-1.83			
98	0.980	-0.18	198	0.370	-8.64	298	0.780	-2.16			

Elevation Pattern

Type:	ATW17H3H		Polarization:	Horizontal
Directivity:			Frequency:	16 (ATSC)
Main Lobe:	17.00 numeric	(12.30 dB)	Location:	Topeka, KS
Horizontal:	14.14 numeric	(11.50 dB)	Beam Tilt:	0.75 degrees



Tabulated Data for Elevation PatternType: ATW17H3H

-10 to 10 degrees in 0.25 degree increments.


10 to 90 degrees in 0.50 degree increments.

Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB
-10.00	0.081	-21.83	2.25	0.710	-2.97	19.00	0.056	-25.04	43.50	0.003	-50.46	68.00	0.051	-25.85
-9.75	0.070	-23.10	2.50	0.625	-4.08	19.50	0.043	-27.33	44.00	0.021	-33.56	68.50	0.059	-24.58
-9.50	0.056	-25.04	2.75	0.540	-5.35	20.00	0.025	-32.04	44.50	0.038	-28.40	69.00	0.067	-23.48
-9.25	0.042	-27.54	3.00	0.462	-6.71	20.50	0.026	-31.70	45.00	0.053	-25.51	69.50	0.072	-22.85
-9.00	0.036	-28.87	3.25	0.396	-8.05	21.00	0.048	-26.38	45.50	0.062	-24.15	70.00	0.076	-22.38
-8.75	0.046	-26.74	3.50	0.348	-9.17	21.50	0.067	-23.48	46.00	0.066	-23.61	70.50	0.079	-22.05
-8.50	0.065	-23.74	3.75	0.323	-9.82	22.00	0.074	-22.62	46.50	0.064	-23.88	71.00	0.080	-21.94
-8.25	0.086	-21.31	4.00	0.316	-10.01	22.50	0.069	-23.22	47.00	0.057	-24.88	71.50	0.079	-22.05
-8.00	0.106	-19.49	4.25	0.322	-9.84	23.00	0.052	-25.68	47.50	0.046	-26.74	72.00	0.077	-22.27
-7.75	0.121	-18.34	4.50	0.330	-9.63	23.50	0.027	-31.37	48.00	0.033	-29.63	72.50	0.074	-22.62
-7.50	0.131	-17.65	4.75	0.336	-9.47	24.00	0.018	-34.89	48.50	0.023	-32.77	73.00	0.070	-23.10
-7.25	0.133	-17.52	5.00	0.335	-9.50	24.50	0.042	-27.54	49.00	0.023	-32.77	73.50	0.065	-23.74
-7.00	0.128	-17.86	5.25	0.324	-9.79	25.00	0.063	-24.01	49.50	0.032	-29.90	74.00	0.059	-24.58
-6.75	0.116	-18.71	5.50	0.304	-10.34	25.50	0.075	-22.50	50.00	0.041	-27.74	74.50	0.053	-25.51
-6.50	0.096	-20.35	5.75	0.276	-11.18	26.00	0.075	-22.50	50.50	0.048	-26.38	75.00	0.046	-26.74
-6.25	0.073	-22.73	6.00	0.241	-12.36	26.50	0.064	-23.88	51.00	0.050	-26.02	75.50	0.040	-27.96
-6.00	0.055	-25.19	6.25	0.203	-13.85	27.00	0.045	-26.94	51.50	0.048	-26.38	76.00	0.034	-29.37
-5.75	0.060	-24.44	6.50	0.165	-15.65	27.50	0.024	-32.40	52.00	0.042	-27.54	76.50	0.028	-31.06
-5.50	0.091	-20.82	6.75	0.133	-17.52	28.00	0.022	-33.15	52.50	0.032	-29.90	77.00	0.024	-32.40
-5.25	0.132	-17.59	7.00	0.113	-18.94	28.50	0.037	-28.64	53.00	0.021	-33.56	77.50	0.021	-33.56
-5.00	0.175	-15.14	7.25	0.111	-19.09	29.00	0.049	-26.20	53.50	0.012	-38.42	78.00	0.020	-33.98
-4.75	0.215	-13.35	7.50	0.123	-18.20	29.50	0.052	-25.68	54.00	0.016	-35.92	78.50	0.021	-33.56
-4.50	0.249	-12.08	7.75	0.139	-17.14	30.00	0.044	-27.13	54.50	0.028	-31.06	79.00	0.023	-32.77
-4.25	0.275	-11.21	8.00	0.154	-16.25	30.50	0.028	-31.06	55.00	0.039	-28.18	79.50	0.025	-32.04
-4.00	0.290	-10.75	8.25	0.163	-15.76	31.00	0.009	-40.92	55.50	0.048	-26.38	80.00	0.028	-31.06
-3.75	0.292	-10.69	8.50	0.165	-15.65	31.50	0.024	-32.40	56.00	0.054	-25.35	80.50	0.030	-30.46
-3.50	0.279	-11.09	8.75	0.160	-15.92	32.00	0.048	-26.38	56.50	0.056	-25.04	81.00	0.032	-29.90
-3.25	0.252	-11.97	9.00	0.147	-16.65	32.50	0.066	-23.61	57.00	0.056	-25.04	81.50	0.034	-29.37
-3.00	0.208	-13.64	9.25	0.128	-17.86	33.00	0.076	-22.38	57.50	0.052	-25.68	82.00	0.035	-29.12
-2.75	0.150	-16.48	9.50	0.105	-19.58	33.50	0.077	-22.27	58.00	0.045	-26.94	82.50	0.035	-29.12
-2.50	0.080	-21.94	9.75	0.082	-21.72	34.00	0.068	-23.35	58.50	0.037	-28.64	83.00	0.035	-29.12
-2.25	0.038	-28.40	10.00	0.064	-23.88	34.50	0.052	-25.68	59.00	0.028	-31.06	83.50	0.035	-29.12
-2.00	0.118	-18.56	10.50	0.075	-22.50	35.00	0.030	-30.46	59.50	0.021	-33.56	84.00	0.034	-29.37
-1.75	0.222	-13.07	11.00	0.118	-18.56	35.50	0.009	-40.92	60.00	0.019	-34.42	84.50	0.032	-29.90
-1.50	0.332	-9.58	11.50	0.150	-16.48	36.00	0.018	-34.89	60.50	0.023	-32.77	85.00	0.031	-30.17
-1.25	0.443	-7.07	12.00	0.159	-15.97	36.50	0.035	-29.12	61.00	0.029	-30.75	85.50	0.029	-30.75
-1.00	0.553	-5.15	12.50	0.145	-16.77	37.00	0.046	-26.74	61.50	0.034	-29.37	86.00	0.026	-31.70
-0.75	0.658	-3.64	13.00	0.115	-18.79	37.50	0.049	-26.20	62.00	0.038	-28.40	86.50	0.024	-32.40
-0.50	0.753	-2.46	13.50	0.085	-21.41	38.00	0.045	-26.94	62.50	0.039	-28.18	87.00	0.021	-33.56
-0.25	0.837	-1.55	14.00	0.078	-22.16	38.50	0.033	-29.63	63.00	0.039	-28.18	87.50	0.018	-34.89
0.00	0.905	-0.87	14.50	0.094	-20.54	39.00	0.018	-34.89	63.50	0.036	-28.87	88.00	0.014	-37.08
0.25	0.956	-0.39	15.00	0.110	-19.17	39.50	0.005	-46.02	64.00	0.030	-30.46	88.50	0.011	-39.17
0.50	0.988	-0.10	15.50	0.111	-19.09	40.00	0.019	-34.42	64.50	0.023	-32.77	89.00	0.007	-43.10
0.75	1.000	0.00	16.00	0.096	-20.35	40.50	0.033	-29.63	65.00	0.015	-36.48	89.50	0.004	-47.96
1.00	0.993	-0.06	16.50	0.068	-23.35	41.00	0.042	-27.54	65.50	0.008	-41.94	90.00	0.000	---
1.25	0.966	-0.30	17.00	0.034	-29.37	41.50	0.044	-27.13	66.00	0.011	-39.17			
1.50	0.922	-0.71	17.50	0.020	-33.98	42.00	0.040	-27.96	66.50	0.021	-33.56			
1.75	0.863	-1.28	18.00	0.041	-27.74	42.50	0.030	-30.46	67.00	0.031	-30.17			
2.00	0.791	-2.04	18.50	0.056	-25.04	43.00	0.016	-35.92	67.50	0.041	-27.74			

Azimuth Pattern

Type:	ATW-P230-V		Polarization:	Vertical
Directivity:	1.41 numeric	(1.49 dB)	Frequency:	16 (ATSC)
Peak(s) at:			Location:	Topeka, KS
			NOTE: Pattern shape and directivity may vary with channel and mounting configuration.	

Relative Field



Tabulated Data for Azimuth Pattern


Type:

ATW-P230-V

Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB
0	1.000	0.00	100	0.875	-1.16	200	0.913	-0.79	300	0.735	-2.67
2	0.999	-0.01	102	0.864	-1.27	202	0.896	-0.95	302	0.724	-2.81
4	0.996	-0.03	104	0.852	-1.39	204	0.879	-1.12	304	0.715	-2.91
6	0.992	-0.07	106	0.838	-1.54	206	0.861	-1.30	306	0.709	-2.99
8	0.985	-0.13	108	0.823	-1.69	208	0.843	-1.48	308	0.705	-3.04
10	0.977	-0.20	110	0.807	-1.86	210	0.824	-1.68	310	0.704	-3.05
12	0.967	-0.29	112	0.792	-2.03	212	0.806	-1.87	312	0.706	-3.02
14	0.956	-0.39	114	0.776	-2.20	214	0.788	-2.07	314	0.711	-2.96
16	0.943	-0.51	116	0.761	-2.37	216	0.771	-2.26	316	0.719	-2.87
18	0.929	-0.64	118	0.747	-2.53	218	0.755	-2.44	318	0.729	-2.75
20	0.913	-0.79	120	0.735	-2.67	220	0.741	-2.60	320	0.741	-2.60
22	0.896	-0.95	122	0.724	-2.81	222	0.729	-2.75	322	0.755	-2.44
24	0.879	-1.12	124	0.715	-2.91	224	0.719	-2.87	324	0.771	-2.26
26	0.861	-1.30	126	0.709	-2.99	226	0.711	-2.96	326	0.788	-2.07
28	0.843	-1.48	128	0.705	-3.04	228	0.706	-3.02	328	0.806	-1.87
30	0.824	-1.68	130	0.704	-3.05	230	0.704	-3.05	330	0.824	-1.68
32	0.806	-1.87	132	0.706	-3.02	232	0.705	-3.04	332	0.843	-1.48
34	0.788	-2.07	134	0.711	-2.96	234	0.709	-2.99	334	0.861	-1.30
36	0.771	-2.26	136	0.719	-2.87	236	0.715	-2.91	336	0.879	-1.12
38	0.755	-2.44	138	0.729	-2.75	238	0.724	-2.81	338	0.896	-0.95
40	0.741	-2.60	140	0.741	-2.60	240	0.735	-2.67	340	0.913	-0.79
42	0.729	-2.75	142	0.755	-2.44	242	0.747	-2.53	342	0.929	-0.64
44	0.719	-2.87	144	0.771	-2.26	244	0.761	-2.37	344	0.943	-0.51
46	0.711	-2.96	146	0.788	-2.07	246	0.776	-2.20	346	0.956	-0.39
48	0.706	-3.02	148	0.806	-1.87	248	0.792	-2.03	348	0.967	-0.29
50	0.704	-3.05	150	0.824	-1.68	250	0.807	-1.86	350	0.977	-0.20
52	0.705	-3.04	152	0.843	-1.48	252	0.823	-1.69	352	0.985	-0.13
54	0.709	-2.99	154	0.861	-1.30	254	0.838	-1.54	354	0.992	-0.07
56	0.715	-2.91	156	0.879	-1.12	256	0.852	-1.39	356	0.996	-0.03
58	0.724	-2.81	158	0.896	-0.95	258	0.864	-1.27	358	0.999	-0.01
60	0.735	-2.67	160	0.913	-0.79	260	0.875	-1.16	360	1.000	0.00
62	0.747	-2.53	162	0.929	-0.64	262	0.885	-1.06			
64	0.761	-2.37	164	0.943	-0.51	264	0.892	-0.99			
66	0.776	-2.20	166	0.956	-0.39	266	0.898	-0.93			
68	0.792	-2.03	168	0.967	-0.29	268	0.901	-0.91			
70	0.807	-1.86	170	0.977	-0.20	270	0.902	-0.90			
72	0.823	-1.69	172	0.985	-0.13	272	0.901	-0.91			
74	0.838	-1.54	174	0.992	-0.07	274	0.898	-0.93			
76	0.852	-1.39	176	0.996	-0.03	276	0.892	-0.99			
78	0.864	-1.27	178	0.999	-0.01	278	0.885	-1.06			
80	0.875	-1.16	180	1.000	0.00	280	0.875	-1.16			
82	0.885	-1.06	182	0.999	-0.01	282	0.864	-1.27			
84	0.892	-0.99	184	0.996	-0.03	284	0.852	-1.39			
86	0.898	-0.93	186	0.992	-0.07	286	0.838	-1.54			
88	0.901	-0.91	188	0.985	-0.13	288	0.823	-1.69			
90	0.902	-0.90	190	0.977	-0.20	290	0.807	-1.86			
92	0.901	-0.91	192	0.967	-0.29	292	0.792	-2.03			
94	0.898	-0.93	194	0.956	-0.39	294	0.776	-2.20			
96	0.892	-0.99	196	0.943	-0.51	296	0.761	-2.37			
98	0.885	-1.06	198	0.929	-0.64	298	0.747	-2.53			

Elevation Pattern

Type:	ATW14H3H		Polarization:	Vertical
Directivity:			Frequency:	16 (ATSC)
Main Lobe:	14.00 numeric	(11.46 dB)	Location:	Topeka, KS
Horizontal:	12.64 numeric	(11.02 dB)	Beam Tilt:	0.75 degrees



Tabulated Data for Elevation Pattern

Type: ATW14H3H



-10 to 10 degrees in 0.25 degree increments.

10 to 90 degrees in 0.50 degree increments.


Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB	Angle	Field	dB
-10.00	0.149	-16.54	2.25	0.741	-2.60	19.00	0.009	-40.92	43.50	0.147	-16.65	68.00	0.048	-26.38
-9.75	0.168	-15.49	2.50	0.657	-3.65	19.50	0.018	-34.89	44.00	0.154	-16.25	68.50	0.051	-25.85
-9.50	0.194	-14.24	2.75	0.570	-4.88	20.00	0.037	-28.64	44.50	0.154	-16.25	69.00	0.057	-24.88
-9.25	0.225	-12.96	3.00	0.485	-6.29	20.50	0.063	-24.01	45.00	0.146	-16.71	69.50	0.062	-24.15
-9.00	0.260	-11.70	3.25	0.408	-7.79	21.00	0.096	-20.35	45.50	0.132	-17.59	70.00	0.067	-23.48
-8.75	0.295	-10.60	3.50	0.348	-9.17	21.50	0.133	-17.52	46.00	0.111	-19.09	70.50	0.071	-22.97
-8.50	0.327	-9.71	3.75	0.310	-10.17	22.00	0.166	-15.60	46.50	0.086	-21.31	71.00	0.074	-22.62
-8.25	0.355	-9.00	4.00	0.298	-10.52	22.50	0.192	-14.33	47.00	0.059	-24.58	71.50	0.075	-22.50
-8.00	0.376	-8.50	4.25	0.307	-10.26	23.00	0.207	-13.68	47.50	0.033	-29.63	72.00	0.075	-22.50
-7.75	0.388	-8.22	4.50	0.327	-9.71	23.50	0.207	-13.68	48.00	0.016	-35.92	72.50	0.073	-22.73
-7.50	0.392	-8.13	4.75	0.349	-9.14	24.00	0.194	-14.24	48.50	0.025	-32.04	73.00	0.070	-23.10
-7.25	0.386	-8.27	5.00	0.366	-8.73	24.50	0.171	-15.34	49.00	0.039	-28.18	73.50	0.066	-23.61
-7.00	0.369	-8.66	5.25	0.375	-8.52	25.00	0.141	-17.02	49.50	0.050	-26.02	74.00	0.061	-24.29
-6.75	0.343	-9.29	5.50	0.374	-8.54	25.50	0.113	-18.94	50.00	0.056	-25.04	74.50	0.055	-25.19
-6.50	0.308	-10.23	5.75	0.363	-8.80	26.00	0.094	-20.54	50.50	0.057	-24.88	75.00	0.049	-26.20
-6.25	0.265	-11.54	6.00	0.342	-9.32	26.50	0.088	-21.11	51.00	0.054	-25.35	75.50	0.042	-27.54
-6.00	0.219	-13.19	6.25	0.313	-10.09	27.00	0.091	-20.82	51.50	0.049	-26.20	76.00	0.036	-28.87
-5.75	0.172	-15.29	6.50	0.278	-11.12	27.50	0.095	-20.45	52.00	0.046	-26.74	76.50	0.029	-30.75
-5.50	0.134	-17.46	6.75	0.239	-12.43	28.00	0.095	-20.45	52.50	0.046	-26.74	77.00	0.023	-32.77
-5.25	0.117	-18.64	7.00	0.199	-14.02	28.50	0.093	-20.63	53.00	0.049	-26.20	77.50	0.018	-34.89
-5.00	0.129	-17.79	7.25	0.163	-15.76	29.00	0.091	-20.82	53.50	0.055	-25.19	78.00	0.013	-37.72
-4.75	0.159	-15.97	7.50	0.134	-17.46	29.50	0.090	-20.92	54.00	0.060	-24.44	78.50	0.011	-39.17
-4.50	0.193	-14.29	7.75	0.119	-18.49	30.00	0.091	-20.82	54.50	0.062	-24.15	79.00	0.011	-39.17
-4.25	0.222	-13.07	8.00	0.120	-18.42	30.50	0.091	-20.82	55.00	0.062	-24.15	79.50	0.013	-37.72
-4.00	0.242	-12.32	8.25	0.132	-17.59	31.00	0.088	-21.11	55.50	0.057	-24.88	80.00	0.016	-35.92
-3.75	0.249	-12.08	8.50	0.148	-16.59	31.50	0.080	-21.94	56.00	0.049	-26.20	80.50	0.019	-34.42
-3.50	0.243	-12.29	8.75	0.164	-15.70	32.00	0.069	-23.22	56.50	0.039	-28.18	81.00	0.022	-33.15
-3.25	0.223	-13.03	9.00	0.177	-15.04	32.50	0.061	-24.29	57.00	0.030	-30.46	81.50	0.024	-32.40
-3.00	0.189	-14.47	9.25	0.186	-14.61	33.00	0.061	-24.29	57.50	0.030	-30.46	82.00	0.026	-31.70
-2.75	0.145	-16.77	9.50	0.193	-14.29	33.50	0.071	-22.97	58.00	0.042	-27.54	82.50	0.027	-31.37
-2.50	0.104	-19.66	9.75	0.198	-14.07	34.00	0.085	-21.41	58.50	0.060	-24.44	83.00	0.027	-31.37
-2.25	0.103	-19.74	10.00	0.201	-13.94	34.50	0.098	-20.18	59.00	0.079	-22.05	83.50	0.028	-31.06
-2.00	0.162	-15.81	10.50	0.211	-13.51	35.00	0.105	-19.58	59.50	0.098	-20.18	84.00	0.027	-31.37
-1.75	0.250	-12.04	11.00	0.227	-12.88	35.50	0.106	-19.49	60.00	0.115	-18.79	84.50	0.027	-31.37
-1.50	0.349	-9.14	11.50	0.245	-12.22	36.00	0.102	-19.83	60.50	0.129	-17.79	85.00	0.025	-32.04
-1.25	0.453	-6.88	12.00	0.254	-11.90	36.50	0.094	-20.54	61.00	0.139	-17.14	85.50	0.024	-32.40
-1.00	0.557	-5.08	12.50	0.248	-12.11	37.00	0.088	-21.11	61.50	0.147	-16.65	86.00	0.022	-33.15
-0.75	0.656	-3.66	13.00	0.223	-13.03	37.50	0.086	-21.31	62.00	0.150	-16.48	86.50	0.020	-33.98
-0.50	0.748	-2.52	13.50	0.181	-14.85	38.00	0.090	-20.92	62.50	0.150	-16.48	87.00	0.018	-34.89
-0.25	0.829	-1.63	14.00	0.128	-17.86	38.50	0.096	-20.35	63.00	0.146	-16.71	87.50	0.015	-36.48
0.00	0.896	-0.95	14.50	0.074	-22.62	39.00	0.101	-19.91	63.50	0.138	-17.20	88.00	0.012	-38.42
0.25	0.949	-0.45	15.00	0.041	-27.74	39.50	0.102	-19.83	64.00	0.128	-17.86	88.50	0.009	-40.92
0.50	0.983	-0.15	15.50	0.055	-25.19	40.00	0.099	-20.09	64.50	0.116	-18.71	89.00	0.006	-44.44
0.75	1.000	0.00	16.00	0.077	-22.27	40.50	0.093	-20.63	65.00	0.103	-19.74	89.50	0.003	-50.46
1.00	0.998	-0.02	16.50	0.087	-21.21	41.00	0.089	-21.01	65.50	0.089	-21.01	90.00	0.000	---
1.25	0.977	-0.20	17.00	0.081	-21.83	41.50	0.091	-20.82	66.00	0.075	-22.50			
1.50	0.940	-0.54	17.50	0.065	-23.74	42.00	0.101	-19.91	66.50	0.063	-24.01			
1.75	0.886	-1.05	18.00	0.043	-27.33	42.50	0.117	-18.64	67.00	0.053	-25.51			
2.00	0.819	-1.73	18.50	0.022	-33.15	43.00	0.133	-17.52	67.50	0.048	-26.38			

LIFT ANTENNA FROM TRUCK BED USING ANTENNA PLATES, NOT THE RADOMES, AT THE LOCATIONS INDICATED. TO PREVENT ROLLING, LIFT FROM THE PLATES AS SHOWN IN VIEW "X-X". DO NOT LIFT ANTENNA BY FIBERGLASS RADOMES, **DAMAGE WILL OCCUR.**

1. THE LIFTING DETAILS PROVIDED IDENTIFY THE PRIMARY RIGGING ATTACHMENT POINTS ON THE ANTENNA FOR DELIVERY LOADING/UNLOADING, UPENDING, AND HOISTING OPERATIONS.
2. ALL RIGGING COMPONENTS SHALL BE PROPERLY SELECTED AND SIZED BY THE CONTRACTOR'S QUALIFIED PERSON TO ENSURE THE COMPONENTS ARE UTILIZED IN ACCORDANCE WITH RIGGING MANUFACTURER'S WLL LIMITS AND ASSOCIATED SPECIFICATIONS.
3. CONTACT ERI FOR REVIEW AND APPROVAL IF ALTERNATE RIGGING ATTACHMENT POINTS ARE NEEDED FOR HANDLING OR HOISTING OPERATIONS.



DETAIL B



PROJECT NO.		35662E/1
ERI APPROVAL	NAME	DATE
DRAWN BY	ACB	7/10/2019
DRAFTING	GAG	7/10/2019
DESIGN MGR.	K.SCHARP	7/10/2019
ENG.		
MANUF.		
EXT. APPROVAL		
SUPERSEDES PART NO.		
FILE NAME: LD35662E-1.idw		



ELECTRONICS RESEARCH INC
ESTABLISHED 1943

7777 GARDNER Rd.
CHANDLER, IN
47610-9219
PHONE: (812) 925-6000
FAX: (812) 925-4030

TITLE:

LE: LIFTING DETAILS


35662E - TOPEKA, KS - CH. 16

SIZE B	CAGE CODE OZNS1	DWG NO. LD35662E-1	REV A
SCALE : 1 / 30		WEIGHT: N/A	SHEET: 1 OF 4



This document/drawing contains information considered confidential by Electronics Research Inc. ("ERI"). This information is disclosed on a confidential basis and only authorized for use in the installation, operation, and maintenance of ERI tower and antenna equipment, as appropriate. Reproduction, transmission or disclosure to others, or unauthorized use, without the express written consent of ERI, is strictly prohibited. UNAUTHORIZED DUPLICATION, REPRODUCTION, OR DISCLOSURE OF THIS INFORMATION IS A VIOLATION OF FEDERAL LAW. COPYRIGHT © 2019 ERI. ELECTRONICS RESEARCH INC.

THIRD ANGLE PROJECTION



MATERIAL

FINISH

TOLERANCES


OVERALL-NOT CUMULATIVE
UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE IN INCHES
AND APPLICABLE AT 20°C (68°F)

INTERPRET DIMENSIONS AND TOLERANCES
PER ASME Y14.5M-1994

1 PLACE DECIMAL $\pm .1$
2 PLACE DECIMAL $\pm .03$
3 PLACE DECIMAL $\pm .010$
ANGULAR $\pm .5^\circ$
FRACTIONAL $\pm 1/16"$


FIGURE #2

PLACE ALL ANTENNA RADOME JOINTS WITH THE STEEL CENTER PLATES ON WOODEN SUPPORTS AS SHOWN. ANTENNA SHOULD BE LEVEL TO PREVENT DAMAGE. USE SUPPORTS HIGH ENOUGH TO AVOID DAMAGING THE RADOMES AND TO ALLOW FOR ELECTRICAL GROUND TEST OF THE ANTENNA. PLATES RESTING 6.0 INCHES ABOVE THE GROUND IS SUFFICIENT.



This document/drawing contains information considered confidential by Electronics Research, Inc. ("ERI"). This information is disclosed on a confidential basis and only authorized for use in the installation, operation, and maintenance of ERI tower and antenna equipment, as appropriate. Reproduction, transmission or disclosure to others, or unauthorized use, without the express written consent of ERI, is strictly prohibited. UNAUTHORIZED DUPLICATION, REPRODUCTION, OR DISCLOSURE OF THIS INFORMATION IS A VIOLATION OF FEDERAL LAW. COPYRIGHT 2019 ERI, ELECTRONICS RESEARCH INC.

THIRD ANGLE PROJECTION




MATERIAL

FINISH

TOLERANCES
OVERALL-NOT CUMULATIVE
UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE IN INCHES
AND APPLICABLE AT 20°C (68°F)
1 PLACE DECIMAL ± .1
2 PLACE DECIMAL ± .03
3 PLACE DECIMAL ± .010
ANGULAR ± .5°
FRACTIONAL ± 1/16"

INTERPRET DIMENSIONS AND TOLERANCES
PER ASME Y14.5M-1994

PROJECT NO. 35662E/1		
ERI APPROVAL	NAME	DATE
DRAWN BY	ACB	7/10/2019
DRAFTING	GAG	7/10/2019
DESIGN MGR.	K.SCHARP	7/10/2019
ENG.		
MANUF.		
EXT. APPROVAL		
SUPERSEDES PART NO.		
FILE NAME: LD35662E-1.idw		


 ELECTRONICS RESEARCH INC. ESTABLISHED 1943			7777 GARDNER Rd. CHANDLER, IN 47610-9219 PHONE: (812) 925-6000 FAX: (812) 925-4030		
TITLE: LIFTING DETAILS 35662E - TOPEKA, KS - CH. 16					
SIZE B	CAGE CODE OZNS1	DWG NO. LD35662E-1			REV. A
SCALE : 1 / 30		WEIGHT: N/A		SHEET: 2 OF 4	

4 3 2 1

FIGURE #3A


WHEN LIFTING THE ANTENNA FOR INSTALLATION, LIFT AS SHOWN TO PREVENT DAMAGE TO THE BASE OF THE ANTENNA. WHEN THE ANTENNA IS VERTICAL, THE ADDITIONAL BASE LIFTING CABLE CAN BE REMOVED. (SEE FIGURE #3B).

NOTE: THIS ILLUSTRATION IS INTENDED TO SHOW A CONCEPT FOR LIFTING THE ERI INC. TRASAR ANTENNA TO PREVENT DAMAGE TO THE ANTENNA AND THE RADOMES. SAFE AND PROPER IMPLEMENTATION OF THIS CONCEPT ARE THE RESPONSIBILITY OF THE INSTALLER.



This document/drawing contains information considered confidential by Electronics Research, Inc. ("ERI"). This information is disclosed on a confidential basis and only authorized for use in the installation, operation, and maintenance of ERI tower and antenna equipment, as appropriate. Reproduction, transmission or disclosure to others, or unauthorized use, without the express written consent of ERI, is strictly prohibited. UNAUTHORIZED DUPLICATION, REPRODUCTION, OR DISCLOSURE OF THIS INFORMATION IS A VIOLATION OF FEDERAL LAW. COPYRIGHT 2019 ERI, ELECTRONICS RESEARCH INC.

THIRD ANGLE PROJECTION



MATERIAL

FINISH

TOLERANCES
OVERALL-NOT CUMULATIVE
UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE IN INCHES
AND APPLICABLE AT 20°C (68°F)
INTERPRET DIMENSIONS AND TOLERANCES
PER ASME Y14.5M-1994

1 PLACE DECIMAL ± .1
2 PLACE DECIMAL ± .03
3 PLACE DECIMAL ± .010
ANGULAR ± .5°
FRACTIONAL ± 1/16"

PROJECT NO. 35662E/1		
ERI APPROVAL	NAME	DATE
DRAWN BY	ACB	7/10/2019
DRAFTING	GAG	7/10/2019
DESIGN MGR.	K.SCHARP	7/10/2019
ENG.		
MANUF.		
EXT. APPROVAL		
SUPERSEDES PART NO.		
FILE NAME: LD35662E-1.idw		



		ELECTRONICS RESEARCH INC. <i>ESTABLISHED 1943</i>		7777 GARDNER Rd. CHANDLER, IN 47610-9219 PHONE: (812) 925-6000 FAX: (812) 925-4030	
TITLE:					
LIFTING DETAILS					
35662E - TOPEKA, KS - CH. 16					
SIZE	CAGE CODE	DWG NO.			REV.
B	OZNS1	LD35662E-1			A
SCALE :		WEIGHT:	SHEET:		
1 / 30		N/A	3 OF 4		


FIGURE #3B

NOTE: THIS ILLUSTRATION IS INTENDED TO SHOW A CONCEPT FOR LIFTING THE ERI, INC. TRASAR ANTENNA TO PREVENT DAMAGE TO THE ANTENNA AND THE RADOMES. SAFE AND PROPER IMPLEMENTATION OF THIS CONCEPT ARE THE RESPONSIBILITY OF THE INSTALLER.



This document/drawing contains information considered confidential by Electronics Research, Inc. ("ERI"). This information is disclosed on a confidential basis and only authorized for use in the installation, operation, and maintenance of ERI tower and antenna equipment, as appropriate. Reproduction, transmission or disclosure to others, or unauthorized use, without the express written consent of ERI, is strictly prohibited. UNAUTHORIZED DUPLICATION, REPRODUCTION, OR DISCLOSURE OF THIS INFORMATION IS A VIOLATION OF FEDERAL LAW. COPYRIGHT 2019 ERI, ELECTRONICS RESEARCH INC.

THIRD ANGLE PROJECTION




MATERIAL

FINISH

TOLERANCES
OVERALL-NOT CUMULATIVE
UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE IN INCHES
AND APPLICABLE AT 20°C (68°F)
INTERPRET DIMENSIONS AND TOLERANCES
PER ASME Y14.5M-1994

1 PLACE DECIMAL ± .1
2 PLACE DECIMAL ± .03
3 PLACE DECIMAL ± .010
ANGULAR ± .5°
FRACTIONAL ± 1/16"

PROJECT NO. 35662E/1		
ERI APPROVAL	NAME	DATE
DRAWN BY	ACB	7/10/2019
DRAFTING	GAG	7/10/2019
DESIGN MGR.	K.SCHARP	7/10/2019
ENG.		
MANUF.		
EXT. APPROVAL		
SUPERSEDES PART NO.		
FILE NAME: LD35662E-1.idw		



ELECTRONICS RESEARCH INC.
ESTABLISHED 1943

7777 GARDNER Rd.
CHANDLER, IN
47610-9219
PHONE: (812) 925-6000
FAX: (812) 925-4030

TITLE:
LIFTING DETAILS
35662E - TOPEKA, KS - CH. 16

SIZE B	CAGE CODE OZNS1	DWG NO. LD35662E-1	REV. A
SCALE : 1 / 30		WEIGHT: N/A	SHEET: 4 OF 4

4

3

2

1

NOTES:

1. REMOVE ALL BURRS AND SHARP EDGES.

2. LOC-TITE ALL THREADS PER BOP 2.02.01.

3. TORQUE ALL 5/8" HARDWARE TO 60-65 FT/LBS.

4. TORQUE ALL 1/2" HARDWARE TO 50-65 FT/LBS.

5. TORQUE ALL 3/8" HARDWARE TO 28 FT/LBS.

6. ALL EXTERIOR HARDWARE TO BE ASSEMBLED WITH THE HEAD OF THE BOLT TOWARDS THE BOTTOM OF THE ANTENNA.

7. USE SMALL ERI SHIPPING LABEL WHERE NOTED.

8. USING BLACK PAINT, STENCIL AS SHOWN, USING MIN. 1/2" HIGH CHARACTERS.

9. BEFORE PULLING ELECTRICAL CABLE FOR LIGHT, RELEASE PRESSURE ON ANTENNA TO PREVENT DAMAGE. AFTER CABLE IS INSTALLED, ANTENNA MUST BE PLACED BACK UNDER PRESSURE TO 5 PSIG MAX.

CONNECTION NOTES:

1. FOR PROPER PERFORMANCE AFTER INSTALLATION, PLUMB THE ANTENNA TO WITHIN 0.1° FROM VERTICAL (5/8 INCH IN 30 FEET). A KIT OF SHIMS IS INCLUDED WITH THE ANTENNA. AS REQUIRED FOR PROPER PLUMB, GAPS BETWEEN ANTENNA MOUNTING FLANGE AND TOWER TOP PLATE MUST BE FILLED USING THE SUPPLIED SHIM KIT OR SUITABLE STEEL SHIM STOCK.

2. ANTENNA MOUNTING FLANGE BOLTED CONNECTION SHALL BE BROUGHT TO A SNUG-TIGHT CONDITION WHERE JOINT TIGHTNESS IS ATTAINED WITH A FEW IMPACTS OF AN IMPACT WRENCH OR FULL EFFORT OF AN IRONWORKER USING AN ORDINARY SPUD WRENCH TO BRING THE PLIES INTO "FIRM" CONTACT, AND THEN AN ADDITIONAL 1/3 TURN (120° ± 30°) APPLIED TO THE NUT OR BOLT HEAD FOR FINAL BOLT TIGHTENING. A SYSTEMATIC APPROACH SHALL BE USED WHEN TIGHTENING THE BOLTS STARTING WITH THE MOST RIGID PART OF THE JOINT. THE PART NOT TURNED BY THE WRENCH SHALL BE PREVENTED FROM ROTATING DURING THIS OPERATION.

3. IT IS ERI'S INTENTION THAT AN ANCO LOCKNUT BE PROVIDED FOR ALL HIGH-STRENGTH ASTM A325 BOLTED CONNECTIONS, UNLESS OTHERWISE NOTED. FLAT WASHERS ARE REQUIRED ON MOUNTING FLANGE CONNECTIONS.

4. UNLESS OTHERWISE NOTED, ALL ANTENNA MOUNTING FLANGE HARDWARE GRADES ARE AS FOLLOWS:

TABLE	
COMPONENT	DESCRIPTION
STRUCTURAL BOLT	ASTM A325 GALVANIZED
ANCO LOCKNUT	ASTM A563 GRADE DH GALVANIZED HEAVY HEX NUT WITH STAINLESS PIN
FLAT WASHER	ASTM F436 TYPE I GALVANIZED

REVISION HISTORY

REV	DESCRIPTION	DATE	APPROVED
A	ADDED ITEMS #13, #14 & #15	10/31/19	K. SCHARP
B	ITEM #5 QTY WAS 2, ITEM #6 WAS STUB-6.25, ITEM #7 WAS INPUT-6.25-1.711	11/5/19	K. SCHARP
C	ADDED NOTE #9 TO ALL (3) PAGES	4/29/2020	K. SCHARP

15

16

NLA2007GA

1 1/4-7 GALV. ANCO LOCK NUT

14

32

WF20GA

1-1/4" FLAT WASHER F436 HDG STRUCTURAL

13

16

SC2007H0700GA

1 1/4-7 UNC x 7.00 in A325 Galv. Hex Bolt, 4" THREAD

12

1

167423

SHIM PAK (NOT SHOWN)

11

4

LRK0007-KIT

LIGHTNING SPUR HARDWARE KIT

10

12

LR0075-N003

LIGHTNING ROD ARRESTOR TIP

9

4

LR0062-4800GA-N001

5/8"-11 X 48" 30 DEG BENT GALV W/2 NUT

8

1

ACX675-20

6-1/8" 75 OHM STANDARD INNER CONNECTOR

7

1

STRINPUT-6.25-1.711

6.25" INPUT ADAPTOR

6

5

1

RLA600-21

6-1/8" HARDWARE KIT

4

1

68157

6" INPUT HARDWARE KIT

3

1

66593

PRESSURE LABEL

2

1

38296-61

TRASAR LABEL

1

1

TA35662E-1

Ø8.625 TOP LEVEL ASSEMBLY

ITEM

QTY

PART NUMBER

DESCRIPTION

BILL OF MATERIAL

PROJECT NO.

35662E/1

ERI APPROVAL

NAME

DATE

DRAWN BY

ACB

7/9/2019

DRAFTING

GAG

7/11/2019

DESIGN MGR.

K.SCHARP

7/11/2019

ENG.

MANUF.

EXT. APPROVAL

SUPERSEDES PART NO.

FILE NAME:

PM35662E-1.idw

SIZE

B

CAGE CODE

OZNS1

DWG NO.

PM35662E-1

REV.

C

TITLE:

MECH. PARAMETERS / INSTALLATION ASS'Y.

35662E - TOPEKA, KS - CH. 16

SCALE :

1 / 55

WEIGHT:

N/A

SHEET:

1 OF 3

AMERICAN INSTITUTE OF STEEL CONSTRUCTION

★

★

FOUNDED 1921

ASCE

CERTIFIED FABRICATOR

This document/drawing contains information considered confidential by Electronics Research, Inc. ("ERI"). This information is disclosed on a confidential basis and only authorized for use in the installation, operation, and maintenance of ERI tower and antenna equipment, as appropriate. Reproduction, transmission or disclosure to others, or unauthorized use, without the express written consent of ERI, is strictly prohibited. UNAUTHORIZED DUPLICATION, REPRODUCTION, OR DISCLOSURE OF THIS INFORMATION IS A VIOLATION OF FEDERAL LAW. COPYRIGHT 2019 ERI, ELECTRONICS RESEARCH INC.

THIRD ANGLE PROJECTION

MATERIAL

FINISH

TOLERANCES

OVERALL-NOT CUMULATIVE

UNLESS OTHERWISE SPECIFIED,

ALL DIMENSIONS ARE IN INCHES

AND APPLICABLE AT 20°C (68°F)

1 PLACE DECIMAL ± .1

2 PLACE DECIMAL ± .03

3 PLACE DECIMAL ± .010

ANGULAR ± .5°

FRACTIONAL ± 1/16"

INTERPRET DIMENSIONS AND TOLERANCES

PER ASME Y14.5M-1994


D:\Workspace\Designs\35662E\1\PM35662E-1.idw

ACB7/9/2019

3

2

1




PRESSURE NOTE:

BEFORE PULLING ELECTRICAL CABLE FOR LIGHT, RELEASE PRESSURE ON ANTENNA TO PREVENT DAMAGE. AFTER CABLE IS INSTALLED, ANTENNA MUST BE PLACED BACK UNDER PRESSURE TO 5 PSIG MAX.



This document/drawing contains information considered confidential by Electronics Research, Inc. ("ERI"). This information is disclosed on a confidential basis and only authorized for use in the installation, operation, and maintenance of ERI tower and antenna equipment, as appropriate. Reproduction, transmission or disclosure to others, or unauthorized use, without the express written consent of ERI, is strictly prohibited. UNAUTHORIZED DUPLICATION, REPRODUCTION, OR DISCLOSURE OF THIS INFORMATION IS A VIOLATION OF FEDERAL LAW. COPYRIGHT 2019 ERI, ELECTRONICS RESEARCH INC.




MATERIAL


FINISH

TOLERANCES
OVERALL-NOT CUMULATIVE
UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE IN INCHES
AND APPLICABLE AT 20°C (68°F)
INTERPRET DIMENSIONS AND TOLERANCES
PER ASME Y14.5M-1994

1 PLACE DECIMAL ± .1
2 PLACE DECIMAL ± .03
3 PLACE DECIMAL ± .010
ANGULAR ± .5°
FRACTIONAL ± 1/16"

PROJECT NO.	35662E/1	
ERI APPROVAL	NAME	DATE
DRAWN BY	ACB	7/9/2019
DRAFTING	GAG	7/11/2019
DESIGN MGR.	K.SCHARP	7/11/2019
ENG.		
MANUF.		
EXT. APPROVAL		
SUPERSEDES PART NO.		
FILE NAME: PM35662E-1.idw		

		ELECTRONICS RESEARCH INC. <i>ESTABLISHED 1943</i>		7777 GARDNER Rd. CHANDLER, IN 47610-9219 PHONE: (812) 925-6000 FAX: (812) 925-4030
TITLE: MECH. PARAMETERS / INSTALLATION ASS'Y. 35662E - TOPEKA, KS - CH. 16				
SIZE B	CAGE CODE OZNS1	DWG NO. PM35662E-1		REV. C
SCALE : 1 / 55		WEIGHT: N/A	SHEET: 2 OF 3	




PRESSURE NOTE:

BEFORE PULLING ELECTRICAL CABLE FOR LIGHT, RELEASE PRESSURE ON ANTENNA TO PREVENT DAMAGE. AFTER CABLE IS INSTALLED, ANTENNA MUST BE PLACED BACK UNDER PRESSURE TO 5 PSIG MAX.



This document/drawing contains information considered confidential by Electronics Research, Inc. ("ERI"). This information is disclosed on a confidential basis and only authorized for use in the installation, operation, and maintenance of ERI tower and antenna equipment, as appropriate. Reproduction, transmission or disclosure to others, or unauthorized use, without the express written consent of ERI, is strictly prohibited. UNAUTHORIZED DUPLICATION, REPRODUCTION, OR DISCLOSURE OF THIS INFORMATION IS A VIOLATION OF FEDERAL LAW. COPYRIGHT 2019 ERI, ELECTRONICS RESEARCH INC.




MATERIAL

FINISH

TOLERANCES
OVERALL-NOT CUMULATIVE
UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE IN INCHES
AND APPLICABLE AT 20°C (68°F)
INTERPRET DIMENSIONS AND TOLERANCES
PER ASME Y14.5M-1994

1 PLACE DECIMAL ± .1
2 PLACE DECIMAL ± .03
3 PLACE DECIMAL ± .010
ANGULAR ± .5°
FRACTIONAL ± 1/16"

PROJECT NO.	35662E/1	
ERI APPROVAL	NAME	DATE
DRAWN BY	ACB	7/9/2019
DRAFTING	GAG	7/11/2019
DESIGN MGR.	K.SCHARP	7/11/2019
ENG.		
MANUF.		
EXT. APPROVAL		
SUPERSEDES PART NO.		
FILE NAME: PM35662E-1.idw		

		ELECTRONICS RESEARCH INC. ESTABLISHED 1943		7777 GARDNER Rd. CHANDLER, IN 47610-9219 PHONE: (812) 925-6000 FAX: (812) 925-4030	
TITLE: MECH. PARAMETERS / INSTALLATION ASS'Y. 35662E - TOPEKA, KS - CH. 16					
SIZE B	CAGE CODE OZNS1	DWG NO. PM35662E-1			REV. C
SCALE : 1 / 55	WEIGHT: N/A		SHEET: 3 OF 3		