

TELECOMMUNICATIONS ENGINEERING
GRAY FRIERSON HAERTIG & ASSOC.
4646 S.W. COUNCIL CREST DRIVE
PORTLAND, OREGON 97239
503-282-2989 (Office)
503-807-2989 (Cell)

ELECTRONIC MAIL
gfh@haertig.com

17 March 2021
Prepared for the Jicarilla Apache Tribe

RADIOFREQUENCY FIELDS

An engineering analysis was performed to determine whether the facilities proposed herein comply with the Maximum Permissible Exposure standards outlined in 47CFR1.1310 as regards human exposure to radiofrequency electromagnetic fields and whether environmental processing would be required.

The applicant proposes to operate at 0.55 kilowatts, elliptically polarized, using a Shively 6810-2/DA antenna mounted at the 13-meter level of an existing 15 meter tower. This antenna consists of two radiating elements spaced one wavelength apart.

The antenna support structure is located near the apex of a local promontory. There are no other significant emitters of radiofrequency energy in the immediate vicinity. The base of the tower is accessible to the general public.

The Commission's FMModel computer software was used to calculate the radiofrequency electromagnetic power density in a plane 2 meters AGL as a function of the distance from the antenna support structure. A copy of the graphical output of this program is attached.

The highest power density occurs at a point 2.6 meters from the base of the tower and is equal to 178 uW/cm^2 . This represents 89% of the general public/uncontrolled MPE standard.

Appropriate signs will be installed at the base of the tower warning workers and others that the maximum permissible exposure standard may be exceeded at locations on the tower.

The applicant believes that the facilities proposed herein conform to the MPE standards outlined in 47CFR1.1310 and that environmental processing is not warranted.

