

**GREG BEST  
CONSULTING, INC.**

16100 Outlook Avenue  
Stilwell, KS 66085  
816-792-2913

March 2, 2021

Federal Communications Commission  
Media Bureau  
445 12<sup>th</sup> Street SW  
Washington, DC 20554

Dear Sir,

This will serve as the exhibit for the RF Radiation Hazard calculation for this proposed facility.

The RF radiation near the ground (2 meters above ground) can be calculated using the OET-65 formula for broadcast television stations taking into account the following factors

S= power density in watts per square meter

P= total Effective Radiated Power from the antenna

F= field radiated on the axis to the ground level

R= distance to the ground level (actually 2 meters above ground)

Therefore, given the following data for the proposed facility:

P= 19.5 kwatts (15 kW Hpol + 4.5 kW Vpol)

R=Radiation center above building rooftop level – 2 meters)  
= 5.62 meters

F= 0.1 for UHF antennas

The RF radiation near the ground level can be calculated with the following result:

206  $\mu\text{watts/cm}^2$

which is 55.5 % of the general population exposure limit of 371  $\mu\text{w/cm}^2$  for this channel 28 facility

The licensee, in coordination with the other users of the antenna facility, will reduce power or cease operation as necessary to protect persons having access to the tower or antenna from RF energy in excess of the FCC guidelines.

Should you have any questions regarding this information please contact me.

Sincerely,



President