

# Gallup Public Radio

Black Rock 220

REFERENCE  
35 07 04.00 N.  
108 44 38.00 W.

CH# 220A - 91.9 MHz, Pwr= 0.1 kW DA, HAAT= 108.2 M, COR= 2188 M  
Average Protected F(50-50)= 10.71 km  
Standard Directional

DISPLAY DATES  
DATA 10-30-21  
SEARCH 10-30-21

CH CITY	CALL	TYPE STATE	ANT STATE	AZI <--	DIST FILE #	LAT LNG	PWR(kw) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
219C3 Gallup	KGLP	LIC _CN NM		6.1 186.2	54.32 BLED20060126AHR	35 36 13.10 108 40 47.30	0.880 350	48.4 2414	31.6 Gallup Public Radio	1.0	16.2
221C1 Holbrook	KZUA^	LIC _CN AZ		260.5 79.7	128.28 BLH20110701AAG	34 55 13.10 110 07 55.40	100.000 299	105.3 1894	72.7 Petracom Of Holbrook, L.L.	8.0	34.4
219C2 Springerville	AL4362	____ AZ		218.9 38.4	123.26	34 15 06.16 109 35 08.35	50.000 150	97.2 2391	66.9	10.8	34.5
217A Houck	KHCK	LIC _HN AZ		292.1 111.8	49.38 BLED20110822AEV	35 17 01.10 109 14 53.30	0.200 1	1.0 1930	6.9 Advance Ministries, Inc.	37.8	40.0
223C1 Eagar	KTHQ«	LIC _CN AZ		218.9 38.4	123.21 BLH20100426AAW	34 15 06.10 109 35 08.30	65.000 359	11.3 2602	84.2 wsk Family Credit Shelter	75.0R	48.2M

Terrain database is FCC NGDC 30 Sec , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM  
In & Out distances between contours are shown at closest points. Reference zone= - Zone 2, Co to 3rd adjacent.  
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, \_= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)  
« = Station meets FCC minimum distance spacing for its class.  
^ = Power and antenna height 'Max classed' as per Sec 73.215 protection requirements