



RADIO FREQUENCY IMPACT, SAFETY & STATEMENT OF COMPLIANCE

The licensee of KSNV is committed to the protection of station personnel and/or tower contractors working near the KSNV antenna at KTNV-TV's studio tower and will reduce power or cease operation, when necessary, to ensure protection to personnel.

As shown in Appendix A the proposed KSNV channel 33 experimental STA facility proposed herein will operate with a maximum ERP of 42 kW from an elliptically polarized directional transmitting antenna with a centerline height of 47.4 meters above ground level (AGL). Considering the elevation pattern submitted elsewhere in this application, the vertical plane relative field factor is less than 0.210 at all depression angles greater than 12 degrees. The proposed experimental STA facility is predicted to produce a worst-case power density at two meters above ground level, at 31.8 meters from the tower base, of $15.674 \mu\text{W}/\text{cm}^2$, which is 4.01% of the FCC guideline value of $391.33 \mu\text{W}/\text{cm}^2$ for an "uncontrolled" environment, and 0.802% of the FCC's guideline value for "controlled" environments. Therefore, pursuant to Section 1.1307(b)(3) of the FCC Rules, because the proposed facility would not exceed 5% of the uncontrolled and controlled exposure limits, the proposal's power density contribution is considered insignificant.

Further, the applicant will continue to cooperate and coordinate with other any other site users and reduce power or cease operation during times of service or maintenance of the transmission systems as necessary to avoid potentially harmful exposure to personnel. In light of the above, the proposed facility should be categorically excluded from RF environmental processing under Section 1.1307(b) of the Commission's Rules.

KSNV-STA
Channel 33 - Las Vegas, Nevada
ERP = 42000.00 WATTS

APPENDIX A

Maximum ERP 42 kW

Polarization ----- 2 Circular
 Antenna Height Above Ground - 47.4 meters 155.5 feet
 FCC Uncontrolled RFR Limit --- 391.33 $\mu\text{W}/\text{cm}^2$

Maximum Computed Power Density 15.674 $\mu\text{W}/\text{cm}^2$
 4.01% of limit

Angle Below Horizontal (degrees)	<Point X> Horiz Distance from tower to 2 m AGL (meters)	Slant Distance from antenna to Point X (meters)	Vertical Pattern (REL. FIELD)	KSNV-STA ERP (kW)	KSNV-STA Calculated Power Density $\mu\text{W}/\text{cm}^2$	Percent Limit	Limit Exceeded?
0			1.000	42.0000			
5	518.9	520.9	0.575	13.8863	3.419	0.87%	No
10	257.5	261.4	0.329	4.5461	4.443	1.14%	No
15	169.4	175.4	0.081	0.2756	0.598	0.15%	No
20	124.7	132.7	0.168	1.1854	4.494	1.15%	No
25	97.4	107.4	0.073	0.2238	1.296	0.33%	No
30	78.6	90.8	0.052	0.1136	0.920	0.24%	No
35	64.8	79.2	0.110	0.5082	5.419	1.38%	No
40	54.1	70.6	0.110	0.5082	6.805	1.74%	No
45	45.4	64.2	0.070	0.2058	3.335	0.85%	No
50	38.1	59.3	0.109	0.4990	9.490	2.43%	No
55	31.8	55.4	0.131	0.7208	15.674	4.01%	No
60	26.2	52.4	0.060	0.1512	3.675	0.94%	No
65	21.2	50.1	0.005	0.0011	0.028	0.01%	No
70	16.5	48.3	0.100	0.4200	12.019	3.07%	No
75	12.2	47.0	0.066	0.1830	5.532	1.41%	No
80	8.0	46.1	0.030	0.0378	1.188	0.30%	No
85	4.0	45.6	0.007	0.0021	0.066	0.02%	No
90	0.0	45.4	0.000	0.0000	0.000	0.00%	No

