

**March 2005**  
**WPAY-FM Channel 281C Portsmouth, Ohio**  
**NIER Analysis**

**Facilities Proposed**

The proposed operation will be on Channel 281C (104.1 MHz) with a maximum lobe effective radiated power of 100 kilowatts. Operation is proposed with an antenna to be side-mounted on a uniform cross-section guyed tower. There are no other broadcast stations at this site.

Notice of the proposed tower construction has been filed with the Federal Aviation Administration on FAA Form 7460-1. Upon receipt of the FAA's determination of no hazard, FCC Antenna Structure Registration for the tower will be filed on FCC Form 854, and the resulting Antenna Structure Registration Number will be promptly supplied to the Audio Services Division.

**NIER Calculations**

The power density calculations shown below were made using the techniques outlined in OET Bulletin No. 65. "Ground level" calculations in this report have been made at a reference height of 2 meters above ground to provide a worst-case estimate of exposure for persons standing on the ground in the vicinity of the tower. The equation shown below was used to calculate the ground level power density figures from each antenna.

$$S(\text{mW} / \text{cm}^2) = \frac{33.40981 \times \text{AdjERP}(\text{Watts})}{D^2}$$

Where: *AdjERP(Watts)* is the maximum lobe effective radiated power times the element pattern factor times the array pattern factor.

*D* is the distance in meters from the center of radiation to the calculation point.

"Worst case" calculations of the power density produced by the antenna system have been made using the above formula, presuming that the antenna will radiate 200 kW (100 kW

Hatfield & Dawson Consulting Engineers

Horizontal + 100 kW Vertical) straight down. The results indicate a maximum ground level power density of  $53.3 \mu\text{W}/\text{cm}^2$ , which is 5.3% of  $1000 \mu\text{W}/\text{cm}^2$  (the FCC standard for controlled environments) and 26.7% of  $200 \mu\text{W}/\text{cm}^2$  (the FCC standard for uncontrolled environments). This is a worst-case figure. The actual ground level power densities from the antenna to be used will likely be lower.

Public access to the site will be restricted and the antenna tower will be posted with warning signs. Pursuant to OET Bulletin No. 65, all station personnel and contractors are required to follow appropriate safety procedures before any work is commenced on the antenna tower, including reduction in power or discontinuance of operation before any maintenance work is undertaken.

The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency radiation in excess of FCC guidelines.