

## K207BK Minor Change

Educational Communications Of Colorado Springs, Inc.

REFERENCE  
37 23 03.0 N.  
102 17 01.0 W.CH# 207D - 89.3 MHz, Pwr= 0.25 kW, HAAT= 51.5 M, COR= 1247 M  
Average Protected F(50-50)= 9.42 km  
Omni-directionalDISPLAY DATES  
DATA 11-06-16  
SEARCH 11-06-16

CH CITY	CALL	TYPE STATE	ANT	AZI <--	DIST FILE #	LAT LNG	PWR(kW) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
207D Walsh	<del>K207BK</del>	LIC _C_ CO		20.3 200.3	0.49 BLFT19941212TF	37 23 18.0 102 16 54.0	0.250 56	27.9 1251	8.4 Educational	-38.2*	-44.4*
207D Lamar Translator	K207BI KTLFFM,	LIC _CN CO		339.1 158.9	77.62 BLFT19931026TJ	38 02 10.0 102 35 58.0	0.250 129	43.9 1275	12.9 Educational	24.7	36.4
208A Lamar	DKTLH	LIC _CX CO		339.1 158.9	77.62 BLED20120629ADL	38 02 10.0 102 35 58.0	1.500 130	30.0 1275	20.7 Educational	38.5	44.5

Terrain database is NGDC 30 SEC , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM  
In & Out distances between contours are shown at closest points. Reference zone= West Zone, Co to 3rd adjacent.  
All separation margins (if shown) include rounding. Call signs with strikeout need not be protected.  
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, \_= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)  
\*\*\*affixed to 'IN' or 'OUT' values = site inside restricted contour.