

Quick Contours: Cell 0000001 (KNMO)

EDX contour file 0.000 360.000 5.000 -1.000 331.00 1 0.000 KNMO
37.800 97.E

DISTANCES TO CONTOURS (Kilometers):

Antenna COR elevation (AMSL): 331 mtrs Average HAAT: 87 mtrs
Frequency: 97.5000 MHz

Coordinates: N 37 52 45.17 w 94 20 14.90
F(50,50) Curves Number of Contours: 2 7

AZ HAAT ERPd CONTOUR LEVELS (dBu):
(degs) (m) (kW) 70.0 60.0

0.0	106	6.0256	16.7	29.2
5.0	106	6.0256	16.7	29.3
10.0	104	6.0256	16.5	29.0
15.0	102	6.0256	16.4	28.8
20.0	100	6.0256	16.2	28.5
25.0	97	6.0256	15.9	28.1

KNMO, Harbit Communications, Inc.
Nevada, Missouri

MODIFICATION OF PENDING

APPLICATION

30.0	95	6.0256	15.7	27.8
35.0	91	6.0256	15.4	27.3

EXHIBIT E-2
Distance to Contour, HAAT

Calculation

40.0	85	6.0256	15.0	26.5
45.0	74	6.0256	14.0	24.9
50.0	72	6.0256	13.8	24.6
55.0	75	6.0256	14.1	25.1
60.0	76	6.0256	14.2	25.2
65.0	73	6.0256	13.9	24.7
70.0	72	6.0256	13.8	24.6
75.0	77	6.0256	14.3	25.4
80.0	81	6.0256	14.6	25.9
85.0	81	6.0256	14.6	26.0
90.0	81	6.0256	14.6	25.9
95.0	80	6.0256	14.6	25.9
100.0	80	6.0256	14.5	25.8
105.0	81	6.0256	14.6	26.0
110.0	79	6.0256	14.5	25.7
115.0	76	6.0256	14.1	25.1
120.0	73	6.0256	13.8	24.6
125.0	71	6.0256	13.7	24.4
130.0	69	6.0256	13.5	24.0
135.0	66	6.0256	13.2	23.6
140.0	65	6.0256	13.1	23.3
145.0	65	6.0256	13.1	23.4
150.0	65	6.0256	13.1	23.4
155.0	63	6.0256	12.9	22.9
160.0	62	6.0256	12.8	22.8
165.0	63	6.0256	12.9	22.9
170.0	67	6.0256	13.3	23.7
175.0	72	6.0256	13.8	24.6
180.0	78	6.0256	14.4	25.6
185.0	84	6.0256	14.8	26.3
190.0	83	6.0256	14.8	26.3
195.0	83	6.0256	14.8	26.3

200.0	87	6.0256	15.1	26.7
205.0	86	6.0256	15.0	26.7
210.0	83	6.0256	14.8	26.2
215.0	81	6.0256	14.6	26.0
220.0	80	6.0256	14.5	25.8
225.0	83	6.0256	14.8	26.3
230.0	85	6.0256	15.0	26.6
235.0	88	6.0256	15.2	26.9
240.0	89	6.0256	15.3	27.1
245.0	90	6.0256	15.4	27.3
250.0	94	6.0256	15.7	27.7
255.0	98	6.0256	16.0	28.3
260.0	100	6.0256	16.2	28.5
265.0	99	6.0256	16.1	28.3
270.0	97	6.0256	16.0	28.2

P;ap I

Quick Contours: Cell 0000001 (KNM0)

275.0	96	6.0256	15.9	28.0
280.0	95	6.0256	15.8	27.9
285.0	96	6.0256	15.8	28.0
290.0	97	6.0256	15.9	28.2
295.0	97	6.0256	15.9	28.1
300.0	97	6.0256	15.9	28.1
305.0	97	6.0256	15.9	28.2
310.0	100	6.0256	16.1	28.5
315.0	101	6.0256	16.3	28.7
320.0	103	6.0256	16.4	28.9
325.0	103	6.0256	16.4	28.8
330.0	102	6.0256	16.3	28.8
335.0	100	6.0256	16.2	28.5
340.0	100	6.0256	16.2	28.5
345.0	103	6.0256	16.4	28.8
350.0	105	6.0256	16.6	29.1
355.0	105	6.0256	16.6	29.1
360.0	106	6.0256	16.7	29.2