

EXHIBIT 15-N-2 Tabulation of Distance to WDVA Daytime Allocation Contours

WDVA	1250 kHz	Lic	DANU	BL791221AG	01-Jan-2007
VA	DANVILLE		5.000 kW	1 Tower	0 Augmentations
N. Lat:	36 34 53	W. Lon:	79 26 33		0 Measured Cond

Conductivities are from M-3 map unless supplemented by measurements.
All distances are in kilometers (US metric curves)
All radiations are in mV/m at one kilometer

Bearing	Radiation	Distance to Contours	
		0.500	0.025
0.0	725.8	56.49	166.59
5.0	725.8	57.28	167.80
10.0	725.8	57.28	167.83
15.0	725.8	57.09	167.19
20.0	725.8	56.59	166.70
25.0	725.8	56.22	166.33
30.0	725.8	55.96	166.06
35.0	725.8	55.78	165.88
40.0	725.8	55.58	165.68
45.0	725.8	55.48	165.58
50.0	725.8	55.47	165.57
55.0	725.8	55.54	165.64
60.0	725.8	55.71	165.81
65.0	725.8	55.97	166.07
70.0	725.8	56.14	166.24
75.0	725.8	56.36	166.46
80.0	725.8	56.68	166.79
85.0	725.8	57.13	167.23
90.0	725.8	57.28	167.81
95.0	725.8	57.28	168.13
100.0	725.8	57.28	168.57
105.0	725.8	57.28	169.15
110.0	725.8	57.28	169.68
115.0	725.8	57.28	170.36
120.0	725.8	57.28	171.24
125.0	725.8	57.28	172.20
130.0	725.8	57.28	173.28
135.0	725.8	57.28	175.73
140.0	725.8	57.28	183.56
145.0	725.8	57.28	189.82
150.0	725.8	57.28	191.32
155.0	725.8	57.28	184.99
160.0	725.8	57.28	182.17
165.0	725.8	57.28	180.50
170.0	725.8	57.28	179.93
175.0	725.8	57.28	180.17

EXHIBIT 15-N-2 (cont.)
 Tabulation of Distance to WDVA Daytime Allocation Contours

WDVA	1250 kHz	Lic	DANU	BL791221AG	01-Jan-2007
VA	DANVILLE		5.000 kW	1 Tower	0 Augmentations
N. Lat:	36 34 53	W. Lon:	79 26 33		0 Measured Cond

Bearing	Radiation	Distance to Contours	
		0.500	0.025
-----	-----	-----	-----
180.0	725.8	57.28	181.04
185.0	725.8	57.28	182.63
190.0	725.8	57.28	184.59
195.0	725.8	57.28	186.93
200.0	725.8	57.28	189.99
205.0	725.8	57.28	191.32
210.0	725.8	57.28	191.32
215.0	725.8	57.28	191.32
220.0	725.8	57.28	185.97
225.0	725.8	55.87	169.68
230.0	725.8	54.88	164.98
235.0	725.8	54.36	164.46
240.0	725.8	53.96	164.07
245.0	725.8	53.67	163.77
250.0	725.8	53.58	163.69
255.0	725.8	53.73	163.84
260.0	725.8	53.96	164.07
265.0	725.8	54.29	164.39
270.0	725.8	54.72	164.82
275.0	725.8	55.09	165.20
280.0	725.8	54.91	165.02
285.0	725.8	54.39	164.49
290.0	725.8	53.90	164.01
295.0	725.8	53.53	163.63
300.0	725.8	53.25	163.35
305.0	725.8	53.06	163.16
310.0	725.8	52.94	163.04
315.0	725.8	52.89	163.00
320.0	725.8	52.92	163.02
325.0	725.8	53.01	163.12
330.0	725.8	53.19	163.29
335.0	725.8	53.44	163.54
340.0	725.8	53.78	163.89
345.0	725.8	54.24	164.34
350.0	725.8	54.82	164.92
355.0	725.8	55.55	165.66