

EXHIBIT 2
MODIFICATION OF DTV CONSTRUCTION PERMIT
BPCDT20011130AEP
MEREDITH CORPORATION
STATION KPHO-DT
PHOENIX, ARIZONA
CH 17, 1000KW-D, 83m AGL

The proposed KPHO DTV facility was evaluated in terms of potential radio frequency (RF) energy exposure at ground level to workers and the general public. The radiation center for the proposed DTV antenna is located 83 meters above ground level. A power level of 1000 kW ERP was utilized in the calculations. A conservative relative field value of 0.13 is assumed for the antenna's downward radiation. The calculated power density at a point 2 meters (6.6 feet) above ground level is 0.086 mW/cm² which is 5.3% of the FCC's recommended limit of 1.64 mW/cm² for the occupational/controlled environment and 26.3% of 0.33 mW/cm² for general public/uncontrolled exposure.

Access to the transmitting site is restricted by fences with locked gates and appropriately marked with warning signs. As this is a multi-user site, there is an agreement among users. In the event that workers or other authorized personnel enter restricted areas or climb the tower, appropriate measures are taken to assure workers safety with respect to radio frequency radiation exposure. Such measures include reducing the average exposure by spreading out the work over a long period of time, wearing "accepted" RFR protective clothing and/or RFR exposure monitors or scheduling work when the stations are at reduced power or shut down. The proposed DTV operation appears to be otherwise categorically excluded from environmental processing.