

Allocation Study**1. Compliance with 47 C.F.R. 73.207**

The proposed facility meets all minimum distance separation requirements with regard to co-channel, first, second, or third adjacent channel stations, and those separated by 53/54 channels, except the license of WGRM-FM Channel 230C3 Greenwood, MS. The proposed facility is 6.3 kilometers short-spaced to WGRM-FM.

This application proposes contour protection for WGRM-FM according to the guidelines of 47 C.F.R. 73.215. Section 47 C.F.R. 73.215(e) states that the minimum separation requirement between a class C3 and a class C3 facility, which are co-channel, is 142 km. Exhibit 30-A shows that WGRM-FM is separated from the proposed facility by 146.73 km.

Therefore, the proposed facility is permitted to use contour protection toward the short-space facilities (See Exhibit 34 for compliance with contour protection requirements).

Educational Media Foundation

5700 West Oaks Boulevard ♦ Rocklin ♦ California ♦ 95765

Exhibit 30-A

Pearl, MS

Proposed Site Spacing

REFERENCE		CLASS = C3	DISPLAY DATES
32 14 06.0 N.			DATA 11-18-15
89 53 46.0 W.	Current	Spacings to 3rd Adj.	SEARCH 11-18-15
----- Channel 230 - 93.9 MHz -----			

Call		Channel	Location		Azi	Dist	FCC	Margin
WJAI	LIC-N	230C3	Pearl	MS	0.0	0.00	153.0	-153.0
WGRM-FM	LIC-N	230C3	Greenwood	MS	349.1	146.73	153.0	-6.3
WHJT	LIC	228A	Clinton	MS	285.7	42.39	42.0	0.39
WHJT	APP-N	228C3	Kearney Park	MS	301.8	44.87	43.0	1.9
WHJT	RSV-A	228C3	Kearney Park	MS	313.5	52.82	43.0	9.8
KGGM	LIC	230C3	Delhi	LA	279.3	167.19	153.0	14.2
WEMX	LIC	231C1	Kentwood	LA	212.9	180.92	144.0	36.9
WZBQ	LIC	231C0	Carrollton	AL	56.5	200.90	163.0	37.9
WKZW	CP	232C2	Sandersville	MS	141.9	100.02	56.0	44.0
WMJY	LIC-Z	229C	Biloxi	MS	149.7	224.15	176.0	48.2
WKZW	LIC-Z	232C2	Sandersville	MS	141.5	113.92	56.0	57.9

RSV-R = reserved - needs protection, RSV-A = allocation.