

TECHNICAL EXHIBIT
CONCERNING HUMAN EXPOSURE TO RF ELECTROMAGNETIC ENERGY
PREPARED FOR
STATION WAKA-DT
SELMA, ALABAMA
CH 42 847 KW-ND 496 M

Technical Statement

The proposed facilities were evaluated in terms of potential radio frequency (RF) energy exposure at ground level to workers and the general public. The radiation center for the proposed DTV antenna is located 504.5 meters above ground level. The maximum DTV ERP is 847 kW (horizontal polarization). A “worst-case” vertical plane relative field value of 0.1 (for angles below 60 degrees downward) is assumed for the antenna's downward radiation (see Figure 2). The calculated power density at a point 2 meters above ground level is less than 0.0130 mW/cm^2 . This is less than 3.0% of the FCC's recommended limit of 0.43 mW/cm^2 for channel 42 for an “uncontrolled” environment. Therefore, based on the responsibility threshold of 5%, the proposal will comply with the RF emission rules.

Access to the transmitting site is restricted by fencing and appropriately marked with RFR warning signs. Furthermore, as this is a multi-user site, a protocol is in effect with the other stations in the event that workers or other authorized personnel enter the restricted area or climb the tower to ensure that appropriate measures will be taken to assure worker safety with respect to radio frequency radiation exposure. Such measures include reducing the average exposure by spreading out the work over a longer period of time, wearing “accepted” RFR protective clothing and/or RFR exposure.

Finally, it is noted that this technical exhibit only addresses the potential for radio frequency electromagnetic field exposure. All other aspects of the

environmental processing analysis have already has been provided to the FCC by the tower owner as part of the tower registration process.

A handwritten signature in black ink, appearing to read 'T. Howell', is centered on the page.

Thomas J. Howell

du Treil, Lundin & Rackley, Inc.

201 Fletcher Avenue

Sarasota, FL 34237-6019

(941) 329-6000

TOM@DLR.COM


March 31, 2008



Date	12 Mar 2008	
Call Letters	WAKA-DT	Channel 42
Location	Selma, AL	
Customer	Bahakel	
Antenna Type	TFU-30GTH 04	

ELEVATION PATTERN

RMS Gain at Main Lobe	27.0 (14.31 dB)	Beam Tilt	0.75 Degrees
RMS Gain at Horizontal	18.7 (12.72 dB)	Frequency	641.00 MHz
Calculated / Measured	Calculated	Drawing #	30G270075-90



Remarks: