

Limon CO K220IK Minor Change
Calvary Chapel of Twin Falls, Inc.
Average Protected F(50-50)= 10.31 km
Omni-directional

REFERENCE
39 22 34.0 N.
103 41 41.0 W.

CH# 220D - 91.9 MHz, Pwr= 0.075 kW, HAAT= 115.6 M, COR= 1809 M
Average Protected F(50-50)= 10.31 km
Omni-directional

DISPLAY DATES
DATA 04-05-18
SEARCH 04-05-18

CH CITY	CALL	TYPE STATE	ANT	AZI <--	DIST FILE #	LAT LNG	PWR(kw) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
220D Limon	K220IK	LIC _V_ CO		0.0 0.0	0.00 BLFT20121120AAW	39 22 34.0 103 41 41.0	0.075 135	41.6 1830	12.6 Calvary Chapel of Twin Fal	-53.4*	-51.9*
220D Limon	K220IK	CP _V_ CO		269.3 89.2	9.16 BPFT20160929ADA	39 22 30.0 103 48 05.0	0.050	34.8 1888	10.4 Calvary Chapel of Twin Fal	-43.3*	-22.5*
222A Hugo	DKKHG	VAC ____ CO		176.8 356.8	30.12	39 06 20.0 103 40 30.0	6.000 100	2.8 1764	28.4 Kona Coast Radio, LLC	15.4	1.1
221C2 Castle Rock	KJMN	LIC NCX CO		270.9 90.1	116.27 BLH20050603AAV	39 23 07.0 105 02 52.0	42.000 163	96.2 2226	65.6 Entravision Holdings, LLC	11.6	39.3
06N-- Manitou Springs	K06BI	LI DHN CO		241.8 61.0	118.85 BLTTV-1446	38 51 49.9 104 54 15.0	0.001 -999	1.6 2012	0.8	2.4R	116.4M

Terrain database is USGS 03 SEC , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
In & Out distances between contours are shown at closest points. Reference zone= West Zone, Co to 3rd adjacent.
All separation margins (if shown) include rounding.
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
"*"affixed to 'IN' or 'OUT' values = site inside restricted contour.