

Exhibit 13

TX Alice

Freespace Interference Study based on Vertical Radiation Pattern Nicom BKG77 Single bay

Depression Angle from Antenna	Antenna Relative Field	ERP Watts	ERP dBk	Distance to Ground from Antenna (m)	Free Space Signal (dBu)	dB Loss for Reflection	Signal Strength at Ground (dBu)	Circular Distance From Tower (m)	Distance to Contour using Free Space (m)	Height of Contour above Ground (m)
90	0.100	0.150	-38.24	74.00	91.30	0	91.30	0.00	8.29	65.71
85	0.180	0.486	-33.13	74.28	96.37	0	96.37	6.47	14.92	59.14
80	0.260	1.014	-29.94	75.14	99.46	0	99.46	13.05	21.55	52.77
75	0.330	1.634	-27.87	76.61	101.37	0	101.37	19.83	27.36	47.58
70	0.400	2.400	-26.20	78.75	102.80	0	102.80	26.93	33.16	42.84
65	0.480	3.456	-24.61	81.65	104.07	0	104.07	34.51	39.79	37.94
60	0.550	4.538	-23.43	85.45	104.85	0	104.85	42.72	45.59	34.51
55	0.610	5.582	-22.53	90.34	105.27	0	105.27	51.82	50.57	32.58
50	0.670	6.734	-21.72	96.60	105.50	0	105.50	62.09	55.54	31.45
45	0.730	7.994	-20.97	104.65	105.55	0	105.55	74.00	60.52	31.21
40	0.790	9.362	-20.29	115.12	105.41	0	105.41	88.19	65.49	31.90
35	0.830	10.334	-19.86	129.02	104.85	0	104.85	105.68	68.81	34.53
30	0.870	11.354	-19.45	148.00	104.07	0	104.07	128.17	72.12	37.94
25	0.910	12.422	-19.06	175.10	103.00	0	103.00	158.69	75.44	42.12
20	0.950	13.538	-18.68	216.36	101.53	0	101.53	203.31	78.75	47.06
15	0.965	13.968	-18.55	285.91	99.25	0	99.25	276.17	80.00	53.30
10	0.980	14.406	-18.41	426.15	95.91	0	95.91	419.67	81.24	59.89
5	0.990	14.702	-18.33	849.05	90.01	0	90.01	845.82	82.07	66.85

Distance to Ground Level assumes flat ground or a site where the site level is above average terrain in all azimuths.

Maximum ERP	15 watts	Max dBu at Ground Level	105.55	Lowest Height of Contour (m)	31.21
Radiation Center AG	74 m			Lowest Height of Contour (ft)	102.39
Radiation Center AG	243 ft.				
Maximum ERP	-18.24 dBk				
Protected dBu	70.31 dBu				
Interfering dBu	110.3 dBu				
Free Space Distance	82.90 m				