

[Exhibit 13]

Non-Interference Compliance

Regarding Facility id 148200

Channel 279

Description of Exhibit 13 Contents

This exhibit demonstrates that the proposed facility complies with contour overlap and interference protection provisions in all of the applicable rule sections and that this application for a construction permit is in full compliance with 47 C.F.R. § 74.1204.

Let it be noted that should any actual real world interference occur, the applicant acknowledges that it will promptly suspend operation of this translator in accordance with 47 C.F.R. § 74.1203.

Page 2 of this exhibit is an explanation of the method used to demonstrate compliance with contour overlap and interference provisions based on 47 C.F.R. § 74.1204(d), which states:

[A]n application otherwise precluded by this section will be accepted if it can be demonstrated that no actual interference will occur due to intervening terrain, lack of population or such other factors as may be applicable.

Page 3 of this exhibit contains the tabulated data from the interference analysis, which shows all stations whose protected contours come within 50 km of the 34 dB μ F(50,10) contour of the proposed translator. These tabulated values were calculated using data from the FCC's CDBS files and 30 arc second terrain data. The column labeled "Adj" shows the number of channels difference between the entry and the proposed translator. The column labeled "Dist" shows the distance in km. The column labeled "Overlap" shows the area of contour overlap in square kilometers.

Page 4 of this exhibit is a portion of a USGS 1:24,000 scale 7.5 minute quadrangle at full scale with the calculated area of interference overlaid. The sheet includes the quadrangle name and measurement scale at the bottom-left corner (note: "Mt" refers to meters). The area of interference was calculated using the free space equation and 120 radials.

Page 5 of this exhibit is an aerial photo of the vicinity surrounding the proposed translator's tower site.

Compliance with 47 C.F.R. § 74.1204(d)

All authorized second and third adjacent stations with which the proposed translator has contour overlap are tabulated below. Column four show the station's signal level at the proposed translator's tower site, and column five gives the minimum value within the entire standard interfering contour of the proposed translator (100 dBμ for most classes, 94 for class B, 97 for class B1). The minimum second or third adjacent F(50,50) contour within the proposed translator's standard interfering contour was used to calculate the proposed translator's actual "worst-case" interfering contour.

Application_id	File Number	Callsign	Contour at Tower	Min. Contour
1554789	BNPFT20130328ARN	K276GD	66.3	66.3
1713698	BNPH20151013AGJ	KYVY	75.9	75.7
193787	BLH19940111KC	KFMU-FM	72.5	72.3

Minimum F(50,50) Contour of Adjacent Station within
Proposed Translator's Standard Interfering Contour **66.3**

FCC 02-244 at Section II.A.5 states that "when demonstrating that 'no actual interference will occur due to . . . other factors,' pursuant to Section 74.1204(d), an applicant may use the undesired-to-desired signal ratio method." The undesired-to-desired ratio for second and third adjacent stations required by § 74.1204(a) is 40 dB. Since the minimum protected contour strength within the proposed translator's standard interference contour is **66.3 dBμ**, this makes the proposed translator's worst-case interfering contour **106.3 dBμ**. By the free-space equation, this contour is calculated to extend a maximum of **122.5 m** from the transmit antenna.

The interfering contour of the proposed translator was calculated for 120 radials and plotted on the pertinent portion of a USGS quadrangle (page 4 of this exhibit). As demonstrated on the quadrangle, there are no populated structures or highways within the area of interference (Note: FCC 02-244 at Section II.A.6 states that USGS quadrangles "have been recognized as acceptable to demonstrate lack of population").


Note: The only structures within the zone of predicted interference are unoccupied communications buildings so in accordance with 47 C.F.R. § 74.1204(d) and the clarification provided by the FCC in the decision *Re: Living Way Ministries* (FCC 02-244), a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Antenna Manufacturer: NIC
Antenna Model: BKG77
CORAGL: 7 m
Maximum ERP: 0.013 kW
Interfering Contour: 106.3 dBμ
Max Int. Contour Distance: 122.5 m

Adjacent Channel Study
For Station K276GD, Facility_id: 148200

Co-channel through third adjacent:

App_id	Fac_id	File_Number	Call	Licensee	Class	City	State	Status	ERP	RCAMSL	Char	Adj	Dist	Overlap
1713698	198724	BNPH-20151013AGJ	KYVY	EDUCATIONAL MEDIA FOUNDAT	C3	YAMPA	CO	CP	8.5	2536	277	2	21.4	0.0776
193787	34434	BLH-19940111KC	KFMU-FM	ALWAYSMOUNTAINTIME, LLC	C3	OAK CREEK	CO	LIC	1.4	2831	281	2	25.2	0.0776
1447071	142165	BLFT-20111003ASF	K281AM	ALWAYSMOUNTAINTIME, LLC	D	VAIL	CO	LIC	0.05	2727	281	2	100	0
220640	57337	BMLH-19960220KC	KSNO-FM	COOL RADIO, LLC	A	SNOWMASS VILL	CO	LIC	6	2798	280	1	135.2	0
580269	43884	BMLH-20010913AAJ	KSPN-FM	ALWAYSMOUNTAINTIME, LLC	A	ASPEN	CO	LIC	3	2876	276	3	137.5	0



Facility id: 148200
Area of Interference

