

Exhibit 15-N-3

Tabulation of Distance to WLVA Daytime Allocation Contours

WLVA	590 kHz	Lic	DA2U	BL951002AD	20060522
VA	LYNCHBURG			5.000 kW	2 Towers
					0 Augmentations
N. Lat:	37 25 39	W. Lon:	79 13 23		20 Measured Cond

Conductivities are from M-3 map unless supplemented by measurements.
All distances are in kilometers (US metric curves)
All radiations are in mV/m at one kilometer

'M*' bearing is supplemented by measurements.
'+-' 10 deg. variance from measured bearing.

Bearing	Radiation	Distance to Contour
-----	-----	-----
0.0-	362.9	12.20
1.0M*	369.3	12.31
5.0+	398.7	12.81
10.0+	444.7	13.55
11.0+	455.1	13.71
15.0	500.4	27.94
15.5-	506.4	20.00
20.0-	564.4	20.00
25.0-	634.7	20.00
25.5M*	642.0	20.00
30.0+	708.7	20.76
35.0+	783.4	21.80
35.5+	790.8	21.90
40.0-	855.7	31.07
45.0-	922.1	32.19
45.5M*	928.3	32.31
50.0+	979.5	33.28
55.0+	1024.9	34.11
55.5+	1028.7	34.18
56.5-	1035.8	27.49
60.0-	1055.7	27.74
65.0-	1070.0	27.91
66.5M*	1070.9	27.92
70.0M*	1066.7	27.87
75.0+	1045.6	27.61
76.5+	1035.9	27.49
80.0+	1007.3	27.13
85.0	953.5	38.32
90.0	886.4	37.03
95.0-	809.0	18.30
100.0-	724.6	17.33
105.0M*	637.1	16.26
110.0+	550.3	15.10
115.0+	468.2	13.91
120.0-	394.8	15.47
125.0M*	334.2	14.18

Exhibit 15-N-3 (cont.)
 Tabulation of Distance to WLVA Daytime Allocation Contours

WLVA	590 kHz	Lic	DA2U	BL951002AD	20060522
VA LYNCHBURG				5.000 kW 2 Towers	0 Augmentations
N. Lat: 37 25 39	W. Lon: 79 13 23				20 Measured Cond

Bearing	Radiation	Distance to Contour 5.000
-----	-----	-----
130.0+	289.9	13.14
135.0-	263.5	12.49
137.0-	257.6	12.33
140.0M*	253.0	12.21
145.0-	253.5	13.60
147.0M*	255.4	13.66
150.0+	259.0	13.76
154.5+	264.3	13.91
155.0+	264.8	13.93
157.0-	266.4	10.37
160.0-	267.9	10.40
164.5M*	267.3	10.39
165.0+	267.1	10.38
170.0+	262.7	10.29
174.5-	257.1	10.17
175.0-	256.6	10.16
180.0M*	252.4	10.07
185.0+	255.5	10.14
190.0+	271.9	10.48
195.0	305.5	21.47
199.0-	345.1	19.75
200.0-	356.7	20.10
205.0-	422.8	21.96
209.0M*	484.0	23.53
210.0+	500.2	23.92
215.0+	584.7	25.86
218.0+	637.1	26.97
219.0-	654.7	16.48
220.0-	672.3	16.70
223.0-	724.6	17.33
225.0-	759.0	17.73
228.0M*	809.0	18.30
230.0+	841.0	18.66
233.0M*	886.4	29.03
235.0+	914.7	29.47
238.0+	953.5	30.05
240.0-	976.8	26.74
243.0-	1007.3	27.13
245.0M*	1024.6	27.35
246.5+	1035.9	27.49
250.0+	1056.1	27.74
255.0M*	1070.1	20.99
256.5M*	1070.9	25.34

Exhibit 15-N-3 (cont.)
 Tabulation of Distance to WLVA Daytime Allocation Contours

WLVA	590 kHz	Lic	DA2U	BL951002AD	20060522
VA LYNCHBURG				5.000 kW 2 Towers	0 Augmentations
N. Lat: 37 25 39		W. Lon: 79 13 23			20 Measured Cond

Bearing	Radiation	Distance to Contour 5.000
-----	-----	-----
260.0+	1066.3	25.29
265.0+	1045.3	25.05
266.5+	1035.8	24.94
270.0	1008.4	39.34
275.0-	957.9	15.84
280.0-	896.5	15.31
285.0M*	827.3	14.69
290.0+	753.6	13.99
295.0+	678.8	13.25
300.0	606.0	30.78
305.0	537.9	28.99
310.0	477.0	27.26
315.0-	425.1	12.09
320.0-	383.1	11.45
325.0M*	351.5	10.94
330.0+	329.5	10.57
335.0+	316.3	10.34
340.0-	310.6	10.24
345.0M*	312.0	10.27
350.0+	320.6	10.42
351.0+	323.2	10.46
355.0-	337.2	11.75