

Exhibit 15-J-3

Tabulation of Distance to WGCV Daytime Allocation Contours

WGCV	620 kHz	Lic	ND2U	BL050218CR	20060522
SC	CAYCE			2.500 kW 1 Tower	0 Augmentations
N. Lat:	33 57 34	W. Lon:	81 02 28		2 Measured Cond

Conductivities are from M-3 map unless supplemented by measurements.
All distances are in kilometers (US metric curves)
All radiations are in mV/m at one kilometer

'M*' bearing is supplemented by measurements.
'+-' 10 deg. variance from measured bearing.

Bearing	Radiation	Distance to Contours	
		0.500	0.250
0.0	468.5	86.60	120.27
5.0	468.5	84.78	118.45
10.0	468.5	82.49	116.16
15.0	468.5	79.62	113.29
17.0-	468.5	63.06	85.28
20.0-	468.5	63.06	85.28
25.0-	468.5	63.06	85.28
27.0M*	468.5	63.06	85.28
30.0+	468.5	63.06	85.28
35.0+	468.5	63.06	85.28
37.0+	468.5	63.06	85.28
40.0-	468.5	51.50	65.79
45.0-	468.5	51.50	65.79
47.0M*	468.5	51.50	65.79
50.0+	468.5	51.50	65.79
55.0+	468.5	51.50	65.79
57.0+	468.5	51.50	65.79
60.0	468.5	73.11	98.03
65.0	468.5	73.11	98.03
70.0	468.5	73.11	98.03
75.0	468.5	73.11	98.03
80.0	468.5	74.26	107.93
85.0	468.5	83.83	117.50
90.0	468.5	88.57	122.25
95.0	468.5	91.85	125.52
100.0	468.5	94.20	127.88
105.0	468.5	95.95	129.62
110.0	468.5	97.26	130.94
115.0	468.5	98.26	131.93
120.0	468.5	99.03	132.70
125.0	468.5	99.63	133.31
130.0	468.5	100.09	133.76
135.0	468.5	100.44	134.11
140.0	468.5	100.69	134.36
145.0	468.5	100.87	134.54
150.0	468.5	100.97	134.64

Exhibit 15-J-3 (cont.)
 Tabulation of Distance to WGCV Daytime Allocation Contours

WGCV	620 kHz	Lic	ND2U	BL050218CR	20060522
SC CAYCE				2.500 kW 1 Tower	0 Augmentations
N. Lat: 33 57 34	W. Lon: 81 02 28				2 Measured Cond

Bearing	Radiation	Distance to Contours	
		0.500	0.250
-----	-----	-----	-----
155.0	468.5	100.87	134.55
160.0	468.5	100.71	134.38
165.0	468.5	100.47	134.15
170.0	468.5	100.14	133.81
175.0	468.5	99.71	133.38
180.0	468.5	99.13	132.80
185.0	468.5	98.39	132.07
190.0	468.5	97.45	131.12
195.0	468.5	96.18	129.85
200.0	468.5	94.20	127.87
205.0	468.5	91.45	125.13
210.0	468.5	87.02	120.69
215.0	468.5	73.11	98.03
220.0	468.5	73.11	98.03
225.0	468.5	73.11	98.03
230.0	468.5	73.11	98.03
235.0	468.5	73.11	98.03
240.0	468.5	73.11	98.03
245.0	468.5	73.11	98.03
250.0	468.5	73.11	102.35
255.0	468.5	74.02	107.69
260.0	468.5	78.09	111.76
265.0	468.5	81.26	114.93
270.0	468.5	83.77	117.45
275.0	468.5	85.77	119.44
280.0	468.5	87.37	121.04
285.0	468.5	88.65	122.33
290.0	468.5	89.66	123.33
295.0	468.5	90.43	124.10
300.0	468.5	91.04	124.71
305.0	468.5	91.46	125.13
310.0	468.5	91.72	124.74
315.0	468.5	91.90	122.73
320.0	468.5	91.97	121.16
325.0	468.5	91.90	119.90
330.0	468.5	91.69	119.04
335.0	468.5	91.34	118.76
340.0	468.5	90.81	118.63
345.0	468.5	90.11	119.18
350.0	468.5	89.20	119.87
355.0	468.5	88.05	120.71