

WQMJ

Channel = 261A

Max ERP = 3 kW

RCAMSL = 246 M

N. Lat = 325827.0

W. Lng = 835202.0

New

Channel = 263D

Max ERP = 0.25 kW

RCAMSL = 257 M

N. Lat = 325105.5

W. Lng = 833911.3

Protected
60 dBuInterfering
100 dBu

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
094.0	003.0000	0112.2	025.5	024.6	000.2500	0131.2	013.0	62.1
095.0	003.0000	0113.3	025.7	025.8	000.2500	0131.2	012.6	62.6
096.0	003.0000	0112.0	025.5	026.0	000.2500	0131.2	012.2	63.3
097.0	003.0000	0111.5	025.5	026.4	000.2500	0131.2	011.7	64.0
098.0	003.0000	0110.2	025.3	026.5	000.2500	0132.2	011.3	64.7
099.0	003.0000	0107.7	025.1	026.0	000.2500	0131.2	010.8	65.5
100.0	003.0000	0106.7	025.0	026.1	000.2500	0131.2	010.3	66.3
101.0	003.0000	0107.1	025.0	027.0	000.2500	0132.2	009.9	67.0
102.0	003.0000	0106.8	025.0	027.5	000.2500	0131.4	009.5	67.8
103.0	003.0000	0107.0	025.0	028.4	000.2500	0131.4	009.1	68.6
104.0	003.0000	0106.5	025.0	028.8	000.2500	0131.8	008.6	69.4
105.0	003.0000	0106.8	025.0	029.7	000.2500	0132.5	008.2	70.3
106.0	003.0000	0106.5	025.0	030.3	000.2500	0132.5	007.8	71.2
107.0	003.0000	0106.0	024.9	030.7	000.2500	0130.1	007.4	72.1
108.0	003.0000	0104.9	024.8	030.6	000.2500	0130.1	006.9	73.2
109.0	003.0000	0104.2	024.7	030.7	000.2500	0130.1	006.5	74.4
110.0	003.0000	0103.9	024.7	031.1	000.2500	0130.1	006.0	75.6
111.0	003.0000	0103.8	024.6	031.9	000.2500	0128.7	005.6	76.7
112.0	003.0000	0103.5	024.6	032.4	000.2500	0128.7	005.2	78.0
113.0	003.0000	0103.6	024.6	033.4	000.2500	0128.9	004.8	79.4
114.0	003.0000	0102.8	024.5	033.2	000.2500	0128.9	004.3	80.8
115.0	003.0000	0101.5	024.4	032.0	000.2500	0128.7	003.9	82.5
116.0	003.0000	0099.9	024.2	029.8	000.2500	0132.5	003.4	84.5
117.0	003.0000	0098.1	024.0	026.3	000.2500	0131.2	003.0	86.3
118.0	003.0000	0096.6	023.8	022.4	000.2500	0132.6	002.6	88.5
119.0	003.0000	0095.3	023.7	017.4	000.2500	0135.8	002.2	90.9
120.0	003.0000	0094.4	023.6	011.4	000.2500	0132.5	001.9	93.1
121.0	003.0000	0094.0	023.5	004.5	000.2500	0128.4	001.5	97.4
122.0	003.0000	0093.1	023.4	351.1	000.2500	0124.7	001.2	99.2
123.0	003.0000	0091.1	023.2	328.0	000.2500	0140.0	001.2	99.5
124.0	003.0000	0089.0	022.9	307.1	000.2500	0118.5	001.3	98.5
125.0	003.0000	0089.0	022.9	290.1	000.2500	0114.7	001.4	98.2
126.0	003.0000	0090.6	023.1	271.2	000.2500	0127.5	001.4	98.2
127.0	003.0000	0091.6	023.2	256.0	000.2500	0130.5	001.5	95.2
128.0	003.0000	0091.5	023.2	248.5	000.2500	0123.9	001.9	92.7
129.0	003.0000	0091.1	023.2	244.3	000.2500	0127.6	002.3	90.4

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)		Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
130.0	003.0000	0090.4	023.1		242.5	000.2500	0129.9	002.7	88.1
131.0	003.0000	0090.0	023.0		240.5	000.2500	0133.4	003.1	86.2
132.0	003.0000	0090.4	023.1		237.6	000.2500	0134.9	003.4	84.7
133.0	003.0000	0091.7	023.2		233.5	000.2500	0138.4	003.8	83.4
134.0	003.0000	0093.8	023.5		229.1	000.2500	0140.6	004.2	82.1
135.0	003.0000	0094.5	023.6		227.6	000.2500	0142.7	004.6	80.8
136.0	003.0000	0094.5	023.6		227.4	000.2500	0145.0	005.0	79.6
137.0	003.0000	0094.4	023.6		227.5	000.2500	0145.0	005.4	78.4
138.0	003.0000	0094.7	023.6		227.1	000.2500	0145.0	005.8	77.2
139.0	003.0000	0094.3	023.6		227.6	000.2500	0142.7	006.2	75.9
140.0	003.0000	0094.6	023.6		227.4	000.2500	0145.0	006.6	74.9
141.0	003.0000	0095.1	023.6		227.1	000.2500	0145.0	007.0	73.8
142.0	003.0000	0095.7	023.7		226.8	000.2500	0145.0	007.5	72.8
143.0	003.0000	0095.2	023.7		227.6	000.2500	0142.7	007.9	71.7
144.0	003.0000	0094.3	023.6		228.6	000.2500	0140.6	008.3	70.8
145.0	003.0000	0093.5	023.4		229.5	000.2500	0139.5	008.7	69.9
146.0	003.0000	0093.7	023.5		229.6	000.2500	0139.5	009.1	69.1
147.0	003.0000	0095.1	023.6		228.9	000.2500	0140.6	009.5	68.4
148.0	003.0000	0096.6	023.8		228.2	000.2500	0142.7	009.9	67.7
149.0	003.0000	0097.7	024.0		227.9	000.2500	0142.7	010.4	67.0
150.0	003.0000	0097.7	024.0		228.4	000.2500	0142.7	010.8	66.3
151.0	003.0000	0097.3	023.9		229.0	000.2500	0140.6	011.2	65.5
152.0	003.0000	0096.3	023.8		230.1	000.2500	0139.5	011.6	64.8
153.0	003.0000	0096.3	023.8		230.5	000.2500	0139.5	012.0	64.2
154.0	003.0000	0096.3	023.8		230.9	000.2500	0138.5	012.4	63.5