

BENJAMIN F. DAWSON III, PE
THOMAS M. ECKELS, PE
STEPHEN S. LOCKWOOD, PE
DAVID J. PINION, PE
ERIK C. SWANSON, PE

THOMAS S. GORTON, PE
MICHAEL H. MEHIGAN, PE

HATFIELD & DAWSON
CONSULTING ELECTRICAL ENGINEERS
9500 GREENWOOD AVE. N.
SEATTLE, WASHINGTON 98103

TELEPHONE (206) 783-9151
FACSIMILE (206) 789-9834
E-MAIL hatdaw@hatdaw.com

JAMES B. HATFIELD, PE
CONSULTANT

MAURY L. HATFIELD, PE
(1942-2009)

PAUL W. LEONARD, PE
(1925-2011)

**Engineering Statement
Minor Modification of Construction Permit for WFXW-LD
Channel 17 at The Dalles, OR
January 2013**

This Engineering Statement has been prepared on behalf of Commonwealth Broadcasting Group, permittee of digital LPTV station WFXW-LD at Cleveland, MS. This material has been prepared in connection with an application for minor modification of construction permit.

I. Allocation Study

The WFXW-LD construction permit specifies a maximum lobe ERP of 15 kW (938 watts at pattern minimum) at a radiation center height of 603 meters above ground. The instant application proposes to instead mount an antenna at 55 meters AGL with an ERP of 300 watts. Thus the proposed facility will have less of an interference effect upon other stations that would the currently-authorized facility.

II. RF Exposure Study

OET Bulletin 65 *Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields* (Edition 97-01) states in part that:

When performing an evaluation for compliance with the FCC's RF guidelines all significant contributors to the ambient RF environment should be considered. . . For purposes of such consideration, significance can be taken to mean any transmitter producing more than 5% of the applicable exposure limit (in terms of power density or the square of the electric or magnetic field strength) at accessible locations.

As will be demonstrated below, the proposed operation of WFXW-LD will produce less than 5% of the applicable exposure limit for both controlled and uncontrolled environments. Thus, the proposed facility is categorically excluded from the requirement of further study. Therefore, pursuant to §1.1307(b)(3) of the Commission's Rules no calculations are required for the other FM and TV facilities in the vicinity, and precise calculations are made only with regard to the levels from this proposal.

The power density calculations shown below were made using the techniques outlined in OET Bulletin No. 65. "Ground level" calculations in this report have been made at a reference height of 2 meters above ground to provide a worst-case estimate of exposure for persons standing on the ground in the vicinity of the tower. The equation shown below was used to calculate the ground level power density figures from each antenna.

$$S(\mu W / cm^2) = \frac{33.40981 \times AdjERP(Watts)}{D^2}$$

Where: *AdjERP(Watts)* is the maximum lobe effective radiated power times the element pattern factor times the array pattern factor.

D is the distance in meters from the center of radiation to the calculation point.

Power density levels produced by the proposed facility were calculated for an elevation of 2 meters above ground (53 meters below the antenna radiation center), assuming that the antenna will radiate 100% power straight down. Under this "worst case" assumption,, the highest calculated power density from the proposed antenna alone occurs at the base of the antenna support structure. At this point the power density is calculated to be 3.6 $\mu W/cm^2$, which is 1.1% of 325 $\mu W/cm^2$ (the FCC maximum for uncontrolled environments at the Channel 17 frequency).

Hatfield & Dawson Consulting Engineers

These calculations show that the maximum calculated power density produced at two meters above ground level by the proposed operation alone is less than 5% of the applicable FCC exposure limit at all locations between 1 and 1000 meters from the base of the antenna support structure. Section 1.1307(b)(3) of the Commission's Rules excludes applications for new facilities or modifications to existing facilities from the requirement of preparing an environmental assessment when the calculated emissions from the applicants proposed facility are predicted to be less than 5% of the applicable FCC exposure limit. Therefore, the proposed facility is in compliance with Section 1.1301 *et seq* and no further analysis of RF exposure at this site is required in this application.

Pursuant to OET Bulletin No. 65, all station personnel and contractors are required to follow appropriate safety procedures before any work is commenced on the antenna tower, including reduction in power or discontinuance of operation before any maintenance work is undertaken. The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency radiation in excess of FCC guidelines.

January 22, 2013

Erik C. Swanson, P.E.