

K201IP Sterling, CO Minor Tower Change  
 Calvary Chapel of Twin Falls, Inc.  
 Average Protected F(50-50)= 9.52 km  
 Omni-directional

REFERENCE  
 40 31 57.0 N.  
 103 07 22.0 W.

CH# 201D - 88.1 MHz, Pwr= 0.092 kW, HAAT= 88.5 M, COR= 1394 M  
 Average Protected F(50-50)= 9.52 km  
 Omni-directional

DISPLAY DATES  
 DATA 07-02-18  
 SEARCH 07-02-18

CH CITY	CALL	TYPE STATE	ANT	AZI <--	DIST FILE #	LAT LNG	PWR(kw) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
201D Sterling	K201IP	LIC _V_ CO		85.8 265.8	6.35 BLFT20121105AKX	40 32 12.0 103 02 52.0	0.075 120		1446	---Reference--- Calvary Chapel of Twin Fal	
202D Yuma	K202EK	LIC _C_ CO		148.8 329.0	50.58 BLFT20130603BED	40 08 35.0 102 48 51.0	0.113 117	15.2 1398	10.7 Community Radio For Northe	29.9	31.8

Terrain database is USGS 03 SEC , R= 73.215 qualifying spacings or FCC minimum spacings in KM, M= Margin in KM  
 In & Out distances between contours are shown at closest points. Reference zone= West Zone, Co to 3rd adjacent.  
 All separation margins (if shown) include rounding.  
 Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, \_= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)  
 "\*"affixed to 'IN' or 'OUT' values = site inside restricted contour.