

EXHIBIT 14

TO COMPLY WITH TOWER LOADING AND SPACE REQUIREMENTS THE ANTENNA WAS MODIFIED TO 12 BAYS RATHER THAN 16. THE NEW ANTENNA HAS THE SAME PATTERN, CONTOUR, AND RELATIVE FIELD TAB DATA. ALSO 3' LINE WAS USED. THE TPO WAS SLIGHTLY REDUCED (FROM .8 KW TO .71 KW) TO MAINTAIN THE SAME ERP AS THE ORIGINAL CONSTRUCTION PERMIT.

Original CP Antenna Relative Field Tabulation:

Degrees	Value										
0	1	10	1	20	0.98	30	0.95	40	0.91	50	0.87
60	0.82	70	0.76	80	0.71	90	0.66	100	0.63	110	0.61
120	0.6	130	0.6	140	0.62	150	0.64	160	0.66	170	0.67
180	0.67	190	0.67	200	0.66	210	0.64	220	0.62	230	0.6
240	0.6	250	0.61	260	0.63	270	0.66	280	0.71	290	0.76
300	0.82	310	0.87	320	0.91	330	0.95	340	0.98	350	1

Revised Antenna Relative Field Tabulation with new antenna:

Degrees	Value										
0	1	10	1	20	0.98	30	0.95	40	0.91	50	0.87
60	0.82	70	0.76	80	0.71	90	0.66	100	0.63	110	0.61
120	0.6	130	0.6	140	0.62	150	0.64	160	0.66	170	0.67
180	0.67	190	0.67	200	0.66	210	0.64	220	0.62	230	0.6
240	0.6	250	0.61	260	0.63	270	0.66	280	0.71	290	0.76
300	0.82	310	0.87	320	0.91	330	0.95	340	0.98	350	1