

## K216BB Elko, Spring Creek, NV

Faith Communications Corp.

REFERENCE  
40 48 49.8 N.  
115 41 56.3 W.

CH# 216D - 91.1 MHz, Pwr= 0.046 kw, HAAT= 298.0 M, COR= 1978.4 M  
Average Protected F(50-50)= 14.67 km  
Omni-directional

DISPLAY DATES  
DATA 05-16-12  
SEARCH 05-16-12

CH CITY	CALL	TYPE STATE	ANT ---	AZI ---	DIST FILE #	LAT LNG	PWR(kw) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
214A Spring Creek	KNVQ	LIC _CX NV		189.4 9.4	0.24 BLED20101005ACF	40 48 42.0 115 41 58.0	0.500 287	1.6 1968	27.8 Western Inspirational Broa	-16.6*	-28.0*
218A Elko	KNCC	LIC _CX NV		33.2 213.3	10.75 BMLD20110610ACM	40 53 41.0 115 37 44.0	0.054 622	0.5 2297	20.2 Board Of Regents Of The Ne	1.6	-9.9*
06 D Elko	K06MK-D	LI D_N NV		347.5 167.5	0.82 BLDTV20111123AAA	40 49 16.0 115 42 04.0	0.100 428	6.0 2001	4.2 Elko Television District	10.2R	-9.4M
06 D Ryndon	K06NY-D	LI D_Y NV		23.2 203.3	18.28 BLDTV20111219ABC	40 57 54.0 115 36 47.0	0.062 24	4.8 1586	1.9 Elko Television District	6.7R	11.6M
217C1 Jackpot	KBSJ	LIC _CY NV		33.3 213.9	129.72 BLED20020403AAQ	41 47 08.0 114 50 22.0	3.900 751	91.2 2655	61.6 Idaho State Board Of Educa	29.9	56.0

Terrain database is NGDC 30 SEC, R= 73.215 qualifying spacings or FCC minimum spacings in KM, M= Margin in KM  
Contour distances are on direct line to and from reference station. Reference zone= , Co to 3rd adjacent.  
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, \_= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)  
"\*"affixed to 'IN' or 'OUT' values = site inside protected contour.