

Non-Interference Compliance

Regarding Facility id 151474

Channel 282

Description of Exhibit 12 Contents

This exhibit demonstrates that the proposed facility complies with contour overlap and interference protection provisions in all of the applicable rule sections and that this application for a construction permit is in full compliance with 47 C.F.R. § 74.1204.

Let it be noted that should any actual real world interference occur, the applicant acknowledges that it will promptly suspend operation of this translator in accordance with 47 C.F.R. § 74.1203.

Page 2 of this exhibit is an explanation of the method used to demonstrate compliance with contour overlap and interference provisions based on 47 C.F.R. § 74.1204(d), which states:

[A]n application otherwise precluded by this section will be accepted if it can be demonstrated that no actual interference will occur due to intervening terrain, lack of population or such other factors as may be applicable.

Page 3 of this exhibit contains the tabulated data from the interference analysis, which shows all stations whose protected contours come within 50 km of the 34 dBμ F(50,10) contour of the proposed translator. These tabulated values were calculated using data from the FCC's CDBS files and 30 arc second terrain data. The column labeled "Adj" shows the number of channels difference between the entry and the proposed translator. The column labeled "Dist" shows the distance in km. The column labeled "Overlap" shows the area of contour overlap in square kilometers.

Page 4 of this exhibit is a portion of a USGS 1:24,000 scale 7.5 minute quadrangle at full scale with the calculated area of interference overlaid. The sheet includes the quadrangle name and measurement scale at the bottom-left corner (note: "Mt" refers to meters). The area of interference was calculated using the free space equation and 120 radials.

Compliance with 47 C.F.R. § 74.1204(d)

All authorized second and third adjacent stations with which the proposed translator has contour overlap are tabulated below. Column four show the station's signal level at the proposed translator's tower site, and column five gives the minimum value within the entire standard interfering contour of the proposed translator (100 dBμ for most classes, 94 for class B, 97 for class B1). The minimum second or third adjacent F(50,50) contour within the proposed translator's standard interfering contour was used to calculate the proposed translator's actual "worst-case" interfering contour.

Application_id	File Number	Callsign	Contour at Tower	Min. Contour
1105669	BLH20051227AGO	WTYB	83.8	83.8
Minimum F(50,50) Contour of Adjacent Station within Proposed Translator's Standard Interfering Contour				83.8

FCC 02-244 at Section II.A.5 states that "when demonstrating that 'no actual interference will occur due to . . . other factors,' pursuant to Section 74.1204(d), an applicant may use the undesired-to-desired signal ratio method." The undesired-to-desired ratio for second and third adjacent stations required by § 74.1204(a) is 40 dB. Since the minimum protected contour strength within the proposed translator's standard interference contour is **83.8 dBμ**, this makes the proposed translator's worst-case interfering contour **123.8 dBμ**. By the free-space equation, this contour is calculated to extend a maximum of **23.5 m** from the transmit antenna.

The interfering contour of the proposed translator was calculated for 120 radials and plotted on the pertinent portion of a USGS quadrangle (page 4 of this exhibit). As demonstrated on the quadrangle, there are no populated structures or highways within the area of interference (Note: FCC 02-244 at Section II.A.6 states that USGS quadrangles "have been recognized as acceptable to demonstrate lack of population"). Hence, in accordance with 47 C.F.R. § 74.1204(d) and the clarification provided by the FCC in the decision *Re: Living Way Ministries* (FCC 02-244), a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Antenna Manufacturer: NIC
Antenna Model: BKG77
CORAGL: 94 m
Maximum ERP: 0.027 kW
Interfering Contour: 123.8 dBμ
Max Int. Contour Distance: 23.5 m

Adjacent Channel Study
For Station W282AR, Facility_id: 151474

Co-channel through third adjacent:

Application_id	Facility_id	Prefix	ARN	Call	Licensee	Class	City	State	Status	ERP	RCAMSL	Channel	Adj	Dist	Overlap
1155686	14069	BXLH	20061020ACS	WTYB	CUMULUS LICENSING LLC	C2	TYBEE ISLAND	GA	LIC	15	106	280	2	12.3	0.1611
1105669	14069	BLH	20051227AGO	WTYB	CUMULUS LICENSING LLC	C2	TYBEE ISLAND	GA	LIC	50	106	280	2	12.3	0.1611
1193126	153405	BMPFT	20070628ACY	W282AT	EDGEWATER BROADCASTING INC.	D	HILTON HEAD ISLAND	SC	CP MOD	0.082	20	282	0	38.1	0
200700	40705	BLH	19940705KC	WWJN	ADVENTURE COMMUNICATIONS, INC.	C3	RIDGELAND	SC	LIC	16	128	285	3	47.1	0
192875	7816	BLH	19931210KC	WTHG	BULLIE BROADCASTING CORPORATION	C3	HINESVILLE	GA	LIC	12	165	284	2	60.4	0
1203078	151458	BPFT	20070904ABL	W279AR	EDGEWATER BROADCASTING INC.	D	JESUP	GA	APP	0.012	53	279	3	86	0
1180811	151458	BLFT	20070409AAA	W279AR	EDGEWATER BROADCASTING INC.	D	JESUP	GA	LIC	0.005	41	279	3	86	0
289461	73247	BLH	7748	WBMZ		A	METTER	GA	LIC	3	160	285	3	92.5	0
204164	73247	BMLH	19941118KF	WBMZ	WM. JIMMY PAGE, TR/AS RADIO METTER	A	METTER	GA	APP	6	160	279	3	92.5	0
285872	73932	BLH	19990603KI	WRBX	WRBX / WTNL, INC.	A	REIDSVILLE	GA	LIC	4.9	158	281	1	92.7	0
200765	472	BLH	19940706KB	WRJY	ADMIRAL BROADCASTING, INC.	A	BRUNSWICK	GA	LIC	4.2	120	281	1	101.4	0



Facility id: 151474;
Area of Interference;

Feet	Meters
1	.304
2	.609
3	.914
4	1.219
5	1.524
6	1.828
7	2.133
8	2.438
9	2.743
10	3.048

To convert feet to
meters multiply by .3048

To convert meters
to feet multiply by 3.2808