

Distance to FM Contour

Study: 4 Eutaw Temp Ch289 54dBu  
Site: Eutaw Xltr site

Latitude: N32-55-19.40  
Longitude: W87-49-08.00

True Radial Bearing (Degrees)	Average Elevation (meters)	Radiation Center Height Above Average Terrain (meters)	Effective Radiated Power (KW)	(dBKW)	Distance to Contour 54.0 dBu F(50,10) (km)
0.00	75.05	32.35	0.001	-30.00	2.63
1.00	73.98	33.42	0.001	-30.00	2.67
2.00	73.93	33.47	0.001	-30.00	2.67
3.00	72.98	34.42	0.001	-30.00	2.70
4.00	72.51	34.89	0.001	-30.00	2.72
5.00	71.49	35.91	0.001	-30.00	2.76
6.00	70.45	36.95	0.001	-30.00	2.80
7.00	69.78	37.62	0.001	-30.00	2.82
8.00	68.24	39.16	0.001	-30.00	2.87
9.00	66.68	40.72	0.001	-30.00	2.93
10.00	64.44	42.96	0.001	-30.00	3.00
11.00	62.05	45.35	0.001	-30.00	3.10
12.00	63.02	44.38	0.001	-30.00	3.06
13.00	63.13	44.27	0.001	-30.00	3.05
14.00	62.90	44.50	0.001	-30.00	3.06
15.00	62.81	44.59	0.001	-30.00	3.07
16.00	63.17	44.23	0.001	-30.00	3.05
17.00	62.18	45.22	0.001	-30.00	3.09
18.00	61.35	46.05	0.001	-30.00	3.13
19.00	61.19	46.21	0.001	-30.00	3.13
20.00	60.49	46.91	0.001	-30.00	3.16
21.00	59.70	47.70	0.001	-30.00	3.19
22.00	59.27	48.13	0.001	-30.00	3.20
23.00	58.86	48.54	0.001	-30.00	3.22
24.00	58.41	48.99	0.001	-30.00	3.24
25.00	57.83	49.57	0.001	-30.00	3.26
26.00	56.19	51.21	0.001	-30.00	3.32
27.00	54.71	52.69	0.001	-30.00	3.36
28.00	54.33	53.07	0.001	-30.00	3.38
29.00	55.49	51.91	0.001	-30.00	3.34
30.00	56.99	50.41	0.001	-30.00	3.29
31.00	58.78	48.62	0.001	-30.00	3.22
32.00	60.19	47.21	0.001	-30.00	3.17
33.00	63.62	43.78	0.001	-30.00	3.03
34.00	64.86	42.54	0.001	-30.00	2.99
35.00	63.03	44.37	0.001	-30.00	3.06
36.00	62.15	45.25	0.001	-30.00	3.09
37.00	60.19	47.21	0.001	-30.00	3.17
38.00	60.26	47.14	0.001	-30.00	3.17
39.00	59.87	47.53	0.001	-30.00	3.18

True Radial Bearing (Degrees)	Average Elevation (meters)	Radiation Center Height Above Average Terrain (meters)	Effective Radiated Power (KW)	Distance to Contour 54.0 dBu F(50,10) (dBKW) (km)
40.00	57.87	49.53	0.001	-30.00      3.26
41.00	56.38	51.02	0.001	-30.00      3.31
41.60	54.49	52.91	0.001	-30.00      3.37
42.00	53.51	53.89	0.001	-30.00      3.40
43.00	51.33	56.07	0.001	-30.00      3.47
44.00	49.28	58.12	0.001	-30.00      3.53
45.00	48.61	58.79	0.001	-30.00      3.55
46.00	47.41	59.99	0.001	-30.00      3.58
47.00	46.17	61.23	0.001	-30.00      3.62
48.00	43.91	63.49	0.001	-30.00      3.68
49.00	42.97	64.43	0.001	-30.00      3.70
50.00	41.67	65.73	0.001	-30.00      3.73
51.00	41.13	66.27	0.001	-30.00      3.75
52.00	41.24	66.16	0.001	-30.00      3.75
53.00	41.10	66.30	0.001	-30.00      3.75
54.00	41.11	66.29	0.001	-30.00      3.75
55.00	41.62	65.78	0.001	-30.00      3.74
56.00	41.98	65.42	0.001	-30.00      3.73
57.00	42.36	65.04	0.001	-30.00      3.72
58.00	42.11	65.29	0.001	-30.00      3.72
59.00	41.74	65.66	0.001	-30.00      3.73
60.00	41.61	65.79	0.001	-30.00      3.74
61.00	41.37	66.03	0.001	-30.00      3.74
62.00	41.08	66.32	0.001	-30.00      3.75
63.00	41.13	66.27	0.001	-30.00      3.75
64.00	40.89	66.51	0.001	-30.00      3.75
65.00	40.36	67.04	0.001	-30.00      3.77
66.00	39.94	67.46	0.001	-30.00      3.78
67.00	39.61	67.79	0.001	-30.00      3.79
68.00	39.45	67.95	0.001	-30.00      3.79
69.00	39.51	67.89	0.001	-30.00      3.79
70.00	39.25	68.15	0.001	-30.00      3.80
71.00	39.00	68.40	0.001	-30.00      3.80
72.00	38.22	69.18	0.001	-30.00      3.82
73.00	36.99	70.41	0.001	-30.00      3.85
74.00	35.91	71.49	0.001	-30.00      3.88
75.00	35.26	72.14	0.001	-30.00      3.90
76.00	35.46	71.94	0.001	-30.00      3.89
77.00	35.89	71.51	0.001	-30.00      3.88
78.00	36.25	71.15	0.001	-30.00      3.87
79.00	36.38	71.02	0.001	-30.00      3.87
80.00	36.53	70.87	0.001	-30.00      3.87
81.00	36.66	70.74	0.001	-30.00      3.86
82.00	36.99	70.41	0.001	-30.00      3.85
83.00	37.86	69.54	0.001	-30.00      3.83
84.00	38.79	68.61	0.001	-30.00      3.81

Exhibit 11  
Proposed Contour using Three Second Terrain Data

Page 3 of 9  
September 05, 2009

True Radial Bearing (Degrees)	Average Elevation (meters)	Radiation Center Height Above Average Terrain (meters)	Effective Radiated Power (KW)	(dBKW)	Distance to Contour 54.0 dBu F(50,10) (km)
85.00	40.01	67.39	0.001	-30.00	3.78
86.00	41.16	66.24	0.001	-30.00	3.75
87.00	41.76	65.64	0.001	-30.00	3.73
88.00	42.81	64.59	0.001	-30.00	3.71
89.00	43.63	63.77	0.001	-30.00	3.68
90.00	43.44	63.96	0.001	-30.00	3.69
91.00	43.17	64.23	0.001	-30.00	3.70
92.00	43.44	63.96	0.001	-30.00	3.69
93.00	43.55	63.85	0.001	-30.00	3.69
94.00	43.90	63.50	0.001	-30.00	3.68
95.00	45.38	62.02	0.001	-30.00	3.64
96.00	46.34	61.06	0.001	-30.00	3.61
97.00	46.85	60.55	0.001	-30.00	3.60
98.00	47.95	59.45	0.001	-30.00	3.57
99.00	49.20	58.20	0.001	-30.00	3.53
100.00	49.31	58.09	0.001	-30.00	3.53
101.00	48.79	58.61	0.001	-30.00	3.55
102.00	48.14	59.26	0.001	-30.00	3.56
103.00	47.19	60.21	0.001	-30.00	3.59
104.00	46.45	60.95	0.001	-30.00	3.61
105.00	47.13	60.27	0.001	-30.00	3.59
106.00	46.75	60.65	0.001	-30.00	3.60
107.00	45.44	61.96	0.001	-30.00	3.64
108.00	43.31	64.09	0.001	-30.00	3.69
109.00	39.60	67.80	0.001	-30.00	3.79
110.00	38.49	68.91	0.001	-30.00	3.82
111.00	37.51	69.89	0.001	-30.00	3.84
112.00	36.85	70.55	0.001	-30.00	3.86
113.00	38.04	69.36	0.001	-30.00	3.83
114.00	41.00	66.40	0.001	-30.00	3.75
115.00	42.88	64.52	0.001	-30.00	3.70
116.00	44.29	63.11	0.001	-30.00	3.67
117.00	44.53	62.87	0.001	-30.00	3.66
118.00	46.02	61.38	0.001	-30.00	3.62
119.00	46.90	60.50	0.001	-30.00	3.60
120.00	47.71	59.69	0.001	-30.00	3.58
121.00	48.69	58.71	0.001	-30.00	3.55
122.00	48.38	59.02	0.001	-30.00	3.56
123.00	48.22	59.18	0.001	-30.00	3.56
124.00	48.56	58.84	0.001	-30.00	3.55
125.00	50.63	56.77	0.001	-30.00	3.49
126.00	51.20	56.20	0.001	-30.00	3.47
127.00	50.37	57.03	0.001	-30.00	3.50
128.00	50.28	57.12	0.001	-30.00	3.50
129.00	48.88	58.52	0.001	-30.00	3.54
130.00	48.56	58.84	0.001	-30.00	3.55

Exhibit 11  
Proposed Contour using Three Second Terrain Data

Page 4 of 9  
September 05, 2009

True Radial Bearing (Degrees)	Average Elevation (meters)	Radiation Center Height Above Average Terrain (meters)	Effective Radiated Power (KW)	(dBKW)	Distance to Contour 54.0 dBu F(50,10) (km)
131.00	48.92	58.48	0.001	-30.00	3.54
132.00	48.67	58.73	0.001	-30.00	3.55
133.00	47.18	60.22	0.001	-30.00	3.59
134.00	47.68	59.72	0.001	-30.00	3.58
135.00	47.65	59.75	0.001	-30.00	3.58
136.00	46.40	61.00	0.001	-30.00	3.61
137.00	44.23	63.17	0.001	-30.00	3.67
138.00	41.00	66.40	0.001	-30.00	3.75
139.00	38.23	69.17	0.001	-30.00	3.82
140.00	37.05	70.35	0.001	-30.00	3.85
141.00	36.17	71.23	0.001	-30.00	3.87
142.00	35.82	71.58	0.001	-30.00	3.88
143.00	36.48	70.92	0.001	-30.00	3.87
144.00	36.81	70.59	0.001	-30.00	3.86
145.00	37.16	70.24	0.001	-30.00	3.85
146.00	38.24	69.16	0.001	-30.00	3.82
147.00	39.13	68.27	0.001	-30.00	3.80
148.00	39.61	67.79	0.001	-30.00	3.79
149.00	39.84	67.56	0.001	-30.00	3.78
150.00	39.95	67.45	0.001	-30.00	3.78
151.00	40.00	67.40	0.001	-30.00	3.78
152.00	39.38	68.02	0.001	-30.00	3.79
153.00	39.28	68.12	0.001	-30.00	3.80
154.00	38.16	69.24	0.001	-30.00	3.82
155.00	37.80	69.60	0.001	-30.00	3.83
156.00	37.63	69.77	0.001	-30.00	3.84
157.00	36.99	70.41	0.001	-30.00	3.85
158.00	36.18	71.22	0.001	-30.00	3.87
159.00	35.09	72.31	0.001	-30.00	3.90
160.00	35.31	72.09	0.001	-30.00	3.90
161.00	35.91	71.49	0.001	-30.00	3.88
162.00	36.10	71.30	0.001	-30.00	3.88
163.00	36.05	71.35	0.001	-30.00	3.88
164.00	35.43	71.97	0.001	-30.00	3.89
165.00	34.50	72.90	0.001	-30.00	3.92
166.00	33.73	73.67	0.001	-30.00	3.94
167.00	33.16	74.24	0.001	-30.00	3.95
168.00	32.74	74.66	0.001	-30.00	3.96
169.00	32.34	75.06	0.001	-30.00	3.97
170.00	31.82	75.58	0.001	-30.00	3.98
171.00	31.36	76.04	0.001	-30.00	3.99
172.00	31.02	76.38	0.001	-30.00	4.00
173.00	30.69	76.71	0.001	-30.00	4.01
174.00	30.41	76.99	0.001	-30.00	4.02
175.00	30.15	77.25	0.001	-30.00	4.03
176.00	29.83	77.57	0.001	-30.00	4.03

Exhibit 11  
Proposed Contour using Three Second Terrain Data

Page 5 of 9  
September 05, 2009

True Radial Bearing (Degrees)	Average Elevation (meters)	Radiation Center Height Above Average Terrain (meters)	Effective Radiated Power (KW)	(dBKW)	Distance to Contour 54.0 dBu F(50,10) (km)
177.00	29.19	78.21	0.001	-30.00	4.05
178.00	27.92	79.48	0.001	-30.00	4.09
179.00	26.85	80.55	0.001	-30.00	4.11
180.00	26.63	80.77	0.001	-30.00	4.12
181.00	26.70	80.70	0.001	-30.00	4.12
182.00	27.36	80.04	0.001	-30.00	4.10
183.00	28.17	79.23	0.001	-30.00	4.08
184.00	28.90	78.50	0.001	-30.00	4.06
185.00	30.08	77.32	0.001	-30.00	4.03
186.00	31.37	76.03	0.001	-30.00	3.99
187.00	32.96	74.44	0.001	-30.00	3.95
188.00	33.98	73.42	0.001	-30.00	3.93
189.00	35.18	72.22	0.001	-30.00	3.90
190.00	37.75	69.65	0.001	-30.00	3.83
191.00	39.56	67.84	0.001	-30.00	3.79
192.00	41.36	66.04	0.001	-30.00	3.74
193.00	42.81	64.59	0.001	-30.00	3.71
194.00	42.99	64.41	0.001	-30.00	3.70
195.00	42.82	64.58	0.001	-30.00	3.71
196.00	44.17	63.23	0.001	-30.00	3.67
197.00	45.35	62.05	0.001	-30.00	3.64
198.00	46.23	61.17	0.001	-30.00	3.62
199.00	47.10	60.30	0.001	-30.00	3.59
200.00	46.93	60.47	0.001	-30.00	3.60
201.00	47.08	60.32	0.001	-30.00	3.59
202.00	47.38	60.02	0.001	-30.00	3.59
203.00	47.49	59.91	0.001	-30.00	3.58
204.00	47.59	59.81	0.001	-30.00	3.58
205.00	48.27	59.13	0.001	-30.00	3.56
206.00	48.87	58.53	0.001	-30.00	3.54
207.00	49.36	58.04	0.001	-30.00	3.53
208.00	49.98	57.42	0.001	-30.00	3.51
209.00	50.69	56.71	0.001	-30.00	3.49
210.00	51.32	56.08	0.001	-30.00	3.47
211.00	52.13	55.27	0.001	-30.00	3.45
212.00	53.44	53.96	0.001	-30.00	3.41
213.00	54.70	52.70	0.001	-30.00	3.37
214.00	55.43	51.97	0.001	-30.00	3.34
215.00	55.72	51.68	0.001	-30.00	3.33
216.00	56.58	50.82	0.001	-30.00	3.30
217.00	56.93	50.47	0.001	-30.00	3.29
218.00	56.28	51.12	0.001	-30.00	3.31
219.00	56.77	50.63	0.001	-30.00	3.29
220.00	58.30	49.10	0.001	-30.00	3.24
221.00	59.38	48.02	0.001	-30.00	3.20
222.00	60.37	47.03	0.001	-30.00	3.16

Exhibit 11  
Proposed Contour using Three Second Terrain Data

Page 6 of 9  
September 05, 2009

True Radial Bearing (Degrees)	Average Elevation (meters)	Radiation Center Height Above Average Terrain (meters)	Effective Radiated Power (KW)	(dBKW)	Distance to Contour 54.0 dBu F(50,10) (km)
223.00	61.37	46.03	0.001	-30.00	3.12
224.00	62.25	45.15	0.001	-30.00	3.09
225.00	62.65	44.75	0.001	-30.00	3.07
226.00	62.90	44.50	0.001	-30.00	3.06
227.00	63.43	43.97	0.001	-30.00	3.04
228.00	63.82	43.58	0.001	-30.00	3.03
229.00	63.93	43.47	0.001	-30.00	3.02
230.00	64.56	42.84	0.001	-30.00	3.00
231.00	64.54	42.86	0.001	-30.00	3.00
232.00	64.44	42.96	0.001	-30.00	3.00
233.00	64.60	42.80	0.001	-30.00	3.00
234.00	64.14	43.26	0.001	-30.00	3.01
235.00	64.15	43.25	0.001	-30.00	3.01
236.00	64.09	43.31	0.001	-30.00	3.02
237.00	63.11	44.29	0.001	-30.00	3.06
238.00	61.43	45.97	0.001	-30.00	3.12
239.00	59.56	47.84	0.001	-30.00	3.19
240.00	59.89	47.51	0.001	-30.00	3.18
241.00	61.54	45.86	0.001	-30.00	3.12
242.00	62.14	45.26	0.001	-30.00	3.09
243.00	61.70	45.70	0.001	-30.00	3.11
244.00	60.96	46.44	0.001	-30.00	3.14
245.00	60.96	46.44	0.001	-30.00	3.14
246.00	62.38	45.02	0.001	-30.00	3.08
247.00	62.83	44.57	0.001	-30.00	3.07
248.00	62.86	44.54	0.001	-30.00	3.07
249.00	63.57	43.83	0.001	-30.00	3.04
250.00	64.06	43.34	0.001	-30.00	3.02
251.00	64.67	42.73	0.001	-30.00	2.99
252.00	65.06	42.34	0.001	-30.00	2.98
253.00	65.11	42.29	0.001	-30.00	2.98
254.00	64.72	42.68	0.001	-30.00	2.99
255.00	64.71	42.69	0.001	-30.00	2.99
256.00	65.76	41.64	0.001	-30.00	2.96
257.00	66.33	41.07	0.001	-30.00	2.94
258.00	66.94	40.46	0.001	-30.00	2.92
259.00	67.09	40.31	0.001	-30.00	2.91
260.00	66.97	40.43	0.001	-30.00	2.92
261.00	67.15	40.25	0.001	-30.00	2.91
262.00	67.23	40.17	0.001	-30.00	2.91
263.00	67.94	39.46	0.001	-30.00	2.88
264.00	67.85	39.55	0.001	-30.00	2.89
265.00	67.57	39.83	0.001	-30.00	2.90
266.00	67.18	40.22	0.001	-30.00	2.91
267.00	66.57	40.83	0.001	-30.00	2.93
268.00	66.21	41.19	0.001	-30.00	2.94

Exhibit 11  
Proposed Contour using Three Second Terrain Data

Page 7 of 9  
September 05, 2009

True Radial Bearing (Degrees)	Average Elevation (meters)	Radiation Center Height Above Average Terrain (meters)	Effective Radiated Power (KW)	(dBKW)	Distance to Contour 54.0 dBu F(50,10) (km)
269.00	66.37	41.03	0.001	-30.00	2.94
270.00	66.42	40.98	0.001	-30.00	2.94
271.00	66.85	40.55	0.001	-30.00	2.92
272.00	66.84	40.56	0.001	-30.00	2.92
273.00	67.13	40.27	0.001	-30.00	2.91
274.00	67.80	39.60	0.001	-30.00	2.89
275.00	68.45	38.95	0.001	-30.00	2.87
276.00	68.37	39.03	0.001	-30.00	2.87
277.00	68.17	39.23	0.001	-30.00	2.88
278.00	67.97	39.43	0.001	-30.00	2.88
279.00	67.60	39.80	0.001	-30.00	2.90
280.00	69.32	38.08	0.001	-30.00	2.84
281.00	70.15	37.25	0.001	-30.00	2.81
282.00	70.27	37.13	0.001	-30.00	2.80
283.00	70.44	36.96	0.001	-30.00	2.80
284.00	70.47	36.93	0.001	-30.00	2.80
285.00	70.64	36.76	0.001	-30.00	2.79
286.00	71.37	36.03	0.001	-30.00	2.76
287.00	71.97	35.43	0.001	-30.00	2.74
288.00	71.50	35.90	0.001	-30.00	2.76
289.00	71.34	36.06	0.001	-30.00	2.76
290.00	70.70	36.70	0.001	-30.00	2.79
291.00	69.94	37.46	0.001	-30.00	2.82
292.00	69.39	38.01	0.001	-30.00	2.83
293.00	68.95	38.45	0.001	-30.00	2.85
294.00	68.99	38.41	0.001	-30.00	2.85
295.00	69.46	37.94	0.001	-30.00	2.83
296.00	70.05	37.35	0.001	-30.00	2.81
297.00	69.97	37.43	0.001	-30.00	2.81
298.00	70.15	37.25	0.001	-30.00	2.81
299.00	70.19	37.21	0.001	-30.00	2.81
300.00	70.73	36.67	0.001	-30.00	2.79
301.00	71.40	36.00	0.001	-30.00	2.76
302.00	72.29	35.11	0.001	-30.00	2.73
303.00	73.35	34.05	0.001	-30.00	2.69
304.00	73.11	34.29	0.001	-30.00	2.70
305.00	73.82	33.58	0.001	-30.00	2.67
306.00	75.32	32.08	0.001	-30.00	2.62
307.00	77.48	29.92	0.001	-30.00	2.54
308.00	79.44	27.96	0.001	-30.00	2.54
309.00	81.64	25.76	0.001	-30.00	2.54
310.00	81.97	25.43	0.001	-30.00	2.54
311.00	81.41	25.99	0.001	-30.00	2.54
312.00	82.10	25.30	0.001	-30.00	2.54
313.00	84.34	23.06	0.001	-30.00	2.54
314.00	84.32	23.08	0.001	-30.00	2.54

Exhibit 11  
Proposed Contour using Three Second Terrain Data

Page 8 of 9  
September 05, 2009

True Radial Bearing (Degrees)	Average Elevation (meters)	Radiation Center Height Above Average Terrain (meters)	Effective Radiated Power (KW)	(dBKW)	Distance to Contour 54.0 dBu F(50,10) (km)
315.00	83.47	23.93	0.001	-30.00	2.54
316.00	82.83	24.57	0.001	-30.00	2.54
317.00	82.98	24.42	0.001	-30.00	2.54
318.00	83.24	24.16	0.001	-30.00	2.54
319.00	81.94	25.46	0.001	-30.00	2.54
320.00	82.16	25.24	0.001	-30.00	2.54
321.00	81.90	25.50	0.001	-30.00	2.54
322.00	83.34	24.06	0.001	-30.00	2.54
323.00	84.13	23.27	0.001	-30.00	2.54
324.00	83.91	23.49	0.001	-30.00	2.54
325.00	82.75	24.65	0.001	-30.00	2.54
326.00	81.58	25.82	0.001	-30.00	2.54
327.00	81.27	26.13	0.001	-30.00	2.54
328.00	82.30	25.10	0.001	-30.00	2.54
329.00	82.86	24.54	0.001	-30.00	2.54
330.00	82.32	25.08	0.001	-30.00	2.54
331.00	82.17	25.23	0.001	-30.00	2.54
332.00	83.31	24.09	0.001	-30.00	2.54
333.00	84.11	23.29	0.001	-30.00	2.54
334.00	83.56	23.84	0.001	-30.00	2.54
335.00	83.98	23.42	0.001	-30.00	2.54
336.00	85.36	22.04	0.001	-30.00	2.54
337.00	86.47	20.93	0.001	-30.00	2.54
338.00	86.05	21.35	0.001	-30.00	2.54
339.00	86.69	20.71	0.001	-30.00	2.54
340.00	87.50	19.90	0.001	-30.00	2.54
341.00	87.30	20.10	0.001	-30.00	2.54
342.00	87.15	20.25	0.001	-30.00	2.54
343.00	86.60	20.80	0.001	-30.00	2.54
344.00	85.40	22.00	0.001	-30.00	2.54
345.00	85.81	21.59	0.001	-30.00	2.54
346.00	86.26	21.14	0.001	-30.00	2.54
347.00	84.63	22.77	0.001	-30.00	2.54
348.00	82.81	24.59	0.001	-30.00	2.54
349.00	82.67	24.73	0.001	-30.00	2.54
350.00	82.24	25.16	0.001	-30.00	2.54
351.00	83.47	23.93	0.001	-30.00	2.54
352.00	83.50	23.90	0.001	-30.00	2.54
353.00	84.07	23.33	0.001	-30.00	2.54
354.00	82.20	25.20	0.001	-30.00	2.54
355.00	79.02	28.38	0.001	-30.00	2.54
356.00	76.55	30.85	0.001	-30.00	2.57
357.00	76.28	31.12	0.001	-30.00	2.58
358.00	76.31	31.09	0.001	-30.00	2.58
359.00	75.76	31.64	0.001	-30.00	2.60



Exhibit 11  
Proposed Contour using Three Second Terrain Data

Page 9 of 9  
September 05, 2009

Radiation Center (AGL):	22.0 meters	72.2 feet
Radiation Center (AMSL):	107.4 meters	352.4 feet
Radiation Center (HAAT):	51.2 meters	167.9 feet
Average Terrain (AMSL):	56.2 meters	184.4 feet
Ground AMSL:	85.4 meters	280.2 feet

Peak ERP:	0.0 KW
Frequency:	101 MHz
Antenna:	
Orientation:	0.00°
Downtilt:	0.00°

Area within 54.0 dBu F(50,10) Contour is 34.6685 km